

Escene IV750 Video IP Door Phone



Product Name: Escene IV750 Video IP Door Phone

Manufacturer: Escene

Model Number: IV750

Please Note: This product is no longer available. For alternatives, we recommend looking at the Fanvil or 2N range.

Escene IV750 Video IP Door Phone

The Escene IV750 is an IP65 certified VoIP intercom. The redesigned case is more secure and has a more streamlined look with increased tamper resistance. The IV750 meets the requirements of industry users and is compatible with different platforms, offering users a convenient service. The IV750 intercom has been installed in offices, airports, schools and libraries etc.

Escene IV750 Key Features

- Support embedded or wall-mounted installation.
- High-quality audio and video communication.
- WEB supports multi-language: Chinese, Russian, French, etc.
- 1 SIP accounts, support 3-way conferencing;
- 1*RJ45 standard Ethernet Ports(LAN), Support PoE;
- Indoor open-door interface and external power supply interface;

Escene IV750 - Technical Specifications

Phone Features

- WEB Support Multi-language
- Support 1 Lines Talking
- DND, Hot line
- Auto-answer, 3-way conferencing
- Direct IP call without SIP proxy
- Custom DSS Key(Speed Dial / Intercom,etc)
- Time setting(SNTP/SIP Server/Manual)
- Full-duplex Talking, Dial with digital keypad
- Support switching SIP server & Second server
- WEB Volume control

Advanced Features

- Built-in Indoor-open interface
- Built-in External Power interface
- Built-in Relay

IP PBX System Integration

- DND&Call Transfer

Codes and Voice Features

- Wideband Codec: G.722
- Narrowband codec: G.711μ/A, G.723.1
- G.726, G.729AB,VAD, CNG, AEC, AGC
- Full-duplex

Escene IV750 Video IP Door Phone

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP connection: Proxy mode & Peering Points mode, DNS SRV (RFC3263)
- Redundant server support
- NAT Traversal: STUN mode
- DTMF: In-Band, RFC2833, SIP Info, Auto
- HTTP/HTTPS Web Management
- IP Assignment: Static/DHCP/PPPoE
- Bridge/Router mode for PC port
- Telnet/HTTP/HTTPS server
- DNS client, NAT/DHCP server

Physical Features

- 1*Speaker Key or DSS key
- 1*RJ-45 10/100M(LAN)
- Support PoE: IEEE802.3af class 0
- Embedded or wall-mounted installation
- Power: 12V/1A DC
- Minimized Power:4W
- Maximum Power: 6W
- Operating humidity: -30~60℃
- Storage temperature: up to 60°C
- Relative Humidity:10-90%

Package Features

- Qty/CTN:
- N.W/CTN:
- G.W/CTN:
- Measurement:
- Dimension:
- Carton Meas:

Please Enquire