

Akuvox HCP-R15P IP Phone



Product Name: Akuvox HCP-R15P IP Phone

Manufacturer: -

Model Number: HCP-R15P

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox HCP-R15P IP Phone

The Akuvox HCP-R15P brings high-quatily, cost effective solution to the seniors after age 70. The intuitive user interface of the Akuvox HCP-R15P makes navigation easy and requires minimal training.

Akuvox HCP-R15P Key Features

� 1 Line (Support 1 SIP account)

آزار Support Call Waiting, Call Forward, Call Transfer

تزار Call on Hold, Mute, Auto-answer, Redial, DND

� Local 3-Way Conference

تزير Volume Adjustable, Ring tones Selectable

ï¿1/2 Speed Dial, Hotline

� Network Packet Capture

� Country Ringtone Signal

آزٰ½ Direct IP call

ï¿1/2 Auto Redial, Call Return

ï¿⅓ Dial Plan

آز½ XML Browser

ï¿1/2 Hot Desking

ï¿1/2 Keypad Lock

ï¿⅓ Action URL/URI

īస్ట్ Phonebook (500 groups), Blacklist (100 groups), Call logs (100 entries)

ï¿1/2 5 Remote Phone Book URL Supported

۲¿⅓ LDAP

� Multi-Languages Support

Akuvox HCP-R15P - Technical Specifications

General

� Easy to use

� HD Voice with High Ajustable Volume

ï¿1/2 Boost Button, Adjustable Tone

� Hearing Aid Compatible (HAC)

ï¿1/2 Big Buttons, SOS key

īస్ట్ Up to 10 Wireless Emergency Pendants Supported(Optional)

ï¿⅓ Support PoE

ï¿⅓ Full Compatible with Asterisk, BroadSoft Platform

IP-PBX Features

ï¿⅓ SMS, MWI

ï¿1/2 Music on hold, Intercom

� Call Pickup, Group Call Pickup

تزير Call Recording

� Anonymous Call, Anonymous Call Rejection



Akuvox HCP-R15P IP Phone

Audio Features

ïزر HD Voice with high volume

� Hearing Aid Compatible (HAC)

آذِ1/2 Wideband Codec: G.722

� Narrowband Codec: PCMA, PCMU, G.729, G723_53, G723_63, G726_16, G726_24,

G726_32, G726_40

� VAD, CNG , Echo Canceller

ï¿⅓ Full-Duplex Speakerphone

Security Features

� Support HTTPS (SSL)

� Support SRTP for Voice Data Encryption

� Support Login for Administration

آذِ SIP Over TLS

Network Features

ï¿1/2 SIP V1(RFC2543), V2(RFC3261)

ï¿⅓ Static IP/DHCP for IP conguration

� 3 DTMF modes: In-Band, RFC2833, SIP INFO

� HTTP/HTTPS Web Server for Management

� NTP for Auto Time Setting

ï¿1/2 TFTP/FTP/HTTP/HTTPS Protocols

� 802.1Q VLAN

Administration Features

ii/2 Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP

เี¿½ Dial through IP PBX Using Phone Number

آزٰ Dial through IP PBX Using URL Address

ī¿1/2 Conguration Manamements with web, keypad on the phone, and Auto Provisioning

ï¿⅓ SNMP

ï¿⅓ TR069

Physical Features

ï¿1/2 Audiocodes Chipset

آذِرُ 2.9&Isquo;' 132x64 Graphical LCD with Backlight

آزا 25 Keys (with 1 SOS key, 4 Soft Keys, 3 Image Programmable Keys)

آذً 3 LED Lights (1 Power Light, 1 Handfree Light and 1 SOS Light)

าั¿½ Up to 10 Wireless Emergency Pendants Supported(Optional)

ï¿1/2 RJ9 Handset Jack and Headset Jack

� 2 RJ45 10/100 Ethernet Jacks

آذًا AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

� PoE: IEEE 802.3af

� Giftbox Size:202*239.5*102.5 (mm),weight: 1.19 kg

Please Enquire