

# ZYCOO CooVox-U20-A202 2 FXO IP PBX

200

Product Name: ZYCOO CooVox-U20-A202 2 FXO IP PBX

Manufacturer: ZYCOO

Model Number: CooVox-U20-A202

#### ZYCOO CooVox-U20-A202 2 FXO IP PBX

The ZYCOO U20-A202 is the second generation of Mini IP Phone System launched by ZYCOO, meanwhile it's the first Mobile IP Phone System with the ability to use the GSM module to connect to the mobile network for mobile telephony. CooVox-U20 is a next-generation smart IP PBX System designed and optimized for today's business telecommunication needs. U20-A202 Key Features

آزِ½ Fax to Email

ï¿1/2 2 FXO, Optional 1 GSM Module

� WebRTC/ Web Dial

ī సై Paging and Intercom function strengthens the working efficiency

ï¿1/2 Monitor and Whisper

تز½ HD Voice Codec G.722 for perfect voice quality

ī సైస్ట్ Strong security features protect your system from hacking

U20-A220 is an affordable, scalable, interoperable, secure and reliable solution which provides not only traditional PBX features such as Automated Attendant and Voicemail, but also many advanced features including Remote Extensions, Conference Bridge, Call Recording, Call Detail Records (CDR), Automatic Call Distribution (ACD), Web Dial, Unified Messaging (Voicemail to Email), and many more features.

ZYCOO U20-A202 Technical Specification

Call Features

� Call Back

آزي Call Forward

� Call Hold

� Call Paging and Intercom

� Call Park

ï¿⅓ Call Pickup

� Call Queue

ï¿1/2 Call Recording

ï¿⅓ Call Routing

ï¿⅓ Blind Transfer

ï¿1/2 Attendant Transfer

ï¿⅓ Call Waiting

� One Number Stations

� Caller ID

آز½ Dial by Name

� Music On Hold/Transfer

ï¿1/2 3-Way Conference

ï¿⅓ Video Call

#### **PBX Features**

ï¿1/2 Black List

� BLF (Busy Lamp Field)

� CDR (Call Detailed Record)

� Conference Room (20 Rooms)

� Call Monitoring

� DID (Direct Inward Dialing Number)



- � DISA (Direct Inward System Access)
- ī సై Distinctive Ringtone
- آزٰ½ DND (Do Not Disturb)
- ï¿1/2 DNIS (Dialed Number Identification Service)
- ï¿⅓ Feature Codes
- آزار FOP (Flash Operation Panel) Status Monitoring
- ïز½ Follow Me
- � IVR (Interactive Voice Responses)
- ï¿⅓ Mobility Extension
- � Multi-Language Prompts
- � Multi-Language GUI
- � One Touch Recording
- � Phone Book(LDAP Server)
- � Phone Provisioning
- آزٰ½ Pin Set
- � Record File Download
- � Ringgroup
- ï¿1/2 SIP Register with UDP/TCP/TLS
- تز½ SIP Trunk
- ï¿⅓ Skype for SIP
- � Smart DID
- ï¿1/2 Speed Dial
- ï¿⅓ Spy
- تز½ SRTP (Secure Realtime Transport Protocol)
- � T.38 Fax (Pass-through)
- آز½ Time Based Rule
- ï¿⅓ WebRTC
- تزير Voicemail & Voicemail to Email

# System Capacities

- � Up to 15 Concurrent Calls
- � Up to 20 Conferences
- � Up to 30 IP Phone Registers/Extensions
- រ៉េ2½ Recording: 36,000 mins (.gsm); 4,000 mins (.wav)
- ī¿½ Voicemail: 36,000 mins (.gsm); 4,000 mins (.wav)

## Codecs and Protocols

- าั¿1/2 Audio Codecs: G.722/G.711-Ulaw/G.711-Alaw/
- � G.726/G.729/GSM/SPEEX
- ї¿1/2 Video Codecs: H.261/H.263/H.263+/H.264
- � Protocols: SIP (RFC3261)/IAX2 � DTMF: RFC2833/SIP INFO/In-Band

## **Network Features**

- ï¿⅓ DDNS Client
- � DHCP Server
- ï¿1/2 IPv4/IPv6/IEEE802.1Q
- ï¿1/2 IP Assignment (PPPoE/DHCP/Static)
- ï¿1/2 SNMP v1/v2
- ï¿⅓ TR069
- ï¿⅓ Static Route Table
- � Trouble Shooting (Ping/Traceroute)



# ZYCOO CooVox-U20-A202 2 FXO IP PBX

� VPN Client (N2N/L2TP/PPTP/OpenVPN/IPSec)� VPN Server (PPTP/L2TP/OpenVPN/IPSec)

### Security Features

� Refuse SIP Register DoS � Refuse Abort Invite DoS � Refuse SSH Login DoS

# Logs

� PBX Log � Web Access Log � PBX Debug Log

#### Hardware Interfaces

� 1 Reset Button � 1 Power Interface � 2 Ethernet Interfaces(WAN/LAN)

าง/2 2 Euremet Interfaces(WAN/LAN าง/2 2 Analog Ports (FXO/FXS) าง/2 1 USB 2.0 Interface for Storage

� 1 Console Port

### Hardware Specifications

� Processor: DualCore A7(1GHz) � SDRAM: DDR3 512MB

า๊¿½ Storage: 8GB SD Card(Industry Standard) า๊¿½ Power Supply: Input AC 100~240V, 50/60Hz;

� Output DC 12V/1A

# Environment

� Working Temperature: 0 ~ 40°C� Storage Temperature: -20 ~ 55°C� Humidity: 5 ~ 95% Non-condensing

# **Packings**

� Dimension: 295 × 155 × 65mm

ī¿½ Weight/Unit: 0.8kg ī¿½ Unit /Carton: 10 Units ī¿½ Weight/Carton: 9kg

Price: £297.50

Options available for ZYCOO CooVox-U20-A202 2 FXO IP PBX:

# **Optional GSM Module required?**

Not Required,



# ZYCOO CooVox-U20-A202 2 FXO IP PBX

1GSM Module Required (+£104.60).