



Product Name: Draytek Vigor 2832n ADSL Router

Manufacturer: -

Model Number: V2832N-K

Please Note: This product has been discontinued. For an alternative, please see the Draytek Vigor 2865-K.

Draytek Vigor 2832n ADSL Router - 802.11n Wireless

The DrayTek Vigor 2832n Triple WAN Router is the latest addition to the DrayTek's ADSL Router/Firewall family. Expanding on the popular Vigor 2830 series (winner of the PC Pro wireless router award), the DrayTek Vigor 2832n includes business-class features such as VLAN tagging, Gigabit Ethernet, Triple-WAN and 3G/4G support. This DrayTek Vigor 2832n Router offers truly comprehensive and unmatched ADSL connectivity and security for small businesses, home office, and end users alike.

Draytek Vigor 2832n Features

าั¿½ Supports ADSL, 3G/4G (USB) and Ethernet-based Broadband

آذِرُ 4-WAN Simultaneous: ADSL, Ethernet and USB 3G/4G

� Up to two 3G/4G/LTE USB modems can be used

� IPv6 Ready - See below for feature support

تز½ 802.11n 2.4GHz Wireless LAN (on Vigor2832n)

� DrayTek Firewall with huge flexibility

12.1/2 Temperature Monitoring (optional Thermometer)

Draytek Vigor 2832n - Technical Specifications

General

ï¿⅓ Wireless Guest Portal

� Multiple Private LAN Subnets

า๊¿½ SMS (Text Message) Alert via 3rd party server

� VLANs (Port, 802.1q based & mp; Wireless)

ï¿⅓ Supports DrayTek SmartMonitor software (30 users)

า๊¿½ Content Filtering (by keyword, data type or category)

� LDAP Integration for VPN and user access

� QoS (Layer 2&3, 802.1p & TOS/DCSP)

� Up to 32 VPN tunnels for LAN-to-LAN or teleworkers (PPTP/L2TP/IPsec)

� Up to 10 SSL VPN Tunnels

� VPN Trunk/Backup to remote sites

12.1/2 USB Port for Printer, Logs or 3G/4G Modem

� Optional VigorCare Available

LAN Ports (Switch)

ï¿1/2 4 X Gigabit Ethernet (1000Mb/s) Ports

ï¿1/2 Port-Based VLAN (Inclusive/Exclusive Groups)

� 802.1q VLAN Tagging

USB Ports:

T¿1/2 2x USB 2.0 ports for 3G/4G Modem, Printer, USB storage or USB temperature sensor

آز½ WAN Ports:

ï¿⅓ WAN1: ADSL, RJ11



ī¿½ WAN2: Gigabit Ethernet (1000Mb/s) Ethernet ī¿½ WAN3: USB Port for 3G/4G Cellular Modem ī¿½ WAN4: USB Port for 3G/4G Cellular Modem

Performance:

� Firewall: Up to 300Mb/s � IPSec VPN: Up to 50Mb/s

ADSL Compatibility:

ï¿1/2 ANSI T1.413 Issue2

ï¿1/2 ITU-T G.992.1 G.dmt (ADSL)

ï¿1/2 ITU-T G.992.2 G.lite

� ITU-T G.992.3 ADSL2

� ITU-T G.992.5 ADSL2+

ï¿1/2 Annex L (READSL)

ï¿⅓ Annex A

ï¿⅓ Annex M

าั¿½ ANFP Issue 3 Compliant/Certified (for Annex A & Description of the Compliant (for Annex A & Description of the Compliant)

� DSL Forum: TR-048/67 & amp; TR-100

Load Balance/Failover Features:

� Outbound Policy-Based Load-Balance

ï¿⅓ WAN Connection Fail-over

� BoD (Bandwidth on Demand)

Vigor 2832 ATM Protocols (DSL):

าั¿½ RFC-2684/RFC-1483 Multiple Protocol over AAL5

� RFC-2516 PPP over Ethernet

� RFC-2364 PPP over AAL5

ï¿1/2 PPPoE pass through LAN/WLAN

� PPPoE/PPPoA Relay

� Transparent bridge for MPoA

ī సై Multiple PVC support for Triple Play Applications (up to 8 simultaneous)

ï¿1/2 Support for RFC4638 for MTU up to 1500

Wireless LAN Features ('n' Models Only):

تز½ 802.11n with backward support for 802.11b/g

� 2.4GHz operating frequency (UK channels 1-13)

ī¿½ Multiple SSID : Create up to 4 virtual wireless LANs (independent or joined)

าั¿½ Optional Higher Gain or directional aerials available - Click Here.

ï¿1/2 Active Client list in Web Interface

آذِات Wireless LAN Isolation (from VLAN groups and wired Ethernet interfaces)

تزير 64/128-bit WEP Encryption

� WPA/WPA2 Encryption

ï¿1/2 Switchable Hidden SSID

161/2 Restricted access list for clients (by MAC address)

าั¿½ Time Scheduling (WLAN can be disabled at certain times of day)

ï¿1/2 Access Point Discovery

ī సైస్ట్ WDS (Wireless Distribution system) for WLAN Bridging and Repeating

ï¿1/2 802.1x Radius Authentication



- ï¿1/2 Wireless VLAN
- � Wireless Rate-Control
- 17.1/2 Automatic Power Management
- تزاره 802.11e WMM (Wi-Fi Multimedia)

WAN Protocols (Ethernet):

- ï¿1/2 DHCP Client
- آزٰ½ Static IP
- PPPoE ½⅓
- PPTP ½⅓
- ï¿⅓ BPA

Firewall & Security Features:

- i¿½ CSM (Content Security Management):
- آذًا URL Keyword Filtering Whitelist or Blacklist specific sites or keywords in URLs
- i¿½ Block Websites by category (e.g. Adult, Gambling etc. Subject to subscription)
- ī¿½ Prevent accessing of websites by using their direct IP address (thus URLs only)
- ī¿½ Blocking automatic download of Java applets and ActiveX controls
- ï¿1/2 Blocking of web site cookies
- i¿½ Block HTTP downloads of file types :- Binary Executable: .EXE / .COM / .BAT / .SCR / .PIF-Compressed: .ZIP / .SIT / .ARC / .CAB/. ARJ / .RAR- Multimedia: .MOV / .MP3 / .MPEG / .MPG / .WMV / .WAV / .RAM / .RA / .RM / .AVI / .AU
- 12.1/2 Time Schedules for enabling/disabling the restrictions
- រ៉េ្ឃ Block popular P2P (Peer-to-Peer) file sharing programs
- آذِيًّ Block Instant Messaging programs (e.g. IRC, MSN/Yahoo Messenger etc.)
- ï¿1/2 Multi-NAT, DMZ Host
- าั¿½ Port Redirection and Open Port Configuration
- � Policy-Based Firewall
- ï¿⅓ MAC Address Filter
- าั¿½ SPI (Stateful Packet Inspection) with new FlowTrack Mechanism
- � DoS / DDoS Protection
- ï¿1/2 IP Address Anti-spoofing
- � E-Mail Alert and Logging via Syslog
- ï¿1/2 Bind IP to MAC Address

Bandwidth Management:

- QoS
- ï¿1/2 Guaranteed Bandwidth for VoIP
- 12/2 Class-based Bandwidth Guarantee by User-Defined Traffic Categories
- � Layer 2&3 (802.1p & TOS/DCSP)
- � DiffServ Code Point Classifying
- آذِرُ 4-level Priority for each Direction (Inbound / Outbound)
- ï¿1/2 Bandwidth Borrowed
- า๊ะู่ 1/2 Temporary (5 minutes) Quick Blocking of any LAN Client
- ï¿1/2 Bandwidth / Session Limitation

Network/Router Management:

- i¿1/2 Web-Based User Interface (HTTP / HTTPS)
- ï¿1/2 CLI (Command Line Interface) / Telnet / SSH
- � Administration Access Control
- � Configuration Backup / Restore



- ï¿⅓ Built-in Diagnostic Function
- ï¿1/2 Firmware Upgrade via TFTP / FTP
- � Logging via Syslog
- ï¿1/2 SNMP v3 Management with MIB-II
- � TR-069
- � TR-104

VPN Facilities:

- าั¿½ Up to 32 Concurrent VPN Tunnels (incoming or outgoing)
- រ៉េ 1 2 Up to 10 SSL VPN Tunnels for remote workers
- าั¿½ Tunnelling Protocols: PPTP, IPSec, L2TP, L2TP over IPSec
- ï¿⅓ IPSec Main and Aggressive modes
- آزا IKE Phase 1 DiffieHelman Groups 1,2,5 & amp; 14
- � IKE Phase 2 DiffieHelman Groups 1,2,5 & amp; 14 (will match phase 1 selection)
- � Encryption : MPPE, DES and Hardware-Based AES (128/192/256bits) / DES / 3DES (168bits)
- า๊¿½ Authentication: Hardware-Based MD5, SHA-1 and SHA-256
- าั¿½ IKE Authentication: Pre-shared Key or X.509 Digital Signature
- تزر LAN-to-LAN & Deer IPSec الماركية LAN-to-LAN & Deer IPSec الماركية الما
- ïز½ NAT-Traversal (NAT-T)
- آذِ1/2 Dead Peer Detection (DPD)
- � VPN Pass-Through
- � MOTP (Mobile One Time Password)

Network Features:

- ï¿1/2 DHCP Client / Relay / Server
- � DHCP Option 66 support
- آزِيً Dynamic DNS
- آزٰ NTP Client (Synchronise Router Time)
- า๊ะ่½ Call Scheduling (Enable/Trigger Internet Access by Time)
- ï¿1/2 RADIUS Client
- ï¿⅓ UPnP Support

Routing Protocols:

- ï¿⅓ Static Routing
- ï¿⅓ RIP V2

Operating Requirements:

- าั¿½ Rack Mountable (Optional Vigor RM1 mounting bracket required)
- ï¿⅓ Wall Mountable
- آذِرُ Temperature Operating : 0°C ~ 45°C
- ï¿1/2 Storage : -25°C ~ 70°C
- � Humidity 10% ~ 90% (non-condensing)
- � Power Consumption: 18 Watt Max.
- � Dimensions: L240.96 * W165.07 * H43.96 (mm)
- 12.1/2 Operating Power: DC 15V (via external PSU, supplied)
- � Warranty : Two (2) Years RTB
- ï¿1/2 Power Requirements : 220-240VAC



Please Enquire