



Product Name: Draytek Vigor 2832n ADSL Router Manufacturer: -Model Number: V2832N-K

Please Note: This product has been discontinued. For an alternative, please see the Draytek Vigor 2865-K.

Draytek Vigor 2832n ADSL Router - 802.11n Wireless

The DrayTek Vigor 2832n Triple WAN Router is the latest addition to the DrayTek's ADSL Router/Firewall family. Expanding on the popular Vigor 2830 series (winner of the PC Pro wireless router award), the DrayTek Vigor 2832n includes business-class features such as VLAN tagging, Gigabit Ethernet, Triple-WAN and 3G/4G support. This DrayTek Vigor 2832n Router offers truly comprehensive and unmatched ADSL connectivity and security for small businesses, home office, and end users alike.

Draytek Vigor 2832n Features

ï¿1/2 Supports ADSL, 3G/4G (USB) and Ethernet-based Broadband

i¿1/2 4-WAN Simultaneous: ADSL, Ethernet and USB 3G/4G

ï¿1/2 Up to two 3G/4G/LTE USB modems can be used

i¿1/2 IPv6 Ready - See below for feature support

ï¿1/2 802.11n 2.4GHz Wireless LAN (on Vigor2832n)

- ï¿<sup>1</sup>/<sub>2</sub> DrayTek Firewall with huge flexibility
- � Temperature Monitoring (optional Thermometer)

Draytek Vigor 2832n - Technical Specifications

#### General

ï¿1/2 Wireless Guest Portal

- ï¿1/2 Multiple Private LAN Subnets
- ï¿1/2 SMS (Text Message) Alert via 3rd party server
- ï¿1/2 VLANs (Port, 802.1q based & amp; Wireless)
- ï¿1/2 Supports DrayTek SmartMonitor software (30 users)
- ï¿<sup>1</sup>/<sub>2</sub> Content Filtering (by keyword, data type or category)
- ï¿1/2 LDAP Integration for VPN and user access
- ï¿1/2 QoS (Layer 2&3, 802.1p & TOS/DCSP)
- i¿1/2 Up to 32 VPN tunnels for LAN-to-LAN or teleworkers (PPTP/L2TP/IPsec)
- i¿1/2 Up to 10 SSL VPN Tunnels
- ï¿1/2 VPN Trunk/Backup to remote sites
- ï¿1/2 USB Port for Printer, Logs or 3G/4G Modem
- ï¿1/2 Optional VigorCare Available

LAN Ports (Switch)

i¿¼ 4 X Gigabit Ethernet (1000Mb/s) Ports i¿¼ Port-Based VLAN (Inclusive/Exclusive Groups) i¿¼ 802.1q VLAN Tagging

USB Ports:

i¿½ 2x USB 2.0 ports for 3G/4G Modem, Printer, USB storage or USB temperature sensor i¿½ WAN Ports: i¿½ WAN1: ADSL, RJ11



i¿½ WAN2: Gigabit Ethernet (1000Mb/s) Ethernet i¿½ WAN3: USB Port for 3G/4G Cellular Modem i¿½ WAN4: USB Port for 3G/4G Cellular Modem

Performance:

i¿½ Firewall: Up to 300Mb/s i¿½ IPSec VPN: Up to 50Mb/s

ADSL Compatibility:

 ĩ¿¼ ANSI T1.413 Issue2

 ĩ¿¼ ITU-T G.992.1 G.dmt (ADSL)

 ĩ½ ITU-T G.992.2 G.lite

 ĩ½ ITU-T G.992.3 ADSL2

 ĩ¼ ITU-T G.992.5 ADSL2+

 ĩ¼ Annex L (READSL)

 ĩ½ Annex A

 ĩ½ Annex M

 ĩ½ ANFP Issue 3 Compliant/Certified (for Annex A & amp; Annex M)

 ĩ½ DSL Forum : TR-048/67 & amp; TR-100

Load Balance/Failover Features:

� Outbound Policy-Based Load-Balance
 � WAN Connection Fail-over
 � BoD (Bandwidth on Demand)

Vigor 2832 ATM Protocols (DSL):

ï¿<sup>1</sup>/<sub>2</sub> RFC-2684/RFC-1483 Multiple Protocol over AAL5

ï¿1/2 RFC-2516 PPP over Ethernet

ï¿1/2 RFC-2364 PPP over AAL5

ï¿1/₂ PPPoE pass through LAN/WLAN

ï¿<sup>1</sup>/<sub>2</sub> PPPoE/PPPoA Relay

ï¿<sup>1</sup>/<sub>2</sub> Transparent bridge for MPoA

i¿1/2 Multiple PVC support for Triple Play Applications (up to 8 simultaneous)

 $\ddot{i}_{2}$  Support for RFC4638 for MTU up to 1500

Wireless LAN Features ('n' Models Only):

i¿½ 802.11n with backward support for 802.11b/g
i¿½ 2.4GHz operating frequency (UK channels 1-13)
i¿½ Multiple SSID : Create up to 4 virtual wireless LANs (independent or joined)
i¿½ Optional Higher Gain or directional aerials available - Click Here.
i¿½ Active Client list in Web Interface
i¿½ Wireless LAN Isolation (from VLAN groups and wired Ethernet interfaces)
i¿½ 64/128-bit WEP Encryption
i¿½ WPA/WPA2 Encryption
i¿½ Switchable Hidden SSID
i¿½ Restricted access list for clients (by MAC address)
i¿½ Time Scheduling (WLAN can be disabled at certain times of day)
i¿½ Access Point Discovery
i¿½ WDS (Wireless Distribution system) for WLAN Bridging and Repeating

ï¿1/2 802.1x Radius Authentication



� Wireless VLAN
� Wireless Rate-Control
� Automatic Power Management
� 802.11e WMM (Wi-Fi Multimedia)

WAN Protocols (Ethernet):

� DHCP Client � Static IP � PPPoE � PPTP � BPA

Firewall & amp; Security Features:

ï¿1/2 CSM (Content Security Management):

ïزئ URL Keyword Filtering - Whitelist or Blacklist specific sites or keywords in URLs

i¿1/2 Block Websites by category (e.g. Adult, Gambling etc. Subject to subscription)

ï¿1/2 Prevent accessing of websites by using their direct IP address (thus URLs only)

ï¿1/2 Blocking automatic download of Java applets and ActiveX controls

ï¿1/2 Blocking of web site cookies

� Block HTTP downloads of file types :- Binary Executable: .EXE / .COM / .BAT / .SCR / .PIF-Compressed: .ZIP / .SIT / .ARC / .CAB/. ARJ / .RAR- Multimedia: .MOV / .MP3 / .MPEG / .MPG / .WMV / .WAV / .RAM / .RA / .RM / .AVI / .AU

ïزئ Time Schedules for enabling/disabling the restrictions

ï¿1/2 Block popular P2P (Peer-to-Peer) file sharing programs

ï¿1/2 Block Instant Messaging programs (e.g. IRC, MSN/Yahoo Messenger etc.)

� Multi-NAT, DMZ Host

ï¿1/2 Port Redirection and Open Port Configuration

ï¿1/₂ Policy-Based Firewall

ï¿1/2 MAC Address Filter

ï¿1/2 SPI (Stateful Packet Inspection) with new FlowTrack Mechanism

ï¿1/2 DoS / DDoS Protection

ï¿1/2 IP Address Anti-spoofing

- ï¿1/2 E-Mail Alert and Logging via Syslog
- ï¿1/2 Bind IP to MAC Address

Bandwidth Management:

� QoS

ï¿1/2 Guaranteed Bandwidth for VoIP

ïزار Class-based Bandwidth Guarantee by User-Defined Traffic Categories

ï¿1/2 Layer 2&3 (802.1p & TOS/DCSP)

� DiffServ Code Point Classifying

i¿1/2 4-level Priority for each Direction (Inbound / Outbound)

ï¿1/2 Bandwidth Borrowed

ï¿1/2 Temporary (5 minutes) Quick Blocking of any LAN Client

ï¿1/2 Bandwidth / Session Limitation

Network/Router Management:

ï¿1/2 Web-Based User Interface (HTTP / HTTPS)

ï¿1/2 CLI ( Command Line Interface ) / Telnet / SSH

ï¿<sup>1</sup>/<sub>2</sub> Administration Access Control

ï¿1/2 Configuration Backup / Restore



i¿½ Built-in Diagnostic Function
i¿½ Firmware Upgrade via TFTP / FTP
i¿½ Logging via Syslog
i¿½ SNMP v3 Management with MIB-II
i¿½ TR-069
i¿½ TR-104

**VPN Facilities:** 

ï¿1/2 Up to 32 Concurrent VPN Tunnels (incoming or outgoing)

� Up to 10 SSL VPN Tunnels for remote workers

ï¿1/2 Tunnelling Protocols: PPTP, IPSec, L2TP, L2TP over IPSec

ï¿1/2 IPSec Main and Aggressive modes

� IKE Phase 1 DiffieHelman Groups 1,2,5 & amp; 14

ïزاية IKE Phase 2 DiffieHelman Groups 1,2,5 & amp; 14 (will match phase 1 selection)

ï¿<sup>1</sup>/<sub>2</sub> Encryption : MPPE, DES and Hardware-Based AES (128/192/256bits) / DES / 3DES (168bits)

ïز1/2 Authentication: Hardware-Based MD5, SHA-1 and SHA-256

ïزائ IKE Authentication: Pre-shared Key or X.509 Digital Signature

i¿1/2 LAN-to-LAN & amp; Teleworker-to-LAN connectivityDHCP over IPSec

� NAT-Traversal(NAT-T)

ï¿1/2 Dead Peer Detection (DPD)

� VPN Pass-Through

ï¿<sup>1</sup>/<sub>2</sub> MOTP (Mobile One Time Password)

Network Features:

� DHCP Client / Relay / Server
� DHCP Option 66 support
� Dynamic DNS
� NTP Client (Synchronise Router Time)
� Call Scheduling (Enable/Trigger Internet Access by Time)
� RADIUS Client
� UPnP Support

Routing Protocols:

ii 21/2 Static Routing ii 21/2 RIP V2

**Operating Requirements:** 

i¿1/2 Rack Mountable (Optional Vigor RM1 mounting bracket required)

ï¿1/2 Wall Mountable

ï¿<sup>1</sup>/<sub>2</sub> Temperature Operating : 0&deg;C ~ 45&deg;C

ï¿1/2 Storage : -25°C ~ 70°C

ï¿<sup>1</sup>/<sub>2</sub> Humidity 10% ~ 90% (non-condensing)

ï¿1/2 Power Consumption: 18 Watt Max.

ï¿1/2 Dimensions: L240.96 \* W165.07 \* H43.96 (mm)

ï¿1/2 Operating Power: DC 15V (via external PSU, supplied)

ï¿1/2 Warranty : Two (2) Years RTB

ï¿<sup>1</sup>/<sub>2</sub> Power Requirements : 220-240VAC



Created on: Thursday 18 April, 2024

# Draytek Vigor 2832n ADSL Router

#### **Please Enquire**