

## 2N Indoor Touch (Black) with WiFi



Product Name: 2N Indoor Touch (Black) with WiFi

Manufacturer: -

Model Number: 91378366

Please Note: This product has been discontinued.

### 2N Indoor Touch (Black) with WiFi

The 2N Indoor Touch (Black) with WiFi is a multifunctional communicator, with an Android operating system, provides audio and video communication with 2N® Helios IP intercoms via SIP 2.0 protocol. It is intended for use in interiors, where it is very simply fitted on the wall in a room.

### 2N Indoor Touch (Black) Key Features

- WiFi Support

- 7" touchscreen with energy saving mode

- Multi-coloured LED status indicator

- Reception of a HD picture from the door communicator

- Two-way communication with other units in the network

- Display of missed calls

- Setting "Do not disturb" ("DND") status

- Powered by PoE or external source

- Simple control and easy configuration

It offers simple and intuitive control using a 7" touchscreen with high definition and energy saving mode. An integrated microphone and speaker for effective communication with visitors and multi-coloured LED status indicator, come as standard.

If you are interested in modern design and like to invest in stylish items, the elegant black version 2N Indoor Touch touchscreen is designed especially for you. You will not only appreciate its technical features, but the combination of luxury and cutting-edge workmanship will also give your interior a stylish touch.

### 2N Indoor Touch - Technical Specifications

#### Signalling protocol

- SIP

#### Power

- Type: External power adapter 12V DC 2A / PoE 802.3af

- Power input: 10 W

#### User interface

- Control: High-capacity touchscreen 16:9

- Display size: 7"

- Resolution: 1024x600px 24bpp (16.7 million colours)

- Backlighting: LED with energy-saving mode

- Status indicator: 1x RGB LED (missed calls, energy-saving mode etc.)

#### Operating system

- Android 4.2

## 2N Indoor Touch (Black) with WiFi

### Audio

- Microphone: Integrated
- Speaker: 1x2W integrated

### Video

- Protocol RTSP, MJPEG/HTTP
- Intercom supervision and control: Yes
- IP camera supervision: Yes

### Interface

- LAN: Ethernet 10/100BaseT, RJ45, Recommended cabling Cat5e or higher
- Memory card: SD card (up to 16 GB)
- GPIOs

### Mechanical parameters

- Wall mounting
- Dimensions (W x H x D): 235x165x40 mm
- Weight: 850g
- Operating temperature: 0°C – 60°C
- Operating relative humidity: 10%-90% (non-condensing)
- Storage temperature: -20°C to 70°C

**Price: \$797.13**