

## Escene ES330 VoIP Phone



Product Name: Escene ES330 VoIP Phone

Manufacturer: Escene

Model Number: ES330

Please Note: This product is no longer available. For alternatives, we recommend looking at the Fanvil range.

### Escene ES330 VoIP Phone

The Escene ES330 is a VoIP phone that adopts the DSPG chipset, support G.722 wideband encoding. The ES330 has a backlit LCD screen with 132 x64 resolution, supporting a Chinese display, with 3 SIP accounts and Provide privacy protection.

### Escene ES330 Key Features

- Adopts the DSPG chipset
- 2 100BASE-T Ethernet interfaces, supports POE power supply
- 128 x64 graphic dot matrix display, 5 lines shows (including one line display icon)
- High-fidelity sound quality
- 3 sip accounts, support BLF/BLA, Open VPN

The Escene ES330 supports three way meetings, speed-dial and 12 programmable keys and can be extended to 192 with the Escene Expansion Module. The phone supports POE, VLAN, VPN and is compatible with leading IP PBXs.

### Escene ES330 Technical Specification

#### Characters

- 3 accounts (with double color light), through the Broadsoft, deal, Asterisk certified
- 49 buttons (include 12 programmable keys)
- Support the Tripartite meeting, SMS, voicemail
- Support line sharing (BLA), hold lamp (BLF)
- Supports call waiting and circuit switching
- Multi-Language
- Supports a variety of method of automatic configuration: FTP/TFTP/HTTP Auto Provision/TR069
- automatic upgrades, installation is convenient
- Support TLS/HTTPS encryption protocol
- Support POE, RJ-9 earphone, dual network interface
- Support 6 Extension Unit 192 programmable keys, Meet the operator work fast and efficient, and call monitoring management

### Phone Features

- Support 3 account lines, hotline
- Support calls holding, calls waiting and calls transfer
- Call transfer (blind turn, turn)
- Caller id, redial, mute, don't disturb
- Auto answer, conference
- Speed-dial, SMS, voicemail
- Message lamp, the state signal, the volume control
- IP direct dial
- Custom ring tone
- Phonebook search/ import /export(300), black list
- Call records: dial calls/received calls/miss calls /
- Friendly user interface

## Escene ES330 VoIP Phone

- Support one key quit menu(button c)
- Support one key to view version number and network state(button c)
- Support Hardware diagnostics
- Multi-Language
- Programmable keys
- Most support 6 Extension Unit

### Advanced Features

- Xml phonebook search and import, help users quickly find number and one key to call
- Enterprise phonebook
- LDAP phonebook
- Fuzzy search
- Customizable home screen
- Compatible with the mainstream IP PBX, as: Broadsoft/Avaya/Asterisk
- Intercom, paging
- BLF/BLA
- Intercom, Paging
- Dial plan, call immediately

### Audio Features

- Wideband encoding: G.722
- Narrow band encoding: G. 711.µ/A, G723.1, G.729AB
- Support VAD, CNG, AEC, PLC, AJB, AGC, such as audio processing ribbon coding
- Full duplex speaker, with automatic echo elimination (AEC)

### Network Features

- Support SIP v1(RFC2543), v2(RFC3261)
- Support DNS-SRV&#65288;RFC3263&#65289;
- Support STUN
- 3 DTMF mode: In-band, RFC2833, SIP INFO
- Support the proxy server and point to point connection mode
- Network model: static, DHCP, PPPOE
- Support bridge and router model
- Support TFTP/DHCP/PPPOE terminal
- Support DNS client, built-in NAT/DHCP service
- Login, logout in the web page

### Configuration Manager

- Support FTP/TFTP/HTTPS automatic configuration
- Support 3 configuration models: web page, phone and auto provision
- Support TR069(choice)
- Load default setting, capture package and system log export

### Security

- Support VPN, VLAN QOS(802.1pq)
- LLDP
- Support TLS(Transport Layer Security)
- Support HTTPS(client)
- Support TLS(Transport Layer Security)
- Support information authentication mechanism MD5

## Escene ES330 VoIP Phone

- Support AES encryption protocol
- Support phone locks, support the Root/User level management mode

### Physical Properties

- DSPG embedded chipset
- 128 x64 graphic dot matrix display, 5 lines shows (including one line display icon)
- 49 buttons(include 12 programmable keys)
- One RJ-9(4P4C) handset interface
- One RJ-9(4P4C) headset interface
- Two 100BASE-T Ethernet interfaces
- One RJ-45 Extension interface
- The power adapter: AC 100-240V input, DC 5V/1A output
- Support POE power supply (IEEE 802.3af)
- Power: 6w
- Net weight: 1.2KG
- Bare machine size: 287mm\*214mm\*90mm
- The operating environment humidity: 10-90%
- Working environment temperature: 0~60; ~ -60~0;

### Please Enquire

---