Ubiquiti EdgeSwitch 24 Port 250W Gigabit Switch (ES-24-250W)

Product Name: Ubiquiti EdgeSwitch 24 Port 250W Gigabit Switch (ES-24-250W)

Manufacturer: -

Model Number: ES-24-250W

Please Note:This Ubiquiti product is no longer available from VoIPon. For our full range of Ubiquiti products, please see the website 4Gon.co.uk.

Ubiquiti EdgeSwitch PoE+ Gigabit Switch (ES-24-250W)
The Ubiquiti EdgeSwitch ES- 24 250W is a 24-Port, fully managed, PoE+ Gigabit switch, delivering 250W intelligent switching performance for growing networks. The EdgeSwitch offers an extensive suite of advanced Layer 2 switching features and protocols, and also provides Layer 3 routing capabilities.
Ubiquiti EdgeSwitch ES-24-250W Key Features

ï¿½ Total Non-Blocking Throughput - 26 Gbps
ï¿½ Gigabit RJ45 Ports - 24
ï¿½ SFP Ports - 2
ï¿½ Max. Power Consumption - 250W
ï¿½ Supports POE+ IEEE 802.3at/af and 24V Passive PoE

Optical Fiber BackhaulUbiquiti EdgeSwitch ES-24-250W featurest two SFP ports, which supports uplinks of up to 1 Gbps. Convenient PoE+ SupportUbiquiti EdgeSwitch ES-24-250W also features auto-sensing IEEE 802.3af/at and 24V passive PoE to power multiple devices on the network.Advanced UIThe comprehensive UI is easy to learn and allows administrators to configure and monitor features in a graphical user interface. For advanced users, a Command-Line Interface (CLI) is available through telnet and SSH.

Ubiquiti EdgeSwitch ES-24-250W - Technical Specifications
General

ï¿½ Dimensions: 485 x 43.7 x 285.4 mm (19.09 x 1.72 x 11.24")
ï¿½ Weight: 4.7 kg (10.4 lb)
ï¿½ Total Non-Blocking Throughput: 26 Gbps
ï¿½ Switching Capacity: 52 Gbps
ï¿½ Forwarding Rate: 38.69 Mpps
ï¿½ Max. Power Consumption: - Includes PoE Output: 250W - Excludes PoE Output: 30W
ï¿½ Power Method: 100-240VAC/50-60 Hz, Universal Input
ï¿½ Power Supply: AC/DC, Internal, 250W DC
ï¿½ LEDs Per Port: - RJ45 Data Ports: PoE, Speed/Link/Activity - SFP Data Ports: Speed/Link/Activity
ï¿½ Networking Interfaces: - (24) 10/100/1000 Mbps RJ45 Ethernet Ports - (2) 1 Gbps SFP Ethernet Ports
ï¿½ Management Interface: (1) RJ45 Serial Port, Ethernet In/Out Band
ï¿½ Certifications: - CE - FCC - IC
ï¿½ Rackmount: Yes, 1U High
ï¿½ ESD/EMP Protection: Air: ±24 kV, Contact: ±24 kV
ï¿½ Operating Temperature: -5 to 40° C (23 to 104° F)
ï¿½ Operating Humidity: 5 to 95% Noncondensing
ï¿½ Shock and Vibration: ETSI300-019-1.4 Standard

PoE Per Port

Ubiquiti EdgeSwitch 24 Port 250W Gigabit Switch (ES-24-250W)

ï¿½ PoE Interfaces: - POE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-) - 24VDC Passive PoE (Pins 4, 5+; 7, 8-)
ï¿½ Max. PoE+ Wattage per Port by PSE 34.2W
ï¿½ Voltage Range 802.3at Mode 50–57V
ï¿½ Max. Passive PoE Wattage per Port 17W
ï¿½ 24V Passive PoE Voltage Range 20-27V

Please Enquire

Options available for Ubiquiti EdgeSwitch 24 Port 250W Gigabit Switch (ES-24-250W) :

Need Product Setup / Training / Support?
Not Required,   Required - 1 Hour (+£65.00).

UK Power Cable (free of charge)
Included (PC-180cm-TS-UK).