

Cetis Teledex E200IP 4GSK IP Phone



Product Name: Cetis Teledex E200IP 4GSK IP Phone

Manufacturer: -

Model Number: E200-4GSK

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Cetis Teledex E200IP 4GSK IP Phone

The Cetis Teledex E200IP is an IP phone with 2 SIP lines. The Teledex E Series phones have created an entirely new hotel guestroom telephone category. Originally designed to meet the limited space requirements aboard cruise ships, the E Series phones require less room on the hotel guestroom desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller.

Cetis Teledex E200IP Key Features

- Single or two-line speakerphones
- Up to seven (7) configurable Guest Service Keys
- LCD display with digital clock screen
- PoE Enabled
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- Available in Ash or Black
- ETrim available *Two-line only

Cetis Teledex E200IP - Technical Specifications

General

- Standard Color: Ash and Black
- Footprint (Desk): 45" (1143cm) (w) x 8" (2032cm) (l) x 3.63" (922cm) (d) (max height with desk stand)
- Footprint (Wall): 45" (1143cm) (w) x 8" (2032cm) (l) x 15" (381cm) (d) (depth from wall mount)
- Footprint (ETrim/RediDock): Same as above
- Weight: 20 lbs (09kg)
- Weight (ETrim/Redidock): 12 oz (034kg)
- Frequency: 19 GHz or 18 GHz
- Power: Power over Ethernet (POE) 8023af Compliant
- Power (Cordless): Remote Charging Station includes Handset with Battery & A/C adaptor
- Standby Time (Cordless): 10 days
- Talk Time (Cordless): 6 hours
- Range (Cordless): 100ft (30m)
- Humidity: 65% ± 20%
- Temperature: 77°±F 50°±C (25°±C ± 10°±C)
- Packaging: 10 per carton
- Packaging (RediDock): 20 per carton
- Faceplate Size: Full length
- FCC Specifications: FCC Part 15 Subpart B: 2009
- Safety Standard: UL - 60950–1 2nd edition ADA/HAC

Cetis Teledex E200IP 4GSK IP Phone

1½ Handset: 10 ft (3048m)
1½ Line Cord: RJ14 line cord - 15 ft (45m)
1½ Line Cord (Cordless): RJ45 line cord - 15 ft (45m)
1½ RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

Please Enquire

Options available for Cetis Teledex E200IP 4GSK IP Phone :

Colour

[Ash \(EV022000S04D\)](#), [Black \(EV012000S04D\)](#).