

Ubiquiti UniFi Video Camera G3 - UVC-G3-AF



Product Name: Ubiquiti UniFi Video Camera G3 - UVC-G3-AF

Manufacturer: -

Model Number: UVC-G3-AF

Please Note: This product has been discontinued. Please see the Ubiquiti UniFi Video Camera G3 BULLET (UVC-G3-BULLET).

Please Note: This product is the latest UVC-G3-AF variant . If you also require a system to record, monitor, and manage the UniFi IP CCTV system, please follow a link to the UVC-NVR-2TB.

Ubiquiti UniFi Video Camera G3 -UVC-G3-AF

The Ubiquiti UniFi Video Camera G3 - UVC-G3-AF is an update on Ubiquiti's popular UVC-G3 camera and features a clear 1080p video resolution. The unique balljoint mount design offers flexible 3-axis adjustment, and can be mounted indoors or outdoors. The camera also has infrared LEDs with an automatic IR cut filter for day and night surveillance. Ubiquiti UniFi Video Camera G3 (UVC-G3-AF) Key Features

- 1080p Full HD, 30 FPS
- EFL 3.6 mm, f/1.8
- Outdoor Weather Resistant
- 802.3af PoE or 24V Passive PoE
- Built-in Microphone
- Wall, Ceiling, or Pole Mount

Powerful Software Management Use the UniFi Video mobile app for easy camera management and live streaming from an iOS or Android-based smartphone or tablet. The UniFi Video mobile app is now available in the App Store for iOS and Google Play Store for Android. **Improved Resolution** Featuring an EFL 3.6 mm f/1.8 lens for superior vision, the Ubiquiti UniFi Video Camera G3 (UVC-G3-AF) provides 1080p HD resolution at 30 FPS - that's an impressive 360p more than its G2 predecessor! **Hybrid Cloud Technology** Hybrid Cloud Technology combines the best of local and cloud management: secure, local storage, and convenient remote access with streaming privacy & no licensing or maintenance fees.

Ubiquiti UniFi Video Camera G3 (UVC-G3-AF) - Technical Specifications

General

- Dimensions: 75 x 140 mm (2.95 x 5.51")
- Weight: 300 g (10.58 oz)
- Enclosure: Injection-Molded Polycarbonate and Die-Cast Aluminum
- Networking Interface: (1) 10/100 Ethernet Port
- Sensor: 1/3" 4-Megapixel HDR Sensor
- Lens: EFL 3.6 mm, f/1.8
- Night Mode: IR LEDs with Mechanical IR Cut Filter
- Microphone: Yes
- Button: Factory Reset Button
- Power Method: 802.3af PoE or 24V Passive PoE
- Power Supply 802.3af PoE Switch
- Maximum Power Consumption:

- Standalone: 4W
- With Optional IR Extender: 9W

Ubiquiti UniFi Video Camera G3 - UVC-G3-AF

• Mounting: Wall/Ceiling/Pole
• Operating Temperature: -30 to 70°C (-22 to 158°F)
• Operating Humidity: 20 - 90% Noncondensing

Video

• Video Compression: H.264
• Resolution: 1080p Full HD (1920x1080)
• Maximum Frame Rate: 30 FPS
• Image Settings: Brightness, Contrast, Sharpness, Saturation, Noise Reduction, 50/60 Hz

Additional Specifications

• Viewing Angle:

• Before Lens Correction: 85° (H), 44.8° (V), 98.1° (D)
• After Lens Correction: 72° (H), 42.9° (V), 80.4° (D)

• Supported UniFi Video Version: UniFi Video 3.8 (or Newer)
• UniFi Video System Requirements: 64-bit Microsoft Windows 10/8/7, Ubuntu 14.04 or 16.04, or Debian 7.0 System with an Intel or Compatible 1.86 GHz (or Above) Processor and a Minimum of 4 GB RAM

Please Enquire
