

## Fanvil H3 VoIP Phone



Product Name: Fanvil H3 VoIP Phone

Manufacturer: Fanvil

Model Number: H3

Please Note: Customise the front panel of the phone free of charge for orders of 200 or more. For smaller orders, there will be a fee of £200. Lead time of 14 days applies. Contact us for more information.

### Fanvil H3 Hotel VoIP Phone

The Fanvil H3 is an IP hotel phone with HD voice and 6 programmable soft keys. The H3 has a full duplex, hands free speaker phone with echo cancellation, and many more standard phone features such as call transfer, call holding, and call waiting. This product also comes with a power supply included.

### Fanvil H3 VoIP Phone Key Features

- 1 SIP line
- 1 USB Port for Phone Charging
- 6 Programmable Keys for Speed Dial Functions
- Support PoE
- Indicator Light
- Call hold, Redial, Call Transfer, Hotline, Voice Mail etc.
- Easy installation and configuration
- High Interoperability - Compatible with major platforms: 3CX, Broadsoft, Elastix, Asterisk, Xorcom, etc.

**Elegant Outlook** Fanvil H3 is the IP Phone designed for hotels. With stylish, fresh appearance, excellent voice quality, and matching integrated communication platform, it can become a new generation of hotel intelligent terminal equipment.

**6 Programmable Soft Keys** The H3 comes with 6 programmable soft keys for maximum flexibility. Choose from a wide range of options, such as housekeeping, ticketing, switchboard, or room service.

### Fanvil H3 Technical Specification

#### Generic

- 1 SIP Line
- POE Enabled
- Handset / Hands-free mode
- Intelligent DSS Keys (speed dial key)
- Desktop
- Optional External Power Supply

### Call Features

- Call out / Answer
- Mute / Unmute (microphone)
- Call Hold / Resume
- Call Waiting
- Call Transfer (Attended/Unattended)
- Speed dial
- Intercom
- Redial
- Voice Message (on server)

## Fanvil H3 VoIP Phone

- Hot Line
- Hot desking

### Phone Features

- Call logs with missed calls/ incoming calls/ outgoing calls
- Max support 600 records(web)
- Dial without registration
- LED light
- Programmable DSS keys
- Custom LCD display text and logo(Only support for H5)
- Action URL / Active URI
- Web dial

### Audio

- Audio CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB, G.722
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band - DTMF(RFC2833) / SIP INFO

### Networking

- 10/100Mbps Ethernet, dual bridged port for PC bypass
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- QoS

### Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- PPPoE
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

### Deployment & Maintenance

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069
- Web Management Portal
- Web-based Packet-dump
- Configuration Export / Import
- Firmware Upgrade

## Fanvil H3 VoIP Phone

1/2 Syslog

### Physical Specifications

1/2 Keypad: 26 keys, including:- 6 DSS Key- 4 Function keys (Hold, Call Transfer, Redial, MWI)- 12 Standard Phone Digits keys- 3 Volume Control keys, Lower/Increase/Mute (Microphone)- 1 Hands-free

1/2 HD Handset (RJ9) x1

1/2 Standard RJ9 Handset Wire x1

1/2 1.5M CAT5 Ethernet Cable x1

1/2 RJ9 Port x1: Handset x1

1/2 RJ45 Port x2: Network x1, PC x1 (Bridged to Network)

1/2 USB Port x1: Standard A, Only used for mobile phone charging

1/2 DC Power Input: 5V / 1A

1/2 Power Consumption: Idle 1.8W~2.5W, Peak 3W~4.5W

1/2 Working Temperature: 0~40°C

1/2 Working Humidity: 10~95%

1/2 Installation: Desktop Stand

1/2 Colour: Black/White

1/2 Device Dimensions: 151.7x193.2x131.7mm

**Price: £57.80**

Options available for Fanvil H3 VoIP Phone :

### Need Product Setup / Training / Support?

Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00), Not Required.

### Power supply unit

Not Required, UK-PSU-5V (+£7.10).