

OpenVox FD182 8 E1 / T1 / BRI ports and 2 Ethernet ports failover appliance



Product Name: OpenVox FD182 8 E1 / T1 / BRI ports and 2 Ethernet ports failover appliance Manufacturer: OpenVox

Model Number: FD182

OpenVox FD182 8 E1 / T1 / BRI ports and 2 Ethernet ports failover appliance The OpenVox FD182 is a 8-port E1/T1/BRI interface and 2 Ethernet ports failover appliance. It can better protect the unpredictable problems happen to the Asterisk PBX. It will provide an effective way to backup the Asterisk PBX when undesirable changes are detected (often when Asterisk fails or power-off of the system).OpenVox FD182 Features

ï¿1/2 Support up to 8 Port Digital T1/E1/PRI/BRI + 2 Ethernet Port

 $\ddot{\imath}_{2}\dot{\prime}_{2}$ Support multiple FD182 devices in one system

i¿1/2 Support all compatible PRI and BRI interface cards

ï¿1/2 Unique highlight:1 USB power supply

ï¿1/2 Five Year Warranty

The OpenVox FD182 is controlled through an Asterisk loadable module res_failover.so. This module keeps sending "running" signal to redundant server when Asterisk is running. Once Asterisk is down or system power is cut off, the module will not be able to send out the "running" signal to FD182 and thus it will automatically switch to the redundant server.

OpenVox FD182 8 E1 / T1 / BRI ports and 2 Ethernet ports failover appliance - Technical Specifications

Features

ï¿¹/₂ 8 E1 / T1 / BRI ports and 2 Ethernet ports

i¿1/2 Easy installation; uses USB to connect computer or server

ï¿1/2 Industry standard USB type B connector

- ï¿1/2 USB 2.0 and 1.1 compliant
- ï¿1/2 Two power supply indicator lights
- i¿1/2 Support the BRI or PRI circuit connection
- ï¿1/2 Supports multiple FD182 devices in one system
- ï¿1/2 Rack/Wall Mountable
- ï¿1/2 Supports hardware watchdog
- ï¿1/2 Low power consumption, takes power from USB bus
- ï¿1/2 Fully supports Asterisk (Version1.2/1.4/1.6)

ï¿¹/₂ Dimension: 44cm*6.6cm*4.5cm

ï¿1/2 Weight: 1658g

Price: £1,315.00