

OpenVox A800P PCI Asterisk Cards



Product Name: OpenVox A800P PCI Asterisk Cards

Manufacturer: -

Model Number: A800P

Please Note: This product has been discontinued. Please see the OpenVox A810P PCI Asterisk Analog Card for an alternative.

OpenVox A800P PCI Asterisk Cards

Please Note: This product may have a lead time of up to 1-2 weeks. Please call 0330 088 0195 and speak to our sales team who can confirm the current available stock for your requirement.
Please Note: The OpenVox A800P contains 8 module banks. Each bank supports one analog interface. The module banks may be filled with up to 8 FXO or FXS modules enabling the creation of any combination of ports. Please select your required modules above.

The OpenVox A800P is a PCI analog card. The OpenVox A800P can be used for connecting analog telephones and analog POTS lines through a PC. It supports combinations of FXS and/or FXO modules for a total of 8 lines.

Key Features and benefits of the OpenVox A800P

- 1/2 Caller ID and Call Waiting Caller ID
- 1/2 ADSI Telephones
- 1/2 Loopstart Signaling Support
- 1/2 Up to 8 Simultaneous PSTN Calls (Per PCIe Slot)
- 1/2 Interchangeable FXS and FXO modules
- 1/2 Scalable: Just add additional cards to extend the system.

The OpenVox A800P delivers great voice quality in the telephony systems. With interchangeable FXS/FXO modules, it can eliminate the requirement for separate channel banks or access gateways. The A800P contains 8 module banks. Each bank supports one analog interface. The module banks may be filled with up to 8 FXO or FXS modules enabling the creation of any combination of ports. Scaling of an analog card solution is accomplished by simply adding additional cards.

Technical Specifications

- 1/2 Up to 8 ports through a combination of FXS and FXO modules
- 1/2 8 RJ-11 interfaces on a single PCI bracket
- 1/2 Firmware accelerate I/O access to achieve high stability
- 1/2 Channel Bank Replacement / Alternative
- 1/2 Small Office Home Office (SOHO) applications
- 1/2 Small and Medium Business (SMB) applications
- 1/2 Gateway Termination to analog telephones/lines

Power

- 1/2 7W Minimum, 37W Maximum at 3.3V or 5V.

Operating temperature

- 1/2 0°C to 50°C

Storage temperature

OpenVox A800P PCI Asterisk Cards

ï¿½ -40°C to 125°C

Interface

ï¿½ PCI

Dimension

ï¿½ 246.7mm*106.7mm*16mm

Minimum Hardware Requirement

ï¿½ 800-Mhz Pentium III

ï¿½ 128MB RAM

Operating Systems

ï¿½ Linux (all versions, releases and distributions from 1.0 up)

Certifications

ï¿½ RoHS Compliant

ï¿½ Certificates: FCC, CE and LVD

ï¿½ Certified by trixbox CE and Elastix

Weight

ï¿½ 133g

Price: \$47.74

Options available for OpenVox A800P PCI Asterisk Cards :

Module 1

Not Required, [OpenVox FXO100 Module \(+\\$53.52\)](#), [OpenVox FXS100 Module \(+\\$53.52\)](#).

Module 2

Not Required, [OpenVox FXO100 Module \(+\\$53.52\)](#), [OpenVox FXS100 Module \(+\\$53.52\)](#).

Module 3

Not Required, [OpenVox FXS100 Module \(+\\$53.52\)](#), [OpenVox FXO100 Module \(+\\$53.52\)](#).

Module 4

Not Required, [OpenVox FXO100 Module \(+\\$53.52\)](#), [OpenVox FXS100 Module \(+\\$53.52\)](#).

Module 5

Not Required, [OpenVox FXO100 Module \(+\\$53.52\)](#), [OpenVox FXS100 Module \(+\\$53.52\)](#).

Module 6

Not Required, [OpenVox FXO100 Module \(+\\$53.52\)](#), [OpenVox FXS100 Module \(+\\$53.52\)](#).

Module 7

OpenVox A800P PCI Asterisk Cards

Not Required, [OpenVox FXO100 Module \(+\\$53.52\)](#), [OpenVox FXS100 Module \(+\\$53.52\)](#).

Module 8

Not Required, [OpenVox FXO100 Module \(+\\$53.52\)](#), [OpenVox FXS100 Module \(+\\$53.52\)](#).