

Fanvil X3G PoE Gigabit VoIP Phone



Product Name: Fanvil X3G PoE Gigabit VoIP Phone

Manufacturer: -

Model Number: X3G

Please Note: This product has been discontinued. Please see the Fanvil X3U.

Please Note: This product does not come with a power supply. If you wish to purchase one, please select this option from the menu box above.

Fanvil X3G PoE Gigabit VoIP Phone

The Fanvil X3G PoE VoIP Phone is a feature-rich and affordable IP phone. The X3G is certified to work with major PBX platforms such as: 3CX, Broadsoft, Elastix, Asterisk, Xorcom, and many more. The PoE enabled X3G also features 2 SIP lines, a 2.4 inch (320 x 240) LCD colour screen, and supports Gigabit.

Fanvil X3G VoIP Phone Key Features

- 2 SIP lines
- 2.4 inch (320 x 240) LCD colour screen
- Gigabit, PoE enabled
- HD voice, full duplex speaker
- EHS support for headsets
- RJ9 headset port
- Desktop/wall mount install options
- Secure and complete provisioning protocols
- High interoperability & compatible with major platforms: 3CX, Elastix, Asterisk, Xorcom, etc.

Supports EHS Wireless Headsets The X3G supports EHS wireless headsets, making a professional enterprise VoIP phone. **Web Page with Mobile Phone** Simply scan the QR code on your X3G screen to get web page access on your mobile, anytime, anywhere!

Fanvil X3S/P IP Phone - Technical Specifications

Generic

- 2 SIP Lines
- HD Voice
- POE Enabled
- Handset (HS) / Hands-free(HF) / Headphone(HP) mode (EHS support for Plantronics headsets)
- Desktop / Wall-mount installation
- Economical and Environmental friendly package
- Industrial Standard Certifications: CE/FCC

Call Features

- Call out / answer / reject
- Mute / unmute (microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Call Forwarding (Always/Busy/No Answer)

Fanvil X3G PoE Gigabit VoIP Phone

- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (depending on server)
- Redial
- Do-Not-Disturb (per line / per phone)
- Auto-Answering (per line)
- Voice Message (on server)
- Local 3-way Conference
- Hot Line

Phone Features

- Phone Accessibility Control by User PIN
- Intelligent Phonebook (up to 500 entries total)
- Remote Phonebook (XML/LDAP)
- Intelligent Contact Number Matching / Filtering
- Call log (300 entries total, in/out/missed)
- Voice Message Waiting Indication (VMWI)
- Network Time Synchronisation
- Multi-language support in screen and web UI: English, Chinese (Traditional/Simplified), Japanese, Russian, Italian, Turkish, Germany, Dutch, Spanish, Hebrew, Polish, French etc.

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0~7KHz Frequency Response)
- Wideband ADC/DAC 16KHz Sampling
- Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB
- Wideband CODEC: G.722
- Full-duplex Acoustic Echo Canceller (AEC) & Hands-free Mode, 96ms tail-length
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band & DTMF-Relay (RFC2833) / SIP INFO

Networking

- Physical: 10/100Mbps(X3S/X3SP), 10/100/1000Mbps(X3G) Ethernet, dual bridged port for PC bypass
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP (Basic Unencrypted) / OpenVPN
- VLAN
- QoS

Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- PPPoE
- 802.1x
- L2TP (Basic Unencrypted)
- OpenVPN
- SNTP

Fanvil X3G PoE Gigabit VoIP Phone

iç½ FTP/TFTP
iç½ HTTP/HTTPS
iç½ TR069

RFCs

iç½ 354/1321/1350/1769/1889/1890/2131/2132/ 2616/2617/2661/2833/2976/3261/3262/3263/
3264/3265/3268/3311/ 3489/3711/4346/4566/ 5630/5865

Deployment & Maintenance

iç½ Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP/OPT66/SIP PNP/TR069
iç½ Web Management Portal
iç½ Web-based Packet Dump
iç½ Configuration Backup/Restore
iç½ Auto/Manual Online Software Upgrade
iç½ Syslog

Physical Specifications

iç½ LCD x1: 2.4 inch (320 x 240) colour screen LCD
iç½ Keypad: 32 keys, including: - 4 Soft-keys - 12 Standard Phone Digits keys - 5 Navigation keys
- 2 Line keys with tri-colour LED - 5 Function key - 3 Volume Control keys, Up/Down/Mute
(Microphone) - 1 Hands-free
iç½ HD Hands-free Speaker (0 ~ 7KHz) x1
iç½ HD Hands-free Microphone (0 ~ 7KHz) x1
iç½ HD Handset (RJ9) x1
iç½ Standard RJ9 Handset Wire x1
iç½ 1.5M CAT5 Ethernet Cable x1
iç½ RJ9 Phone Jacket x2: Handset x1, Headphone x1
iç½ RJ45 Ethernet Jacket x2: Network x1 (802.3AF POE Class 1 Enabled), PC x1 (Bridged to Network)
iç½ Main Chipset: Broadcom
iç½ DC Power Input: 5V/600mA
iç½ Working Temperature: 0 ~ 40℃
iç½ Working Humidity: 10 ~ 65%
iç½ Dual-Functional Back Rack x1: Desktop Stand / Wall-mount
iç½ Colour: Black
iç½ Package Dimensions: 275x215x62mm (W x H x L)

Please Enquire

Options available for Fanvil X3G PoE Gigabit VoIP Phone :

Headset

Plantronics CS520 binaural headset and adapter cable (+£265.89), Fanvil HT202 binaural wideband headset (+£36.70), Jabra Pro 920 headset and adapter (+£143.40), - Not Required -, JPL Connect-1 monaural headset and disconnect cord (+£65.00), Plantronics CS540 monaural headset and adapter cable (+£220.00), Fanvil HT201 monaural wideband headset (+£26.20), JPLConnect-2 binaural headset and disconnect cord (+£76.25).

Fanvil X3G PoE Gigabit VoIP Phone

Power supply unit

Not required, [UK-PSU-5V \(+£3.99\)](#).