

Fanvil X4 Enterprise IP Phone



Product Name: Fanvil X4 Enterprise IP Phone

Manufacturer: -

Model Number: X4

Please Note: This product has been discontinued. For an alternative, please see the Fanvil X4U.

Fanvil X4 Enterprise IP Phone

The Fanvil X4 IP Phone is a high-end enterprise desktop phone with an intelligent DSS key-mapping LCD, which increases the users' productivity at an affordable price.

Fanvil X4 Key Features

- DSS key-mapping LCD colour screen & 6 DSS keys

- 2.8 inch (320 x 240) LCD colour screen

- Fast Ethernet with PoE enabled

- Elegant design with environmentally friendly packaging

- High interoperability & compatible with major platforms: 3CX, Asterisk, Broadsoft, Elastix, Zycoo, etc.

Supports EHS Wireless Headsets

Fanvil's X4 IP phone supports EHS wireless headsets, making a professional enterprise VoIP phone.

Two LCD Screens

The X4 boasts 2 colour LCD screens, with 6 DSS keys corresponding to the LCD display.

High Functionality

Thanks to its versatility, the X4 fulfils all business needs - improving overall business efficiency.

Fanvil X4 Technical Specification

Generic

- 4 SIP Lines

- HD Voice

- PoE Enabled

- 2 LCD Colour Screens (Main + DSS)

- Handset(HS) / Hands-free (HF) / Headphone(HP) mode (EHS support for Plantronics headsets)

- Intelligent DSS Keys

- Desktop / Wall-mount installation

- Optional External Power Supply

- Economical and Environmental friendly package

- Industrial Standard Certifications: CE/FCC

Call Features

- Call out / answer / reject

- Mute / Unmute (microphone)

- Call Hold / Resume

- Call Waiting

- Intercom

- Caller ID Display

- Speed Dial

- Anonymous Call (Hide Caller ID)

Fanvil X4 Enterprise IP Phone

- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (depending on server)
- Redial/Auto-Redial
- Do-Not-Disturb (per line / per phone)
- Auto-Answering (per line)
- Voice Message (on server)
- Local 3-way Conference
- Hot Line
- Hot-Desking

Phone Features

- Phonebook (500 entries)
- Remote Phonebook (XML/LDAP)
- Call log (100 entries, in/out/missed)
- Black/White List Call Filtering
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronisation
- Action URL / Active URI

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ſġ7KHz Frequency Response)
- Wideband ADC/DAC 16KHz Sampling
- Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB
- Wideband CODEC: G.722
- Full-duplex Acoustic Echo Canceller (AEC) – Hands-free Mode, 96ms tail-length
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay (RFC2833) / SIP INFO

Networking

- Physical: 10/100Mbps(X4), 10/100/1000Mbps (X4G) Ethernet, dual bridged port for PC bypass
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP (Basic Unencrypted) / OpenVPN
- VLAN
- QoS

Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- PPPoE
- 802.1x
- L2TP (Basic Unencrypted)

Fanvil X4 Enterprise IP Phone

• OpenVPN
• SNTP
• FTP/TFTP
• HTTP/HTTPS
• TR069

RFCs

• 354/1321/1350/1769/1889/1890/2131/2132/2616/2617/2661/2833/2976
• 3261/3262/3263/3264/3265/3268/3311/3489/3711/4346/4566/5630/ 5865

Deployment & Maintenance

• Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069
• Web Management Portal
• Web-based Packet Dump
• Configuration Export / Import
• Phonebook Import/Export
• Firmware Upgrade
• Syslog

Physical Specifications

• Main LCD x1: 2.8 inch (320x240) LCD colour screen
• DSS key-mapping LCD x1: LCD colour screen
• Keypad: 38 keys, including: - 4 Soft-keys - 6 Function keys - 5 Navigation keys - 12 Standard Phone Digits keys - 3 Volume Control keys, Up/Down/Mute(Microphone) - 1 Hands-free key - 6 DSS Keys with tri-colour LED - 1 Page-Jump/Configuration (PJC) key
• HD Hands-free Speaker (0 ~ 7KHz) x1
• HD Hands-free Microphone (0 ~ 7KHz) x1

• HD Handset (RJ9) x1
• Standard RJ9 Handset Wire x1

• 1.5M CAT5 Ethernet Cable x1 & RJ9 Phone Jacket x2: Handset x1, Headphone x1
• RJ45 Ethernet Jacket x2: Network x1 (802.3AF POE Class 2 Enabled), PC x1 (Bridged to Network)
• Main Chipset: Broadcom
• DC Power Input: 5V/1A
• Power Consumption: (X4) Idle ~ 1.3W, Peak ~ 4.3W (X4G) Idle ~ 1.7W, Peak ~ 5.7W
• Working Temperature: 0 ~ 40°C
• Working Humidity: 10 ~ 65%
• Dual-Functional Back Rack x1: Desktop Stand / Wall-mount
• Colour: Black
• Package Dimensions: 285 x 270 x 65mm (W x H x L)

Please Enquire

Fanvil X4 Enterprise IP Phone

Options available for Fanvil X4 Enterprise IP Phone :

Headset

Fanvil HT202 binaural wideband headset (+£33.00), - Not Required -, Jabra Pro 920 headset and adapter (+£143.40), Fanvil HT201 monaural wideband headset (+£20.00).

Need Product Setup / Training / Support?

Required - 30 minutes (+£40.00), Not Required, Required - 1 Hour (+£65.00).

Power supply unit

Not required, UK-PSU-5V (+£7.10).