

Fanvil X4G 4 Line Enterprise Gigabit IP Phone



Product Name: Fanvil X4G 4 Line Enterprise Gigabit IP Phone

Manufacturer: -

Model Number: X4G

Please Note: This product has been discontinued. Please see the Fanvil X4U Enterprise IP Phone as an alternative.

Please Note: This product does not come with a power supply. If you wish to purchase one, please select this option from the menu box above.

Fanvil X4G Enterprise IP Phone

The Fanvil X4G IP Phone is a high-end enterprise desktop phone with an intelligent DSS key-mapping LCD, which increases the users' productivity at an affordable price.

Fanvil X4G Key Features

- DSS key-mapping LCD colour screen & 6 DSS keys

- 2.8 inch (320 x 240) LCD colour screen

- Fast / Gigabit Ethernet with PoE enabled

- Elegant design with environmentally friendly packaging

- High interoperability & compatible with major platforms: 3CX, Asterisk, Broadsoft, Elastix, Zycoo, etc.

Supports EHS Wireless Headsets

Fanvil's X4G IP phone supports EHS wireless headsets, making a professional enterprise VoIP phone.

Two LCD Screens

The X4G boasts 2 colour LCD screens, with 6 DSS keys corresponding to the LCD display.

High Functionality

Thanks to its versatility, the X4G fulfils all business needs - improving overall business efficiency.

Fanvil X4G Technical Specification

Generic

- 4 SIP Lines

- HD Voice

- PoE Enabled

- 2 LCD Colour Screens (Main + DSS)

- Handset(HS) / Hands-free (HF) / Headphone(HP) mode (EHS support for Plantronics headsets)

- Intelligent DSS Keys

- Desktop / Wall-mount installation

- Optional External Power Supply

- Economical and Environmental friendly package

- Industrial Standard Certifications: CE/FCC

Call Features

- Call out / answer / reject

- Mute / Unmute (microphone)

Fanvil X4G 4 Line Enterprise Gigabit IP Phone

- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (depending on server)
- Redial/Auto-Redial
- Do-Not-Disturb (per line / per phone)
- Auto-Answering (per line)
- Voice Message (on server)
- Local 3-way Conference
- Hot Line
- Hot-Desking

Phone Features

- Phonebook (500 entries)
- Remote Phonebook (XML/LDAP)
- Call log (100 entries, in/out/missed)
- Black/White List Call Filtering
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronisation
- Action URL / Active URI

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- Wideband ADC/DAC 16KHz Sampling
- Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB
- Wideband CODEC: G.722
- Full-duplex Acoustic Echo Cancellation (AEC) – Hands-free Mode, 96ms tail-length
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay (RFC2833) / SIP INFO

Networking

- Physical: 10/100Mbps(X4), 10/100/1000Mbps (X4G) Ethernet, dual bridged port for PC bypass
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP (Basic Unencrypted) / OpenVPN
- VLAN
- QoS

Protocols

- SIP2.0 over UDP/TCP/TLS

Fanvil X4G 4 Line Enterprise Gigabit IP Phone

iC½ RTP/RTCP/SRTP
 iC½ STUN
 iC½ DHCP
 iC½ PPPoE
 iC½ 802.1x
 iC½ L2TP (Basic Unencrypted)
 iC½ OpenVPN
 iC½ SNTP
 iC½ FTP/TFTP
 iC½ HTTP/HTTPS
 iC½ TR069

RFCs

iC½ 354/1321/1350/1769/1889/1890/2131/2132/2616/2617/2661/2833/2976
 /3261/3262/3263/3264/3265/3268/3311/3489/3711/4346/4566/5630/ 5865

Deployment & Maintenance

iC½ Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069
 iC½ Web Management Portal
 iC½ Web-based Packet Dump
 iC½ Configuration Export / Import
 iC½ Phonebook Import/Export
 iC½ Firmware Upgrade
 iC½ Syslog

Physical Specifications

iC½ Main LCD x1: 2.8 inch (320x240) LCD colour screen
 iC½ DSS key-mapping LCD x1: LCD colour screen
 iC½ Keypad: 38 keys, including: - 4 Soft-keys - 6 Function keys - 5 Navigation keys - 12 Standard Phone Digits keys - 3 Volume Control keys, Up/Down/Mute(Microphone) - 1 Hands-free key - 6 DSS Keys with tri-colour LED - 1 Page-Jump/Configuration (PJC) key
 iC½ HD Hands-free Speaker (0 ſġ7KHz) x1
 iC½ HD Hands-free Microphone (0 ſġ7KHz) x1

iC½ HD Handset (RJ9) x1
 iC½ Standard RJ9 Handset Wire x1

iC½ 1.5M CAT5 Ethernet Cable x1 ͻRJ9 Phone Jacket x2: Handset x1, Headphone x1
 iC½ RJ45 Ethernet Jacket x2: Network x1 (802.3AF POE Class 2 Enabled), PC x1 (Bridged to Network)
 iC½ Main Chipset: Broadcom
 iC½ DC Power Input: 5V/1A
 iC½ Power Consumption: (X4) Idle – ſ 1.3W, Peak – ſ4.3W (X4G) Idle – ſ 1.7W, Peak – ſ5.7W
 iC½ Working Temperature: 0 ~ 40ɗ
 iC½ Working Humidity: 10 ſ 65%
 iC½ Dual-Functional Back Rack x1: Desktop Stand / Wall-mount
 iC½ Colour: Black
 iC½ Package Dimensions: 285 x 270 x 65mm (W x H x L)

Fanvil X4G 4 Line Enterprise Gigabit IP Phone

Please Enquire

Options available for Fanvil X4G 4 Line Enterprise Gigabit IP Phone :

Headset

Fanvil HT202 binaural wideband headset (+£36.70), Jabra Pro 920 headset and adapter (+£143.40), - Not Required -, JPL Connect-1 monaural headset and disconnect cord (+£65.00), Plantronics CS540 monaural headset and adapter cable (+£220.00), Fanvil HT201 monaural wideband headset (+£26.20), JPLConnect-2 binaural headset and disconnect cord (+£76.25), Plantronics CS520 binaural headset and adapter cable (+£265.89).

Power supply unit

Not required, UK-PSU-5V (+£3.99).