

BeroNet SB Gateway with 2BRI and 2FXO



Product Name: BeroNet SB Gateway with 2BRI and 2FXO

Manufacturer: beroNet

Model Number: BFSB2S02XO

BeroNet SB Gateway with 2BRI and 2FXO BFSB2S02XO

The BeroNet SB Gateway with 2BRI and 2FXO is designed for the SOHO area, connecting ISDN, VoIP and Analog Lines to any SoftPBX's imaginable. With the new range of modules in the SBL, it will be possible to serve more than 85 % of the PBX market.

BeroNet SB Gateway with 2FXO and 1FXS Key Features

• Remotely manage and monitor through the beroNet Cloud

• End-to-End

• No moving parts, long-life and reliable

• Extend your Gateway with additional beroNet Gateways

• Silent & can be placed anywhere in the Office

• 100% ABS Plastic housing, Robust, Lightweight

beroNet BFSB2HY(2 BRI + 2FXS) Specifications:

• Codecs: G.723.1 and Annex A, G.729 a/b, G.726, G.711 u/a

• G.168/G.165 Echo Cancellation with Echo Path Change Detection, up to 128ms

• Voice Activity Detection / Comfort Noise Generation

• DTMF Digit Detection and Generation

• T.38 fax relay (v.27ter, V.29, and V.17)

• SIP User Agent IETF RFC3261 compliant

• SIP over UDP/TCP with optional TLS support (SIP signalling only)

• TDM bridging over 2 beroNet VoIP Gateways through PCM bus interconnection, 8.192 kB/s

• Operating temperature: 0-70°C

• Compliance: CE (EN55022, EN55024, EN60950)

• Power: 12V

• Dimensions: 168 x 168 x 42mm

• Weight: 800g

Please Enquire