

Cisco 8861 IP Phone



Product Name: Cisco 8861 IP Phone

Manufacturer: Cisco Systems

Model Number: CP-8861

Cisco 8861 IP Phone

With the Cisco 8861 IP Phone you can increase personal productivity through an engaging user experience that is both powerful and easy-to-use. The IP Phone 8861 combines an attractive new ergonomic design with wideband audio for crystal clear voice communications, “always-on” reliability, encrypted voice communications to enhance security, and access to a comprehensive suite of unified communications features from Cisco on-premises and hosted infrastructure platforms. The IP Phone 8861 also can be supported on third party hosted call control services.

Cisco 8861 Key Features

- 5" high resolution colour display (800x480 pixel)
- 2x Gigabit Ethernet Switch
- PoE IEEE 802.3af/at Class 4 compliant (PSU available separately)
- Wideband audio (G.722)
- 5 SIP accounts (5 programmable line keys)
- Hands-free talking (speaker phone)
- 2 x USB ports
- Compatible with up to 3 x Cisco IP Phone 8800 Key Expansion Modules
- Wireless Client Mode 802.11n

In addition, Cisco Intelligent Proximity brings the worlds of desk and mobile together for you when you are using your mobile device at the desk for your work. You can move the audio path over to the IP Phone 8861 during active mobile calls to take advantage of its superior audio acoustics. An example would be to share a conversation with a colleague who you want to listen in. This capability gives you greater flexibility and a superior user experience when at your desk.

Cisco 8861 - Technical Specifications

Features and Benefits

- **Ergonomic design** The phone offers an easy-to-use interface and provides a traditional telephony-like user experience. Graphical display The 800 × 480, 24-bit color, 5-in. WVGA display provides scrollable access to calling features and text-based XML applications.
- **Handset** The handset is a standard wideband-capable audio handset (connects through an RJ-9 port). The standard coiled cord has a custom end for concealed cable routing beneath the phone (cord length is approximately 21 in. [55 cm] coiled and up to 72 in. (183 cm) extended). The handset is hearing aid-compatible (HAC) and meets Federal Communications Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). You can achieve Section 508 loudness requirements by using industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. The dial pad is also ADA-compliant.
- **Speaker phone** The full-duplex speakerphone gives you flexibility in placing and receiving calls with hands free. For added security, the audible dual tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.
- **Analog headset** The analog headset jack is a standard wideband-capable RJ-9 audio port.
- **AUX port** You can use an auxiliary port to support electronic hookswitch control with a third-party headset connected to it.
- **External audio ports** The phone has a 3.5-mm stereo line in/out jack (for optional external headset, speakers, or headphones).
- **USB** Two USB ports enhance the usability of call handling by enabling wired or wireless headsets, as well as provide charging capability to mobile devices such as smartphones or tablets. A side USB port provides up to 500mA power output at 5V or 2.5W. A back USB (in yellow) port provides 500mA power output and is upgradeable to support up to 2.1A

Cisco 8861 IP Phone

power output at 5V or 10.5W.

½ Ethernet switch An internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000BASE-T Ethernet network (IEEE 802.3i/802.3u/802.3ab) through a RJ-45 interface with single LAN connectivity for both the phone and a co-located PC. The system administrator can designate separate VLANs (IEEE 802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.

½ Bluetooth The phone offers Bluetooth 3.0 Enhanced Data Rate (EDR) Class 1 technology (up to 66-ft [20m] range). Hands-Free Profile (HFP) is supported for untethered headset connections and voice communications. Phone Book Access Profile (PBAP) is supported for phone book object exchange between devices.

½ Wi-Fi client As an alternative to wired Ethernet, the Cisco IP Phone 8861 supports a Wi-Fi radio with integrated antenna enabling connectivity to a Wi-Fi access-point infrastructure, thereby saving on the labor costs of pulling Ethernet cables to every work location. Complete Wi-Fi specifications are included in Table 4 later in this document.

½ Keys The phone has the following keys: Line keys; Soft keys; Back and release keys; Four-way navigation and select keys; Hold/Resume, Transfer, and Conference keys; Messaging, Application, and Directory keys; Standard keypad; Volume-control toggle key; Speakerphone, headset, and mute keys

½ Backlit indicator The phone supports backlit indicators for the audio path keys (handset, headset, and speakerphone), select key, line keys, and message waiting.

½ Replaceable bezel The phone includes a black bezel; an optional silver bezel is also orderable separately.

½ Dual-position foot stand The display is easy-to-view and the buttons and keys are easy-to-use. The two-position foot stand

supports viewing angles of 35 and 50 degrees; you can remove the foot stand for wall mounting, with

mounting holes located on the base of the phone.

½ Wall-mountable You can install the phone on a wall using an optional wall-mount kit (orderable separately).

½ Key expansion module (KEM) The phone supports up to three KEMs to expand from 5- to 113-line buttons. You have the convenience of many speed dials or programmable features.

½ Physical security The phone is compatible with the Kensington Security Slot (K-Slot) antitheft system.

½ Power Features IEEE Power over Ethernet (PoE) IEEE Power over Ethernet class 4. The phone is compatible with both IEEE 802.3af and 802.3at switch blades and supports both Cisco Discovery Protocol and Link Layer Discovery Protocol - Power over Ethernet (LLDP-PoE). Cisco IP Phone Power Cube 4 This optional power cube is used as an AC-to-DC (48V) power supply for non-PoE deployments. Use of the power cube 4 also requires the use of one of the corresponding AC country cords Call-Control Support

½ Cisco Unified Communications Manager 8.5.1 (Non-Secured mode Only) 8.6.29.1.210.5.211.0 and later Cisco Unified Communications Manager Express (Unified CME) 10.0 and later through fast track Cisco Business Edition 6000 (BE 6000) 8.6.29.1.210.5.211.0 and later

½ Cisco Hosted Collaboration Solution (HCS) 8.6.2 and later (using supported UCM versions above)

Features and Specifications

½ Audio codec support G.711 a-law and mu-law, G.722, G.729a, Internet Low Bitrate Codec (iLBC), and Internet Speech Audio Codec (iSAC)

½ Key call features support + Dialing Abbreviated dialing Adjustable ring tones and volume levels Adjustable display brightness Agent greeting Auto-answer Auto-detection of headset Barge Busy Lamp Field (BLF) Busy Lamp Field (BLF) Pickup Busy Lamp Field (BLF) speed dial Callback Call forward Call notification Call filter Call history lists Call park Call pickup Call timer Call waiting Call chaperone Caller ID Corporate directory Conference, including traditional Join feature Cross Cluster Extension Mobility (EMCC) Direct transfer Extension

Cisco 8861 IP Phone

mobilityFast-dial serviceForced access codes and client matter codesGroup call pickupHoldIntercomImmediate divertMalicious-caller IDMessage-waiting indicator (MWI)Meet-me conferenceMobilityMusic on hold (MoH)MuteNetwork profiles (automatic)On- and off-network distinctive ringingPersonal directoryPickUpPredialing before sendingPrivacyPrivate Line Automated Ringdown (PLAR)RedialRing tone per line appearanceService URLShared lineSilent monitoring and recordingSpeed dialTime and date displayTransferUniform Resource Locator (URI) dialingVisual voice mailVoice mailWhisper coaching

• **Electronic hookswitch** You can control the hookswitch electronically with a third-party headset connected to either the USB or auxiliary port, or directly paired with the phone through Bluetooth.Audio path moving sends audio through the IP Phone 8861 for a mobile device-connected call.Call history synchronization allows you to view placed and missed calls of your mobile device from the IP PhoneContact synchronization allows you to synchronize the contact objects from your mobile device to your IP Phone

• **Quality-of-service (QoS) options**The phone supports Cisco Discovery Protocol and 802.1Q/p standards, and can be configured with an 801.1Q

• **VLAN header** containing the VLAN ID overrides configured by the Admin VLAN ID.

• **Network features** Session Initiation Protocol (SIP) for signalingSession Description Protocol (SDP)IPv4 and IPv6User Datagram Protocol (UDP) (used only for Real-Time Transport Protocol [RTP] streams)Dynamic Host Configuration Protocol (DHCP) client or static configurationGratuitous Address Resolution Protocol (GARP)Domain Name System (DNS)Trivial File Transfer Protocol (TFTP)Secure Hypertext Transfer Protocol (HTTPS)VLANReal-Time Transport Protocol (RTP)Real-Time Control Protocol (RTCP)Cisco Peer-to-Peer Distribution Protocol (PPDP)Cisco Discovery ProtocolLLDP (including LLDP-MED)Switch speed auto-negotiation

• **Security features** Secure bootSecure credential storageDevice authenticationConfiguration file authentication and encryptionImage authenticationRandom bit generationHardware cryptographic accelerationCertificate Authority Proxy Function (CAPF)Manufacturer-Installed Certificates (MIC)Locally Significant Certificates (LSC)Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Secure

• **Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)**Signaling authentication and encryption using TLSMedia authentication and encryption using SRTPHTTPS for client and serverSecure Shell (SSH) Protocol serverSecure Sockets Layer (SSL)-based VPN client

• **Physical dimensions** (H × W × D) 9.02 x 10.13 x 1.57 in. (229.1 x 257.34 x 40 mm) (exclude foot stand)

• **Weight** 2.62 lb (1.19 kg)

Price: \$297.58