

CyberData SIP Ceiling Tile Drop-In Speaker (011401)

		L

Product Name: CyberData SIP Ceiling Tile Drop-In Speaker (011401) Manufacturer: -Model Number: 011401

Please Note: This product has been discontinued. Please see the CyberData Speakers range.

CyberData SIP Ceiling Tile Drop-In Speaker (011401) Tthe CyberData SIP Ceiling Tile Drop-In Speaker (011401) combines the market leader in IP Speakers, with the latest design in speaker mounts. It's streamlined and easy to install, with a 1' x 2' "drop-in" design. CyberData 011401 Key Features

- i¿½ Support for security code to prevent unwanted SIP calls
- i¿1/2 Optional red/green/blue/white strobe kit connection available
- ï¿1/2 Autoprovisioning via HTTP, HTTPS, or TFTP
- ïزئ HTTPS or HTTP web based configuration. HTTPS is enabled by default.
- ï¿1/2 802.11q VLAN tagging
- ï¿1/2 Configurable sense input for use with fault detection or with optional lighted button kit

i¿1/2 Configurable event generation for device health and status monitoring

ï¿¹/₂ Support for G.722 codecs

ï¿1/2 Powered via PoE (802.3AF or 802.3AT) or 24V auxiliary power supply (not included)

� Enhanced interoperability for hosted environments

The SIP Ceiling Tile Drop-In SIP Speaker is a Power-over-Ethernet (PoE 802.3af/802/3at) and Voice-over-IP (VoIP) public address loudspeaker that easily connects into existing local area networks with a single CAT5 cable connection. The speaker is compatible with most SIP-based IP PBX. In a non-SIP environment, the speaker is capable of playing audio from a multicast source. CyberData 011401 - Technical Specifications Features

ï¿1/2 SIP (RFC 3261) compatible

- ï¿1/2 Night Ringer function
- ï¿1/2 Plays audio from Multicast
- ï¿1/2 Web-based configuration
- ï¿1/2 Paging prioritization and background music
- ï¿¹/₂ User upgradeable firmware via web interface or autoprovisioning
- ï¿1/2 External volume control
- ï¿1/2 Small footprint

ï¿1/2 High efficiency speaker driver

ï¿1/2 IGMP I SIP endpoint or Multicast group member

ï¿1/2 Network-adjustable speaker volume

ï¿¹/₂ Can drive one external analog speaker for greater coverage (part #011120/011121 sold separately)

General

ï¿1/2 Audio Output 802.3af - SPL 109.2 dB @ 1 meter

ï¿1/2 802.3at - SPL 111.9 dB @ 1 meter

- ï¿1/2 Operating Temperature -10 degrees C to 50 degrees C (14 degrees F to 122 degrees F)
- ï¿1/2 Ethernet I/F 10/100 Mbps
- ï¿1/2 Protocol SIP RFC 3261 Compatible

ï¿1/2 Power Input PoE 802.3af/802.3at

ï¿¹/₂ Payload Types G.711 μ-law, G.711 a-law, and G.722



CyberData SIP Ceiling Tile Drop-In Speaker (011401)

� Dimensions (Unit) Length: 12 in. [304.8 mm], Width: 3.23 in. [82.04 mm], Height: 23.75 in. [603.25 mm]

� Dimensions (Boxed) Length: 16.25 in. [412.75 mm], Width 8.125 in. [206.38 mm], Height: 28.25 in. [717.55 mm]

ï¿1/2 Boxed Weight 8.0 lbs. [3.63 kg]

ï¿1/2 Warranty 2 Year Limited

ï¿1/2 Part Number Standard Color 011401, RAL 9002 Gray White (replaces 011128)

Price: £530.90