

## Yealink T27G IP Phone (SIP-T27G)



Product Name: Yealink T27G IP Phone (SIP-T27G)

Manufacturer: Yealink

Model Number: SIP-T27G

Yealink T27G IP Phone (SIP-T27G)

Please Note: The Yealink T27G does not come with a power supply. If you require one, please select this from the drop-down box above.

The Yealink T27G Gigabit IP Phone is a 6 line VoIP phone with unparalleled functionality and expansibility thanks to an all-new USB port. A professional IP Phone with features such as 3.66" 240x120-pixel graphical LCD with backlight and 2 x Gigabit Ethernet Ports. The SIP-T27G is future proof and ready for prospective Bluetooth, Wi-Fi and USB recording features. Yealink T27G Key Features

- 6 SIP accounts
- Yealink Optima HD voice
- 3.66" 240x120-pixel graphical LCD with backlight
- Gigabit
- USB 2.0
- Opus\* codec support
- Paper label free design
- PoE support
- Headset, EHS support
- Supports expansion modules

Seamlessly migrated to GigE-based network infrastructure, SIP-T27G IP phone is also built with the Gigabit Ethernet facilitating very rapidly call handling. By using standard encryption protocols, the SIP-T27G performs highly secure remote provisioning and software upgrades.

Yealink T27G - Technical Specifications

Audio Features

- HD voice: HD handset, HD speaker
- Wideband codec: Opus\*, G.722
- Narrowband codec: Opus\*, G.711(A&micro;), G.723.1, G.729, G.729AB, G.726, iLBC
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 6 VoIP accounts
- One-touch speed dial, redial
- Call forward, call waiting
- Call transfer, call hold
- Call return, group listening
- Mute, auto answer, DND
- 3-way conference call
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Hotline, emergency call
- Set date time manually or automatically
- Dial plan, XML Browser, Action URL/URI
- Integrated Screenshots

## Yealink T27G IP Phone (SIP-T27G)

- RTCP-XR
- USB port (2.0 compliant) Bluetooth earphone through BT40 (pending), Wi-Fi through WF40 (pending), USB call recording through USB flash drive (pending)
- Enhanced DSS key

### Directory

- Local phonebook up to 1000 entries
- Black list
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

### IP-PBX Features

- Busy Lamp Field (BLF)
- Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating
- Call park, call pickup
- Executive and Assistant
- Centralized call recording
- Visual voice mail

### Display and Indicator

- 3.66" 240x120-pixel graphical LCD with backlight
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Power saving

### Feature keys

- 8 line keys with LED
- 8 line keys can be programmed up to 21 paperless DSS keys (3-page view)
- 8 features keys: message, headset, conference, mute, hold, transfer, redial, hands-free speakerphone
- 4 context-sensitive "soft" keys
- 6 navigation keys
- 2 volume control keys
- Illuminated message key
- Illuminated headset key

### Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), Class 21 x USB port (2.0 compliant) 1 x RJ9 (4P4C) handset port 1 x RJ9 (4P4C) headset port 1 x RJ12 (6P6C) EHS port 1 x RJ12 (6P6C) EXT port: Supports up to 6 Expansion Modules

## Yealink T27G IP Phone (SIP-T27G)

### Other Physical Features

- Stand with 2 adjustable angles
- Wall mountable
- External Yealink AC adapter (optional): AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 1.44~3.47W
- Power consumption (PoE): 1.72~7.07W
- Dimension (W\*D\*H\*T): 265mm x 210mm x 170.5mm x 53.5mm
- Operating humidity: 10-95%
- Operating temperature: -10~50&deg;C

### Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

### Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE

### Package Features

- Package content:- Yealink SIP-T27G IP phone- Handset with handset cord- Ethernet Cable (1.5m CAT5E UTP Cable)- Stand- Quick Start Guide- Power Adapter (Optional)- Wall Mount Bracket (Optional)
- Qty/CTN: 5 PCS
- N.W/CTN: 6.6 kg
- G.W/CTN: 7.4 kg
- Giftbox size: 295mm x 224mm x 115mm
- Carton Meas: 602mm x 308mm x 236mm

## Yealink T27G IP Phone (SIP-T27G)

**Price: £61.45**

---

Options available for Yealink T27G IP Phone (SIP-T27G) :

**Power Supply Required?**

[UK PSU 10V Required \(+£10.00\)](#), [None - Using PoE](#).

**Bluetooth Module Required?**

[Yealink BT40 Bluetooth Module \(+£31.08\)](#), [Not Required](#).

**Wi-Fi USB Dongle Required?**

[Yealink WF50 Dual-Band WiFi Module \(+£26.00\)](#), [Not Required](#).