

Akuvox R23C IP Door Phone



Product Name: Akuvox R23C IP Door Phone

Manufacturer: -

Model Number: R23C

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox R23C IP Door Phone

The Akuvox R23C security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R26C enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

Akuvox 23C Key Features

- 1/2 Vandal resistant body, with a flush button
- 1/2 Wide-angle camera: 90°;
- 1/2 PoE (IEEE802.3af, Power-over-Ethernet)
- 1/2 Two-way audio communication over IP networks with Echo Cancel feature
- 1/2 Complies with SIP standard for easy integration in every SIP capable PBXes

Akuvox 23C - Technical Specifications

Physical & Power

- 1/2 Body material: all-aluminum
- 1/2 Camera: 3M pixels, automatic lighting
- 1/2 Button: 1 call button
- 1/2 Output Relay: 2 output relays for door opener
- 1/2 802.3af Power-over-Ethernet
- 1/2 RF Card Reader: 13.56MHz supported
- 1/2 12V DC connector (if not using PoE)
- 1/2 Power consumption: less than 12W
- 1/2 Water-proof & Dust-proof: IP65
- 1/2 Installation: Wall-mounted
- 1/2 Dimension: 190x110x35mm

SIP Endpoint

- 1/2 SIP v1(RFC2543), SIP v2(RFC3261)
- 1/2 Audio codecs: G.711a, G.711µ, G.722, G.729
- 1/2 Video codecs: H.263, H.264
- 1/2 Speech Quality: 7kHz Audio
- 1/2 Echo Cancellation
- 1/2 Voice Activation Detection
- 1/2 Comfort Noise Generator

Video

- 1/2 Resolution: up to 1080p
- 1/2 Maximum image transfer rate: 1080p - 30fps
- 1/2 High intensity white LEDs for picture lighting during dark hours with internal light sensor
- 1/2 Compatible to 3rdPartyVideo components, e.g. NVRs

Door Entry Features

Akuvox R23C IP Door Phone

• Relays controlled individually by DTMF tones

• Camera permanently operational

• White balance: auto

• Auto-night mode with LED illumination

• Minimum illumination: 0.1LUX

Networking

• 1x10/100 Mbps Ethernet port

• Protocols support: IPv4, HTTP, HTTPS, FTP, SNMP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Application Scenarios

• Office door phone with on-site or hosted IP-PBX

• Remote site entry over Internet

• Villa intercom with door access control

Please Enquire
