

Yealink T41S IP Phone (SIP-T41S)



Product Name: Yealink T41S IP Phone (SIP-T41S)

Manufacturer: -

Model Number: SIP-T41S

Please Note: This product has been discontinued. Please see the Yealink T42U IP Phone for an available alternative.

Yealink T41S IP Phone (SIP-T41S)

The Yealink T41S is a feature-rich business tool for superior communications and extended functionality. The SIP-T41S is a six-line IP phone that comes with built-in programmable keys to enhance productivity.

Yealink T41S Key Features

- Up to 6 SIP accounts
- 2.7" 192x64-pixel graphical LCD with backlight
- Opus* codec support
- USB 2.0
- T4S Auto-P template unified
- T4S firmware unified
- PoE support
- Paperless label design
- Headset, EHS support
- Integrated stand with 2 adjustable angles
- Wall mountable

With an all-new USB port, the SIP-T41S boasts unparalleled functionality and expansibility, which comes ready for future Bluetooth, Wi-Fi and USB recording features.

The new T4S series offers the same elegant appearance of the T4 line, but with improvements for greater interoperability and collaboration. The SIP-T41S features Yealink Optima HD Voice technology and wideband codec of Opus delivers superb audio quality and crystal clear voice communications. The T41S offers a faster, more-responsive interface than the T41P and several performance-enhancing functions.

Yealink T41S Technical Specification

Audio Features

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Wideband codec: Opus*, G.722
- Narrowband codec: Opus*, G.711(Aµ), G.723.1, G.729AB, G.726, iLBC
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 6 VoIP accounts
- One-touch speed dial, redial
- Call forward, call waiting
- Call transfer, call hold
- Call return, group listening
- Mute, auto answer, DND
- 3-way conference call
- Direct IP call without SIP proxy

Yealink T41S IP Phone (SIP-T41S)

- Ring tone selection/import/delete
- Hotline, emergency call
- Set date time manually or automatically
- Dial Plan, XML Browser, Action URL/URI
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- USB port (2.0 compliant) Bluetooth earphone through BT40 (pending), Wi-Fi through WF40 (pending), USB call recording through USB flash drive (pending)
- Enhanced DSS key

Directory

- Local phonebook up to 1000 entries
- Black list
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

IP-PBX Features

- Busy Lamp Field (BLF)
- Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating
- Call park, call pickup
- Executive and Assistant
- Centralised call recording
- Visual voice mail
- Call recording

Display and Indicator

- 2.7" 192x64-pixel graphical LCD with backlight
- LED for call and message waiting indication
- Dual-colour (red or green) illuminated LEDs for line status information
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Power saving

Feature keys

- 6 line keys with LED
- 6 line keys can be programmed up to 15 paperless DSS keys (3-page view)
- 5 features keys: message, headset, mute, redial, hands-free speakerphone
- 4 context-sensitive "soft" keys
- 6 navigation keys
- 2 volume control keys
- Illuminated mute key
- Illuminated headset key
- Illuminated hands-free speakerphone key

Interface

Yealink T41S IP Phone (SIP-T41S)

- 2 x RJ45 10/100M Ethernet ports
- Power over Ethernet (IEEE 802.3af), Class 2
- 1 x USB port (2.0 compliant)
- 1 x RJ9 (4P4C) handset port
- 1 x RJ9 (4P4C) headset port
- 1 x RJ12 (6P6C) EHS port

Other Physical Features

- Stand with 2 adjustable angles
- Wall mountable
- External Yealink AC adapter (optional)：AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 1.25-5.1W
- Power consumption (PoE): 1.72-6.73W
- Dimension (W*D*H*T): 212mm*189mm*175mm*54mm
- Operating humidity: 10~95%
- Operating temperature: -10~50°C

Management

- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Broadsoft device management
- Zero-sp-touch TR-069
- Phone lock for personal privacy protection
- Reset to factory, reboot
- Package tracing export, system log

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- Call server redundancy supported
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- SRTP for voice
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X
- IPv6
- LLDP/CDP/DHCP VLAN
- ICE

Package Features

- Package content:- Yealink SIP-T41S IP phone- Handset with handset cord- Ethernet Cable (2m CAT5E UTP Cable)- Stand- Quick Start Guide- Power Adapter (Optional)- Wall Mount Bracket (Optional)

Yealink T41S IP Phone (SIP-T41S)

Please Enquire

Options available for Yealink T41S IP Phone (SIP-T41S) :

Power Supply Required?

[UK PSU required \(+£7.10\)](#), [None - Using PoE](#).

RPS Extension ID

[TEXT](#).

RPS Extension Password

[TEXT](#).

RPS Display Name

[TEXT](#).

RPS PBX URL

[TEXT](#).

RPS NAT Enabled

[TEXT](#).

RPS Outbound Proxy

[TEXT](#).

RPS SIP Port

[TEXT](#).

T4x Wall Mount Bracket

[Required \(+£7.00\)](#), [Not Required](#).

Compatible Headsets

[Yealink UH36 Dual USB Headset \(+£56.25\)](#), [Not Required](#), [Yealink UH33 USB Headset \(+£24.00\)](#), [Grandstream GUV3000 HD USB Headset \(+£35.00\)](#), [JPL Connect-1 monaural headset and disconnect cord \(+£65.20\)](#), [Yealink UH36 Mono USB Headset \(+£47.50\)](#), [Yealink YHS33 IP Headset \(+£35.10\)](#), [Grandstream GUV3005 HD USB Headset with busy-light \(+£68.00\)](#), [JPLConnect-2 binaural headset and disconnect cord \(+£76.25\)](#).

Compatible Wireless Headsets

[Jabra Pro 920 Mono with remote handset lifter \(+£137.80\)](#), [Plantronics CS540 EHS Wireless headset and adapter \(+£215.06\)](#), [Not Required](#), [Plantronics CS520 Binaural wireless EHS headset and adapter \(+£260.89\)](#).

Headset Adapter

[Yealink EHS36 \(+£36.70\)](#), [Not Required](#).

Wi-Fi USB Dongle Required?

[Yealink WF50 Dual-Band WiFi Module \(+£26.00\)](#), [Not Required](#).

DECT USB Dongle Required?

[Yealink DECT USB Dongle DD10K \(+£14.60\)](#), [Not Required](#).

Bluetooth USB Dongle Required?

[Yealink BT41 Bluetooth USB Dongle \(+£20.00\)](#), [Not Required](#).