



Product Name: Polycom VVX 411 Gigabit Business Media Phone (VVX411)

Manufacturer: -

Model Number: 2200-48450-025

Please Note: This product has been discontinued. For an alternative, please see the other Poly Products.

Polycom VVX 411 Gigabit Business Media Phone

The Polycom VVX 411 is mid-range professional VoIP Desktop Phone, with 12 lines and 3.5" colour LCD display, ensuring that it will be a perfect fit for secretaries, salespersons and executives alike. With 12 programmable buttons and 4-speed dial buttons, alongside its 320x240 display and 4-directional navigation buttons, the phone's user interface is intuitive and easy-to-use.Polycom VVX 411 Key Features

� 3.5" TFT (320 x 240)

� 12 lines or speed dial keys

� 2 Gigabit Ethernet ports

تزار Improved memory and processor over the VVX 410

ï¿1/2 HD Voice and Full Duplex Speakerphone

� RJ9 headset jack

Polycom VVX411 - Technical Specifications User interface features

آزا Backlit 3.5 in color LCD (320 x 240) resolution

� Voicemail support1

ï¿1/2 WebKit-based browser

ï¿1/2 Adjustable base height

īస్ట్ Single USB port (2.0 compliant) for media and storage applications

าะ/ Unicode UTF-8 character support. Multilingual user interface including Chinese, Danish, Dutch,

English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian,

Polish, Portuguese, Russian, Slovenian, Spanishand Swedish

## Audio features

تَذِيًا Polycom® HD Voice™ technology delivers life-like voice quality for each audio patch handset, the hands-free speakerphone and the optional headset2

آذِيً Polycom® Acoustic Clarity™ technology. Providing full-duplex conversations, acoustic echo cancellation and background noise suppression Type 1 compliant (IEEE 1329 full duplex)

آذِ½ Frequency response – 150 Hz – 7 kHz for handset, optional headset and hands-free speakerphone modes

� Codecs: G.711 (A-law and μ-law), G.729AB, G.722.1, iLBC

ī¿½ Individual volume settings with visual feedback for each audio path

� Voice activity detection

� Comfort noise generation

าั¿1/2 DTMF tone generation (RFC 2833 and in-band)

� Low-delay audio packet transmission

ï¿1/2 Adaptive jitter buffers

ï¿1/2 Packet loss concealment

Headset and handset compatibility



- ï¿1/2 Dedicated RJ-9 headset port
- าั¿½ Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- � Compliant with ADA Section 508 Subpart B 1194.23 (all)
- រី¿½ Hearing aid compatible handset for magnetic coupling to hearing aids
- า๊¿½ Compatible with commercially available TTY adapter equipment

#### Call handling features1

- � Call handling features1
- � 12 lines (programmable line keys)
- � Shared call/bridged line appearance
- � Busy lamp field
- ī¿½ Flexible line appearance (1 or more line keys can be assigned for each line extension)
- � Supports compatible USB headsets
- 12.1/2 Distinctive incoming call treatment/ call waiting
- � Call timer and call waiting
- ï¿1/2 Call transfer, hold, divert (forward), pickup
- � Called, calling, connected party information
- � Local 3-way audio conferencing
- ï¿1/2 1-touch speed dial, redial
- � Remote missed call notification
- � Do not disturb function
- � Electronic hook switch capable
- � Local configurable digit map/dial plan

### Open application platform

- าั¿¼ WebKit-enabled full browser that supports HTML5, CSS, SSL security and JavaScript
- Ti21/2 Supports Polycom Apps SDK and API for third-party business and personal applications
- าั¿½ Bundled with Polycom UC Software:-- Corporate directory access using LDAP-- Visual conference management-- Local voice call recording on USB flash drive

### Network and Provisioning

- $\ddot{\imath}$  SIP protocol support
- � SDP
- تزار IETF SIP (RFC 3261 and companion RFCs)
- Two-port Gigabit Ethernet switch-- 10/100Base-TX across LAN and PC Ports-- 1000Base-TX available on VVX410-- Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment--Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- 17:1/2 Manual or dynamic host configuration protocol (DHCP) network setup
- 12.1/2 Time and date synchronization using SNTP
- Ti21/2 FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deploymentsProvisioning and call server redundancy supported1
- าั¿½ QoS Support IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- آزار VLAN-CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery
- SIP signalling
- ï¿1/2 RTCP and RTP support
- � Event logging
- ï¿⅓ Syslog
- � Hardware diagnostics
- ï¿⅓ Status and statistics reporting
- آز½ IPv4
- TCP ½⅓



ϊ¿½ UDP ϊ¿½ DNS-SRV

#### Security

- � 802.1X authentication and EAPOL
- � Media encryption via SRTP
- � Transport layer security
- � Encrypted configuration files
- � Digest authentication
- � Password login
- า๊¿½ Support for URL syntax with password for boot server address
- ï¿1/2 HTTPS secure provisioning
- ï¿⅓ Support for signed software executables

#### Power

- าั¿½ Built-in auto-sensing IEEE 802.3af Power over Ethernet
- � Energy-saving after-hours mode
- � External universal AC adapter (optional), 48VDC 0.3A

#### Approvals

- � FCC Part 15 (CFR 47) Class B
- � ICES-003 Class B
- ï¿1/2 EN55022 Class B
- � CISPR22 Class B
- � VCCI Class B
- � EN55024
- � EN61000-3-2; EN61000-3-3
- ï¿⅓ NZ Telepermit
- Korea KC3
- ï¿⅓ UAE TRA
- ï¿⅓ Russia CU
- تز1/2 Brazil ANATEL3
- ï¿1/2 Australia RCM
- ï¿⅓ ROHS compliant

## Safety

- � UL 60950-1
- آذِ½ CE Mark
- ï¿1/2 CAN/CSA C22.2 No. 60950-1
- � EN 60950-1
- � IEC 60950-1
- ï¿1/2 AS/NZS 60950-1
- � ICASA
- � CITC

### Operating condition

� Temperature: 0 to 40°C (+32 to 104°F) � Relative humidity: 5% to 95%, noncondensing

## Storage temperature



 $i \frac{1}{2}$  -40 to +70°C (-40 to +160°F)

Polycom VVX 400 comes with:

� VVX 400 console

ï¿1/2 Handset with handset cord

ï¿1/2 Network (LAN) cable - CAT-5E

 $12\sqrt{2}$  Quick start guide-- A ferrite clamp is included in the box-- Open source OFFER is included in the box

Size

� 7.5 x 6 x 7 in (19 x 15 x 18 cm) (W x H x D)

Weight

� 2.0 lbs (0.9 kg)

Unit box dimensions

� 11.46 x 7.9 x 3.82 in (29.1 x 20 x 9.7 cm) � 3.1 lbs (1.4 kg)

## **Please Enquire**

Options available for Polycom VVX 411 Gigabit Business Media Phone (VVX411) :

## **Require Power Supply**

Not Required, Universal 48V, 0.52A Power supply (+£20.50).