

Polycom VVX 401 Business Media Phone (VVX401)



Product Name: Polycom VVX 401 Business Media Phone (VVX401)

Manufacturer: -

Model Number: 2200-48400-025

Please Note: This product has been discontinued. For an alternative, please see the other Poly Products.

Polycom VVX 401 Business Media Phone - Enhanced processor and memory

The Polycom VVX 401 are expandable colour business media phones that deliver crystal clear communications, enhanced collaboration and personal productivity. Polycom VVX401 Key Features

- ½ 12 line appearances
- ½ 3.5 inch 320 x 240-pixel colour LCD display
- ½ Two-port 10/100 Ethernet switch
- ½ Polycom HD Voice
- ½ Improved memory and processor over the VVX 400
- ½ Power over Ethernet IEEE 802.3af Class 2
- ½ 4 soft keys, 8 function keys, 4-way navigation
- ½ Expandable via USB port

The VVX 401 brings high-quality, cost-effective solutions to front-line staff handling a moderate volume of calls through advanced unified communications (UC) telephony features.

Polycom VVX401 - Technical Specifications

User interface features

- ½ Backlit 3.5 in color LCD (320 x 240) resolution
- ½ Voicemail support
- ½ WebKit-based browser
- ½ Adjustable base height
- ½ Single USB port (2.0 compliant) for media and storage applications
- ½ Unicode UTF-8 character support. Multilingual user interface including Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish and Swedish

Audio features

- ½ Polycom HD Voice® technology delivers life-like voice quality for each audio patch handset, the hands-free speakerphone and the optional headset
- ½ Polycom® Acoustic Clarity® technology. Providing full-duplex conversations, acoustic echo cancellation and background noise suppression Type 1 compliant (IEEE 1329 full duplex)
- ½ Frequency response – 150 Hz – 7 kHz for handset, optional headset and hands-free speakerphone modes
- ½ Codecs: G.711 (A-law and μ-law), G.729AB, G.722.1, iLBC
- ½ Individual volume settings with visual feedback for each audio path
- ½ Voice activity detection
- ½ Comfort noise generation
- ½ DTMF tone generation (RFC 2833 and in-band)
- ½ Low-delay audio packet transmission
- ½ Adaptive jitter buffers
- ½ Packet loss concealment

Polycom VVX 401 Business Media Phone (VVX401)

Headset and handset compatibility

- ½ Dedicated RJ-9 headset port
- ½ Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
- ½ Compliant with ADA Section 508 Subpart B 1194.23 (all)
- ½ Hearing aid compatible handset for magnetic coupling to hearing aids
- ½ Compatible with commercially available TTY adapter equipment

Call handling features

- ½ Call handling features
- ½ 12 lines (programmable line keys)
- ½ Shared call/bridged line appearance
- ½ Busy lamp field
- ½ Flexible line appearance (1 or more line keys can be assigned for each line extension)
- ½ Supports compatible USB headsets
- ½ Distinctive incoming call treatment/ call waiting
- ½ Call timer and call waiting
- ½ Call transfer, hold, divert (forward), pickup
- ½ Called, calling, connected party information
- ½ Local 3-way audio conferencing
- ½ 1-touch speed dial, redial
- ½ Remote missed call notification
- ½ Do not disturb function
- ½ Electronic hook switch capable
- ½ Local configurable digit map/dial plan

Open application platform

- ½ WebKit-enabled full browser that supports HTML5, CSS, SSL security and JavaScript
- ½ Supports Polycom Apps SDK and API for third-party business and personal applications
- ½ Bundled with Polycom UC Software-- Corporate directory access using LDAP-- Visual conference management-- Local voice call recording on USB flash drive

Network and Provisioning

- ½ SIP protocol support
- ½ SDP
- ½ IETF SIP (RFC 3261 and companion RFCs)
- ½ Two-port Gigabit Ethernet switch-- 10/100Base-TX across LAN and PC Ports-- 1000Base-TX available on VVX410-- Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment-- Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
- ½ Manual or dynamic host configuration protocol (DHCP) network setup
- ½ Time and date synchronization using SNTP
- ½ FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deploymentsProvisioning and call server redundancy supported
- ½ QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
- ½ VLAN-CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery
- ½ Network address translation support for static configuration and “keep-alive”
- ½ SIP signalling
- ½ RTCP and RTP support
- ½ Event logging
- ½ Syslog
- ½ Hardware diagnostics
- ½ Status and statistics reporting

Polycom VVX 401 Business Media Phone (VVX401)

- IPv4
- TCP
- UDP
- DNS-SRV

Security

- 802.1X authentication and EAPOL
- Media encryption via SRTP
- Transport layer security
- Encrypted configuration files
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning
- Support for signed software executables

Power

- Built-in auto-sensing IEEE 802.3af Power over Ethernet
- Energy-saving after-hours mode
- External universal AC adapter (optional), 48VDC 0.3A

Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- NZ Telepermit
- Korea KC3
- UAE TRA
- Russia CU
- Brazil ANATEL3
- Australia RCM
- ROHS compliant

Safety

- UL 60950-1
- CE Mark
- CAN/CSA C22.2 No. 60950-1
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1
- ICASA
- CTC

Operating condition

- Temperature: 0 to 40°C (+32 to 104°F)
- Relative humidity: 5% to 95%, noncondensing

Polycom VVX 401 Business Media Phone (VVX401)

Storage temperature

½ -40 to +70°C (-40 to +160°F)

Polycom VVX 400 comes with:

- ½ VVX 400 console
- ½ Handset with handset cord
- ½ Network (LAN) cable - CAT-5E
- ½ Quick start guide-- A ferrite clamp is included in the box-- Open source OFFER is included in the box

Size

½ 7.5 x 6 x 7 in (19 x 15 x 18 cm) (W x H x D)

Weight

½ 2.0 lbs (0.9 kg)

Unit box dimensions

½ 11.46 x 7.9 x 3.82 in (29.1 x 20 x 9.7 cm)
½ 3.1 lbs (1.4 kg)

Please Enquire

Options available for Polycom VVX 401 Business Media Phone (VVX401) :

Require Power Supply

Not Required, Universal 48V, 0.52A Power supply (+£20.50).