



Digium 1B234LF Dual Span Digital BRI PCI Card with Hardware Echo Cancellation



Product Name: Digium 1B234LF Dual Span Digital BRI PCI Card with Hardware Echo Cancellation

Manufacturer: -

Model Number: 1B234LF

Please Note: This product has been discontinued. Please see the Digium Asterisk Cards for an alternative.

Digium 1B234LF Dual Span Digital BRI PCI Card with Hardware Echo Cancellation The Digium 1B234LF is a Two Span Digital BRI PCI Express Card. Digium provides several different BRI interface computer telephony cards. These computer cards quickly and easily connect Asterisk to traditional telephone network, giving users powerful tools to build sophisticated voice applications and to solve connectivity issues.

Featuring on-board echo cancellation and compatibility with traditional PCI as well as PCI-Express slots, and available in low-profile or full-height configurations, Digium's BRI cards are versatile solutions for any business need.

Digium 1B234LF Key Features

า๊ะ่½ Software-configurable interface switching; no jumpers

� Supports NT and TE modes

� 4-wire S/T interfaces

� EuroISDN Signaling Support

� PCI-Express x1connector, fits into any PCIe slot

i¿½ Half-length, low-profile form-factor, fits into any chassis

ï¿1/2 Onboard DSP echo cancellation

� 5-year warranty

Working natively with Asterisk's DAHDI drivers, these interface cards are reliable, trouble-free, and backed by a 5-year warranty. Digium is the trusted name for Asterisk solutions. Digium 1B234LF Technical Specification

Target Applications

� PC based PBX

� VoIP gateways

ï¿⅓ ISDN monitoring

ï¿1/2 ISDN recording

Environment Conditions

าั¿½ Operation Range: 0° to 50°C, 32° to 122° F าั¿½ Storage Range: -20° to 65°C, 4° to 149° F

i¿½ Humidity: 10-90% non-condensing

Configurable Modes

ï¿⅓ EuroISDN TE

� EuroISDN NT

� Software configuarable: B433 and B233 � Jumper- and dipswitch-configurable: B410

Warranty



Digium 1B234LF Dual Span Digital BRI PCI Card with Hardware Echo Cancellation

� 5-year parts and labor � Digium Exceptional Satisfaction Program

Interfaces

� PCI Interface (B410P)32-bit33MHzUniversal PCI 2.2 compliant � PCIe Interface (B233/B433)PCIe 1.0 or greaterx1 connector

Hardware Echo Cancellation

� 64ms (512 taps) of echo cancellation per B-channel

Models

� B433: Quad Port BRI PCle � B233: Dual Port BRI PCle � B410P: Quad Port BRI PCI

Hardware Requirements

� 500-MHz Pentium III or better with 64MB of RAM � Available 3.3V or 5.0V PCI Slot

Price: £389.60