

ZYCOO Coovox U50-PRO IP PBX Bundle

Product Name: ZYCOO Coovox U50-PRO IP PBX Bundle

2000

Manufacturer: -

Model Number: U50-PRO

ZYCOO Coovox U50-PRO IP PBX - Coovox U50 v2 system and 5 user UC PRO Standard perpetual licenses

The ZYCOO Coovox U50-PRO comprises of the ZYCOO Coovox U50 V2 system and 5 user UC

PRO Standard perpetual licenses.

ZYCOO Coovox U50-PRO V2 Key Features

آذًا Includes ZYCOO Coovox U50 V2 + 5 user UC PRO Standard perpetual licenses

� 30 Concurrent Calls

آذِر Up to 100 IP Phone Registers/Extensions

� Voicemail & Samp; Voicemail to Email

ï¿1/2 Video Codecs: H.261/H.263/H.263+/H.264

ï¿1/2 SIP Register with UDP/TCP/TLSSIP Trunk

ï¿⅓ Skype for SIP

U50-PRO is an affordable, scalable, interoperable, secure and reliable solution which provides not only traditional PBX features such as Automated Attendant and Voicemail, but also many advanced features including Remote Extensions, Remote Office Connection, Conference Bridge, Call Recording, Call Detail Records (CDR), Automatic Call Distribution (ACD), Unified Messaging (Voicemail to Email), Web Dial and many more features.

ZYCOO Coovox U50-PRO - Technical Specifications

PBX Features

آزِيً Black List

� BLF (Busy Lamp Field)

ï¿1/2 CDR (Call Detailed Record)

� Conference Room (20 Rooms)

� Call Monitoring

� DID (Direct Inward Dialing Number)

� DISA (Direct Inward System Access)

ï¿1/2 Distinctive Ringtone

� DND (Do Not Disturb)

تزار DNIS (Dialed Number Identification Service)

ï¿⅓ Feature Codes

าั¿1/2 FOP (Flash Operation Panel) Status Monitoring

ï¿⅓ Follow Me

� IVR (Interactive Voice Responses)

ï¿⅓ Mobility Extension

� Multi-Language Prompts

ï¿1/2 Multi-Language GUI

� One Touch Recording

آزيء Phone Book

� Phone Provisioning

آز½ Pin Set

� Record File Download

� Ringgroup

ï¿1/2 SIP Register with UDP/TCP/TLS

� SIP Trunk

آزيء Skype for SIP

� Smart DID

ï¿⅓ Speed Dial



ZYCOO Coovox U50-PRO IP PBX Bundle

- � Spy
- � SRTP (Secure Realtime Transport Protocol)
- ïز½ T.38 Fax (Pass-through)
- � Time Based Rule
- آز½ Fax to Email
- ï¿⅓ WebRTC/ Web Dial
- � Voicemail & Tide Voicemail to Email الانتارة كان المارة كانتارة كانتار كانتار كانتار كان

System Capacities

- ï¿1/2 30 Concurrent Calls
- آزٰ Up to 100 IP Phone Registers/Extensions
- ï¿1/2 Recording: 36,000 mins (.gsm); 4,000 mins (.wav)
- آذِيً Voicemail: 36,000 mins (.gsm); 4,000 mins (.wav)

Codecs & amp; Protocols

- آزٰ Audio Codecs: G.722/G.711-Ulaw/G.711-Alaw/
- ï¿1/2 G.726/G.729/GSM/SPEEX
- ï¿1/2 Video Codecs: H.261/H.263/H.263+/H.264
- � Protocols: SIP (RFC3261)/IAX2
- ϊ¿½ DTMF: RFC2833/SIP INFO/In-Band

Network Features

- ï¿⅓ DDNS Client
- ï¿⅓ DHCP Server
- ï¿1/2 IPv4/IPv6/IEEE802.1Q
- � IP Assignment (PPPoE/DHCP/Static)
- ï¿1/2 SNMP v1/v2
- 73½ TR069 ت∂′
- ï¿1/2 Static Route Table
- � Trouble Shooting (Ping/Traceroute)
- า๊ะ่½ VPN Client (L2TP/PPTP/OpenVPN/N2N/IPSec)
- � VPN Server (L2TP/PPTP/OpenVPN/IPSec)

Security Features

- ï¿1/2 Refuse SIP Register DoS
- � Refuse Abort Invite DoS
- ï¿1/2 Refuse SSH Login DoS
- آزٰ½ Firewall

Logs

- � PBX Log
- ï¿⅓ Web Access Log
- � PBX Debug Log

Hardware Interfaces

- � 1 Reset Button
- تزير 1 Power Interface
- � 2 Ethernet Interfaces
- � 1 Console Interface



ZYCOO Coovox U50-PRO IP PBX Bundle

� 1 USB Interface Slot � 1/2 for Analog/GSM/WCDMA Module

Hardware Specifications Processor:

� Dualcore A7 1Ghz � SDRAM: DDR3 1GB

ï¿⅓ Storage: 8GB SD Card Power

 \ddot{i} ¿½ Supply: Input AC 100~240V, 50/60Hz;

ï¿⅓ Output DC 12V/2A

Environment

� Working Temperature: 0 ~ 40°C � Storage Temperature: -20 ~ 55°C � Humidity: 5 ~ 95% Non-condensing

Price: £466.70