

ZYCOO Coovox U60-PRO IP PBX Bundle



Product Name: ZYCOO Coovox U60-PRO IP PBX Bundle

Manufacturer: -

Model Number: U60-PRO

ZYCOO Coovox U60-PRO IP PBX Bundle - Coovox U60 v2 system and 5 user UC PRO Standard perpetual licenses

The ZYCOO Coovox U60-PRO comprises of the ZYCOO Coovox U60 V2 system and 5 user UC PRO Standard perpetual licenses. ZYCOO Coovox U60-PRO Key Features

- Includes ZYCOO Coovox U60 V2 + 5 user UC PRO Standard perpetual licenses
- Expandable to 16 Ports FXS/FXO (if required)
- Supports 80 Concurrent Calls
- Designed for Legacy deployments with large analog footprint
- Up to 24 Analog Ports (FXO/FXS)
- VGA Port for Ease of Management
- Optional hardware echo cancellation modules
- Full IP PBX features
- Attach external loudspeaker or IPOD device

The ZYCOO Coovox U60 V2 8 FXO IP PBX is specially designed for medium and large companies that need to maintain several PSTN lines or that have many analog phones in use. This new solution closely resembles the U100, except it supports up to 24 analog ports, which is ideal for business with up to 200 extensions, or that requires up to 80 concurrent calls.

ZYCOO Coovox U60-PRO - Technical Specifications

Call Features

- Call Back
- Call Forward
- Call Group
- Call Hold
- Call Paging and Intercom
- Call Park
- Call Pickup
- Call Queue
- Call Recording
- Call Routing
- Blind Transfer
- Attended Transfer
- Call Waiting
- Caller ID
- Dial by Name
- Music On Hold/Transfer
- 3-Way Conference
- Video Call

PBX Features

- Black List
- BLF (Busy Lamp Field)
- CDR (Call Detailed Record)
- Conference Room (12 Rooms)
- Call Monitoring DID (Direct Inward Dialing Number)
- DISA (Direct Inward System Access)
- Distinctive Ringtone DND (Do Not Disturb)

ZYCOO Coovox U60-PRO IP PBX Bundle

- 1/2 DNIS (Dialed Number Identification Service)
- 1/2 Feature Codes
- 1/2 Follow Me
- 1/2 IVR (Interactive Voice Responses)
- 1/2 Mobility Extension
- 1/2 Multi-Language Prompts
- 1/2 Multi-Language GUI
- 1/2 One Touch Recording
- 1/2 Phone Book
- 1/2 Phone Provisioning
- 1/2 Pin Set
- 1/2 Record File Download
- 1/2 Ringgroup SIP Register with UDP/TCP/TLS
- 1/2 SIP Trunk
- 1/2 Skype for SIP
- 1/2 Smart DID
- 1/2 Speed Dial Spy SRTP (Secure Realtime Transport Protocol)
- 1/2 T.38 Fax (Pass-through)
- 1/2 Time Based Rule
- 1/2 Virtual Fax
- 1/2 Voicemail & Voicemail to Email

System Capacities

- 1/2 80(Max) Concurrent Calls
- 1/2 Up to 200 IP Phone Registers/Extensions
- 1/2 Recording: 200,000 mins (.gsm); 20,000 mins (.wav)
- 1/2 Voicemail: 200,000 mins (.gsm); 20,000 mins (.wav) - See more at:
<http://zycoo.com/html/U60.html#sthash.Xf7EdvN8.dpuf>

Codecs and Protocols

- 1/2 Audio Codecs: G.722/G.711-Ulaw/G.711-Alaw/
- 1/2 G.726/G.729/GSM/SPEEX
- 1/2 Video Codecs: H.261/H.263/H.263+/H.264
- 1/2 Protocols: SIP (RFC3261)/IAX2
- 1/2 DTMF: RFC2833/SIP INFO/In-Band

Network Features

- 1/2 DDNS Client
- 1/2 DHCP Server
- 1/2 IPv4/IPv6/IEEE802.1Q
- 1/2 IP Assignment (PPPoE/DHCP/Static)
- 1/2 SNMP v1/v2
- 1/2 TR069
- 1/2 Static Route Table
- 1/2 Trouble Shooting (Ping/Traceroute)
- 1/2 VPN Client (N2N/L2TP/PPTP/OpenVPN)
- 1/2 VPN Server (PPTP/L2TP/OpenVPN, Up to 10 Users)

Security Features

- 1/2 Refuse SIP Register DoS
- 1/2 Refuse Abort Invite DoS

ZYCOO Coovox U60-PRO IP PBX Bundle

• Refuse SSH Login DoS
• Firewall

Logs

• PBX Log
• Web Access Log
• PBX Debug Log

Hardware Interfaces

• 1 Power Interface
• 1 Power Switch
• 2 Ethernet Interfaces (10/100/1000Mbps)
• 1 VGA Interface
• 2 Audio Interfaces
• 2 USB Interfaces 1 Hardware Echo Cancellation Interfaces (onboard)
• 1 UMTS Interface for 3G Data (onboard)
• 24 Analog Ports (FXO/FXS)

Hardware Specifications

• CPU: DualCore 1.86 GHz ATOM
• SDRAM: DDR3 1GB
• Storage: 32GB SSD
• Power Supply: AC 100~240V, 50/60Hz, 1.5A max

Environment

• Working Temperature: 0 ~ 40°C
• Storage Temperature: -20 ~ 55°C
• Humidity: 5 ~ 95% Non-condensing

*PSTN is not perfectly supported temporarily in UK

Price: Â£1,054.10