

## ZYCOO Coovox U80-PRO IP PBX Bundle

Product Name: ZYCOO Coovox U80-PRO IP PBX Bundle

Manufacturer: -

Model Number: U80-PRO

ZYCOO Coovox U80-PRO IP PBX - Coovox U80 system and 5 user UC PRO Standard perpetual licenses

The ZYCOO Coovox U80-PRO comprises of the ZYCOO Coovox U80 system and 5 user UC PRO Standard perpetual licenses. ZYCOO U80-PRO IP PBX Features

• Includes ZYCOO Coovox U80 + 5 user UC PRO Standard perpetual licenses

• PBX Features Up to 200 Extensions

• Up to 60 Simultaneous Calls

• Up to 40 Simultaneous Conference Attendees

• Up to 36 Call Queues

• Up to 36 Conference Rooms

• Recording up to 150 hrs (WAV)

• Recording up to 1500 hrs (GSM)

The ZYCOO Coovox-U80 IP PBX is a next-generation feature-rich IP PBX ideal for medium and large enterprises. The ZYCOO Coovox-U80 features up to 200 extensions and allows up to 60 simultaneous calls.

ZYCOO U80-PRO - Technical Specifications

### PBX Features

• Up to 200 Extensions

• Up to 60 Simultaneous Calls

• Up to 40 Simultaneous Conference Attendees

• Up to 36 Call Queues

• Up to 36 Conference Rooms

• Recording up to 150 hrs (WAV)

• Recording up to 1500 hrs (GSM)

• Automatic Recording/One Touch Recording

• CDR (Call Detailed Recording)

• Multi-layer IVR (Interactive Voice Response)

• TDM/SIP/IAX Extensions/trunks

• Flexible Inbound/Outbound Routing

• Time-based Routing

• Remote Extensions & Remote Offices

• Paging & Intercom

• Video Call

• Call Forward/Transfer

• Web Extension (WebRTC)

• Follow Me

• DND (Do Not Disturb)

• Ring Groups

• Pick-up Groups

• DISA (Direct Inward System Access)

• Virtual Fax

• Voicemail to Email/Fax to Email

• One Number Stations

• Smart DID

### Media

## ZYCOO Coovox U80-PRO IP PBX Bundle

• 1/2 Audio Codecs: G.722/G.711-Ulaw/G.711-Alaw/G.726/G.729/GSM/SPEEX

• 1/2 Video Codecs: H.261/H.263/H.263+/H.264 Fax: T.38 (passthrough)

### Network & Protocols

• 1/2 IPv4, IPv6, VLAN, DHCP, PPPoE, DDNS, SNMPv2, NTP, SNTP, TFTP, SSH, HTTPS, SRTP, TLS, LDAP, TR069

### Security

• 1/2 HTTPS, Fail2Ban, Permit IP, Whitelist, Blacklist VPN Server (PPTP, L2TP, OpenVPN, IPSec) VPN Client (N2N, PPTP, L2TP, OpenVPN, IPSec)

### Hardware

• 1/2 Intel Dual-core 2.41GHz CPU

• 1/2 2GB DDR3L RAM

• 1/2 16GB On board EMMC

• 1/2 HDMI (High-Definition Multimedia Interface)

• 1/2 Audio In/Out (Paging)

• 1/2 2x1000Mbps Ethernet Ports

• 1/2 USB 3.0 + USB

• 1/2 2.0 (Extended Storage)

• 1/2 2xModule Slots

### Telephony Signaling & Control

• 1/2 SIP (RFC3261)

• 1/2 SIP over UDP/TCP/TLS

• 1/2 IAX2

• 1/2 DTMF: RFC2833, SIP Info, In-band

• 1/2 SRTP

• 1/2 PRI, SS7, MFC/R2

### Power

• 1/2 AC 100~240V, 50/60Hz, 1.5A max

### Environment

• 1/2 Working Temperature: 0 ~ 40°C

• 1/2 Storage Temperature: -20 ~ 55°C

• 1/2 Humidity: 5 ~ 95% Non-condensing

**Price: £863.10**