

ZYCOO Coovox U80-PRO IP PBX Bundle



Product Name: ZYCOO Coovox U80-PRO IP PBX Bundle

Manufacturer: -

Model Number: U80-PRO

ZYCOO Coovox U80-PRO IP PBX - Coovox U80 system and 5 user UC PRO Standard perpetual licenses

The ZYCOO Coovox U80-PRO comprises of the ZYCOO Coovox U80 system and 5 user UC PRO Standard perpetual licenses. ZYCOO U80-PRO IP PBX Features

ï¿½ Includes ZYCOO Coovox U80 + 5 user UC PRO Standard perpetual licenses

ï¿½ PBX Features Up to 200 Extensions

ï¿½ Up to 60 Simultaneous Calls

ï¿½ Up to 40 Simultaneous Conference Attendees

ï¿½ Up to 36 Call Queues

ï¿½ Up to 36 Conference Rooms

ï¿½ Recording up to 150 hrs (WAV)

ï¿½ Recording up to 1500 hrs (GSM)

The ZYCOO Coovox-U80 IP PBX is a next-generation feature-rich IP PBX ideal for medium and large enterprises. The ZYCOO Coovox-U80 features up to 200 extensions and allows up to 60 simultaneous calls.

ZYCOO U80-PRO - Technical Specifications

PBX Features

ï¿½ Up to 200 Extensions

ï¿½ Up to 60 Simultaneous Calls

ï¿½ Up to 40 Simultaneous Conference Attendees

ï¿½ Up to 36 Call Queues

ï¿½ Up to 36 Conference Rooms

ï¿½ Recording up to 150 hrs (WAV)

ï¿½ Recording up to 1500 hrs (GSM)

ï¿½ Automatic Recording/One Touch Recording

ï¿½ CDR (Call Detailed Recording)

ï¿½ Multi-layer IVR (Interactive Voice Response)

ï¿½ TDM/SIP/IAX Extensions/trunks

ï¿½ Flexible Inbound/Outbound Routing

ï¿½ Time-based Routing

ï¿½ Remote Extensions & Remote Offices

ï¿½ Paging & Intercom

ï¿½ Video Call

ï¿½ Call Forward/Transfer

ï¿½ Web Extension (WebRTC)

ï¿½ Follow Me

ï¿½ DND (Do Not Disturb)

ï¿½ Ring Groups

ï¿½ Pick-up Groups

ï¿½ DISA (Direct Inward System Access)

ï¿½ Virtual Fax

ï¿½ Voicemail to Email/Fax to Email

ï¿½ One Number Stations

ï¿½ Smart DID

Media

ZYCOO Coovox U80-PRO IP PBX Bundle

• Audio Codecs: G.722/G.711-Ulaw/G.711-Alaw/G.726/G.729/GSM/SPEEX

• Video Codecs: H.261/H.263/H.263+/H.264 Fax: T.38 (passthrough)

Network & Protocols

• IPv4, IPv6, VLAN, DHCP, PPPoE, DDNS, SNMPv2, NTP, SNTP, TFTP, SSH, HTTPS, SRTP, TLS, LDAP, TR069

Security

• HTTPS, Fail2Ban, Permit IP, Whitelist, Blacklist VPN Server (PPTP, L2TP, OpenVPN, IPSec) VPN Client (N2N, PPTP, L2TP, OpenVPN, IPSec)

Hardware

• Intel Dual-core 2.41GHz CPU

• 2GB DDR3L RAM

• 16GB On board EMMC

• HDMI (High-Definition Multimedia Interface)

• Audio In/Out (Paging)

• 2x1000Mbps Ethernet Ports

• USB 3.0 + USB

• 2.0 (Extended Storage)

• 2xModule Slots

Telephony Signaling & Control

• SIP (RFC3261)

• SIP over UDP/TCP/TLS

• IAX2

• DTMF: RFC2833, SIP Info, In-band

• SRTP

• PRI, SS7, MFC/R2

Power

• AC 100~240V, 50/60Hz, 1.5A max

Environment

• Working Temperature: 0 ~ 40°C

• Storage Temperature: -20 ~ 55°C

• Humidity: 5 ~ 95% Non-condensing

Price: £863.10