Yealink T58A IP Phone (SIP-T58A)



Product Name: Yealink T58A IP Phone (SIP-T58A)
Manufacturer: -
Model Number: SIP-T58A

Please Note: The Yealink T58A has been discontinued. For an available alternative, please see the Yealink MP58 Smart Business IP Phone.

Please Note: Yealink T58A IP Phones are PoE and do not include a mains power supply. You can upgrade the T58A to use video conferencing using the Yealink Cam-50 already installed on the T58V model. Please also be aware that this device is interoperable with 2N's IP intercoms.

Yealink T58A 5-Way Audio Conferencing IP Phone (SIP-T58A)
The Yealink SIP-T58A is a modern smart-media IP phone, that is feature rich and simple to use. Business users can benefit from an enhanced HD audio and visual communication experience and features such as 5-way audio conferencing and built-in Wi-Fi (802.11b/g/n).
Yealink T58A Key Features

ï¿½ 7 inch (1024 x 600) capacitive adjustable touch screen
ï¿½ Interoperable with 2N’s IP intercom system
ï¿½ 5-Way Audio Conferencing
ï¿½ Built-in Bluetooth 4.0+ for headsets and pairing mobile devices
ï¿½ Built-in Wi-Fi (802.11b/g/n)
ï¿½ USB 2.0 port (2.0 compliant) for USB headset, media and storage applications
ï¿½ Up to 16 VoIP accounts
ï¿½ Wall-mountable

Based on Android 5.1.1 operating system, the SIP-T58A features a seven-inch adjustable multi-point touch screen, integrated Wi-Fi and Bluetooth4.0+ EDR, and it is coupled with a built-in web browser, calendar, recorder and more, which also support the installation of third-party applications for business customisation. The Yealink SIP-T5 Smart Media Phone Series strikes an exquisite balance between simplicity and sophistication, offering an all-in-one communications solution for today's busy executives, managers and teleworkers.

Yealink T58A - Technical Specifications
Audio Features

ï¿½ HD voice: HD handset, HD speaker
ï¿½ Hearing aid compatible (HAC) handset
ï¿½ Audio codec: Opus, G.722, G.722.1, G.722.1C,G.711 (A/µ), G.723, G.726, G.729AB, iLBC
ï¿½ DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
ï¿½ Full-duplex hands-free speakerphone with AEC
ï¿½ VAD, CNG, AEC, PLC, AJB, AGC

Display and Indicator

ï¿½ LCD screen:- 7" 1024 x 600 capacitive adjustable touch screen- Vertical tilt angle adjustable: 48°
ï¿½ 5 points multi-touch surface
ï¿½ Screensaver and Wallpaper

Yealink T58A IP Phone (SIP-T58A)

ï¿½ LED for call and message waiting indication
ï¿½ Intuitive user interface with icons and soft keys
ï¿½ Multilingual user interface
ï¿½ Caller ID with name, number and photo

Android bundled Applications

ï¿½ FileManager/Email/Calendar/Gallery/Recorder/Calculator/Browser/Message
ï¿½ Third party Android application support

Phone Features

ï¿½ 16 VoIP accounts
ï¿½ Call hold, call forward
ï¿½ Call waiting, call transfer
ï¿½ One-touch speed dial, hotline
ï¿½ Mute, DND
ï¿½ Group listening, emergency call
ï¿½ Redial, call return, auto answer
ï¿½ Direct IP call without SIP proxy
ï¿½ Ring tone select/import/delete
ï¿½ Set date time manually or automatically
ï¿½ Dial plan, action URL/URI
ï¿½ RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
ï¿½ Five-party audio
ï¿½ Data import/export via Bluetooth, email, etc.

IP-PBX Features

ï¿½ Busy Lamp Field (BLF)
ï¿½ Bridged Line Appearance (BLA)
ï¿½ Anonymous call, anonymous call rejection
ï¿½ Remote office, hot desking, intercom, paging
ï¿½ Message Waiting Indicator (MWI)
ï¿½ Voice mail, call park, call pickup, music on hold
ï¿½ Call completion, call recording

Directory

ï¿½ Local phonebook up to 1000 entries
ï¿½ Black list
ï¿½ XML/LDAP remote phonebook
ï¿½ Smart dialing
ï¿½ Phonebook search/import/export
ï¿½ Call history: dialed/received/missed/forwarded

Feature keys

ï¿½ 27 one-touch DSS keys
ï¿½ 8 feature keys: hold, transfer, message, headset, mute, redial,speakerphone, volume
ï¿½ Illuminated mute/headset/hands-free speakerphone key

Interface

ï¿½ Dual-port Gigabit Ethernet

Yealink T58A IP Phone (SIP-T58A)

ï¿½ Built-in Wi-Fi (2.4GHz, 802.11b/g/n)
ï¿½ Built-in Bluetooth 4.0+ EDR for- Bluetooth headsets- Pairing mobile devices
ï¿½ 1 x USB 2.0 port (on the rear of the phone) for:- USB flash drive- Wired/wireless USB headset- Colour-screen expansion modules
ï¿½ 1 x Security lock port
ï¿½ 1 x RJ9 (4P4C) handset port
ï¿½ 1 x RJ9 (4P4C) headset port
ï¿½ Supports up to 3 colour-screen expansion modules

Management

ï¿½ Configuration: browser/phone/auto provision
ï¿½ Auto provision via FTP/TFTP/HTTP/HTTPSfor mass deployment
ï¿½ Auto-provision with PnP, Zero-sp-touch, TR-069
ï¿½ Phone lock for personal privacy protection
ï¿½ Reset to factory, reboot
ï¿½ Package tracing export, system log
ï¿½ T56A&T58A&T58V unified firmware and common.cfg file
ï¿½ Only the administrator can install/uninstall apps via auto-provisioning
ï¿½ Setup Assistant wizard

Network and Security

ï¿½ IPv4/IPv6
ï¿½ SIP v1 (RFC2543), v2 (RFC3261)
ï¿½ Call server redundancy supported
ï¿½ NAT traversal: STUN mode
ï¿½ Proxy mode and peer-to-peer SIP link mode
ï¿½ IP assignment: static/DHCP/PPPoE
ï¿½ HTTP/HTTPS web server
ï¿½ Time and date synchronisation using SNTP
ï¿½ UDP/TCP/DNS-SRV (RFC 3263)
ï¿½ QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
ï¿½ SRTP
ï¿½ Transport Layer Security (TLS)
ï¿½ HTTPS certificate manager
ï¿½ AES encryption for configuration file
ï¿½ Adb encryption authenticated
ï¿½ Digest authentication using MD5/MD5-sess
ï¿½ OpenVPN, IEEE802.1X

Other Physical Features

ï¿½ Wall mountable (optional)
ï¿½ External Yealink AC adapter (optional):AC 100~240V input and DC 5V/2A output
ï¿½ Power consumption (PSU): 1.9W-5.7W
ï¿½ Power consumption (PoE): 2.6W-7.4W
ï¿½ Dimension (W*D*H*T):259.4mm*220mm*239mm*42.6mm
ï¿½ Operating humidity: 10~95%
ï¿½ Operating temperature: -10~40°C

Package Features

ï¿½ Package content:- Yealink SIP-T58V IP phone- Handset with handset cord- Ethernet Cable (2m CAT5E FTP Cable)- Stand- Quick Start Guide- Power Adapter (Optional)

Yealink T58A IP Phone (SIP-T58A)

ï¿½ Qty/CTN: 5 PCS
ï¿½ N.W/CTN: 9.45 kg
ï¿½ G.W/CTN: 10.55 kg
ï¿½ Giftbox size: 324 mm*293 mm*128 mm
ï¿½ Carton Meas: 680 mm*303 mm*332 mm

Please Enquire

Options available for Yealink T58A IP Phone (SIP-T58A) :

Compatible Headsets

Grandstream GUV3000 HD USB Headset (+$44.21), JPL Connect-1 monaural headset and disconnect cord (+$82.35), Yealink UH36 Mono USB Headset (+$60.00), Yealink YHS33 IP Headset (+$44.33), Grandstream GUV3005 HD USB Headset with busy-light (+$85.89), JPLConnect-2 binaural headset and disconnect cord (+$96.31), Yealink UH36 Dual USB Headset (+$71.05), Not Required, Yealink UH33 USB Headset (+$30.31).

Compatible Wireless Headsets

Plantronics CS540 EHS Wireless headset and adapter (+$271.64), Not Required, Plantronics CS520 Binaural wireless EHS headset and adapter (+$329.53), Jabra Pro 920 Mono with remote handset lifter (+$174.05).

Power Supply Required?

None - Using PoE, UK-PSU-5V-2A (+$10.86).

Expansion Module Required?

Not Required, Yealink EXP50 Colour-screen Expansion Module (+$84.00).

DECT USB Dongle Required?

Not Required, Yealink DECT USB Dongle DD10K (+$18.44).