



Product Name: Spectralink 8452 EU Blue Handset Lync & SIP

Manufacturer: -

Model Number: 2200-37198-101

Please Note: This product is end of life. For an alternative, please see the other Spectralink phones.

Spectralink 8452 EU Blue Handset Lync & DP

The Spectralink 8452 EU Blue Handset Lync & Delivers on a fundamental need for enterprise-grade on-site voice mobility. Characterized by market-leading HD voice quality, durability, broad telephony and WLAN interoperability, the Spectralink 84-Series handsets deliver a reliable user experience and predictable return on investment. Spectralink 8452 EU Blue Features

า๊¿½ Four (4) context-sensitive softkey buttons

آزٰ½ Push-to-Talk

า๊¿½ Five-way navigation and select control

� Home & amp; Back navigation keys

� Up/Down volume control

ï¿1/2 Barcode reader (8452/8453 handsets)

ï¿⅓ Start and End Keys

� Panic/Duress

And with Spectralink VQO built into every 84-Series device, you get an engineered system that delivers superior voice quality. Spectralink VQO links seamlessly to access points using a proprietary, adaptive, algorithm. And only advanced, guided implementation by the Spectralink experts can ensure crystal-clear communication.

The Spectralink 84-Series enhances the customer value proposition through an optional integrated barcode scanner and an enhanced standards-based applications interface. In partnership with the Spectralink applications development ecosystem, the Spectralink 84-Series products enable new opportunities for end-user productivity solutions.

Spectralink 8452 EU Blue - Technical Specifications DISPLAY

� 2.2 in. (55.9 mm)� 240 x 320 resolution� 65,000 color palette

STATUS LED

� Message (voicemail) waiting

� Out of coverage

� Phone ringing

PERIPHERAL INTERFACES

īപ് Micro USB interface for wall charging and configuration

� 2.5mm connector for wired headset

تز½ Bluetooth

BATTERIES



- i¿½ Two easy-access cosmetic battery capacity options
- آذِرُ Standard Up to 8 hrs talk time, 80hrs standby time
- � Enhanced Up to 12 hrs talk time, 120hrs standby time May vary based on scanner, applications usage, screen brightness settings, etc.

DURABILITY

- i¿½ Drop/shock: MIL STD 810F, method 516.5 procedure IV
- ii ໄ 1 Ingress protection standard: IP 64 per IEC 60529
- ï¿1/2 Rubberized molding
- � Magnesium LCD mounting

ENVIRONMENTAL

- آذِرً Operational temperature: 32 104° F (0 40° C)
- � Storage temperature: -22 -140° F (-30 60° C)

DIMENSIONS

ī¿½ Dimensions 5.8 x 2.1 x 1.0 inc. (147 x 53 x 25 mm) 5.7 x 2.1 x 1.3 in. (146 x 54 x 34 mm)

Wi-Fi

ï¿⅓ BAND FREQUENCY DATA RATES

ัเ¿½ 802.11a5.15 - 5.25 GHz5.25 - 5.35 GHz5.47 - 5.725 GHz5.725 - 5.825 GHz6, 9, 12, 18, 24, 36,48, 54 Mbps

� 802.11b 2.4 - 2.4835 GHz 1, 2, 5.5, 11 Mbps

� 802.11g 2.4 - 2.4835 GHz6, 9, 12, 18, 24, 36, 48, 54 Mbps

าั¿½ 802.11n* 2.4 & DHz21.7, 43.3, 65, 72.2 Mbps2.4GHz and 5GHz dynamic band roaming supported*Single-stream, 20MHz channel with SGI

Bluetooth Headset Support

- ï¿1/2 Version 2.1, HSP Version 1.2
- � Class 1 support with range of ~10 meters

CALL HANDLING FEATURES*

- � Up to six (6) telephone line appearances
- ï¿1/2 Call Hold/Resume function
- � Last Call Return
- � Music on Hold
- تز½ Consultation Hold
- � Call Transfer (Attended, Unattended)
- تزير Overlap dialing
- � Bridged Line Appearance (BLA)
- � Three-Way Conferencing (local)
- ï¿⅓ Find-Me call forking
- ï¿1/2 Call Screening (Incoming, Outgoing)
- � Automatic Answer
- ï¿1/2 Call Park & amp; Retrieve
- � Group Call Pickup
- � Call Waiting
- ï¿⅓ Multiple Calls per Line



- آز½ Do Not Disturb
- آذِ 1/2 Calling party ID (Name and Number)
- � Called party ID (Name and Number)
- آذِ1/2 Connected party ID (Name and Number)
- าั¿½ Call Forward (Busy, No Answer, Unconditional)
- าั¿½ Call Reject*Summary only actual feature support will vary among call platforms

CODECS

� G.711 (a-law, u-law), G.729, G.722, G.722.1

PUSH-TO-TALK (PTT)/PAGING

- تزير On-board native ' walkie-talkie' capability
- � One-to-one, one-to-many broadcast communication
- � 24 configurable channels
- � Priority, default channel

ADDITIONAL TELEPHONY FEATURES

- � RTCP (RFC 3550, RFC 1889)
- � Call server redundancy
- � Predictive dialing from contacts list
- ï¿⅓ Recent call lists

USER PROFILES

i¿1/2 Downloadable to any handset with ID and Login

PERSONAL SAFETY

- � Duress/Panic button
- ï¿1/2 No motion, running, tilt detection
- ï¿⅓ Alarm notifications

ADDITIONAL

- ï¿⅓ Intuitive Graphical User Interface
- ï¿1/2 Selectable wallpaper/background
- � Adjustable display brightness
- า๊¿1/2 Backlit keypad with adjustable timeout period
- � Ten (10) selectable ring tones
- ï¿1/2 Ten (10) selectable alert tones
- ï¿⅓ Multiple vibrate cadence options
- � Vibrate-to-ring options
- ï¿1/2 Audible and vibrate notification options
- ï¿1/2 Speed dial menu list
- � Contacts directory with support for 1000 local entries
- � Call logs Minimum of 20 logged entries for each call type (Incoming, dialed, and missed)
- � Emergency system-wide speed dial
- � Auto-answer & amp; any key answer capability
- ï¿1/2 Selectable ring tones
- 12/2 Unicode UTF-8 Multilingual User Interface

PROVISIONING



- าั¿½ Server based central provisioning via FTP, FTPS, TFTP, HTTP or HTTPS
- � Centralized user administration
- � Provisioning and call server redundancy
- ï¿1/2 Initial configuration via USB
- � Unicode UTF-8 Multilingual User Interface

PERFORMANCE AND FAULT MANAGEMENT

- � On-board site survey and diagnostics tools
- � Enhanced syslog reporting
- � Roaming and handoff reporting
- � Event logging
- � Hardware diagnostics
- ï¿1/2 Status and status reporting
- � PING support (initiate and response)
- � Traceroute

CONFIGURATION MANAGEMENT

- � User and administrator login and privileges
- ī¿½ PC-connected (USB) and remote over-the-air configuration management

XML APPLICATIONS PROGRAM INTERFACE

- � Standards-based XHTML API
- าั¿½ On-board WebKit-based browser (JavaScript, CSS, DOM) for rich applications integration
- ï¿1/2 Corporate directory access LDAP

SPECTRALINK OPEN APPLICATION INTERFACE (OAI)

i¿1/2 Backward compatibility with Spectralink OAI applications

INSTANT MESSAGING

� Handset-to-handset, PC client-to-handset IM support via Microsoft® OCS and/or Microsoft Lync

REAL TIME LOCATION SERVICES (RTLS)

า๊¿½ Embedded RTLS beacon (Ekahau) for location tracking

� AeroScout

CALENDAR - EXCHANGE SERVER INTEGRATION

- � Day and month view
- ï¿⅓ Meeting reminders

AUDIO QUALITY

- آز½ TIA 810B, TIA 920 audio quality standards
- آذِاً½ Full-duplex audio (compliant with IEEE 1329 full duplex standards)
- � Voice activity detection (VAD)
- � Comfort noise fill
- า๊¿½ Adaptive jitter buffer & packet loss concealment



ī సైస్త Acoustic echo cancellation & amp; background noise suppression

QUALITY OF SERVICE (QOS)

تزار Wi-Fi Multimedia (WMM)

ï¿⅓ WMM-Power Save

� WMM-Admission Control (draft)

ï¿1/2 IEEE 802.1p/Q tagging (VLAN)/DSCP tagging

SECURITY

� WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-FAST, PEAP-MSCHAPv2) with Opportunistic Key Caching (OKC) and Cisco Client Key Management (CCKM)

า๊ะ/2 Media encryption via Secure Real-Time Protocol (SRTP)

ī¿½ SIP signaling encryption via Transport Layer Security (TLS)

� Server-based configuration file encryption (AES 128 bit)

� HTTPS secure provisioning

� Support for signed software executables

Strong support for networking standards

าั¿½ Address assignment via Manual or Dynamic host configuration protocol (DHCP)

រី¿½ Domain name resolution via Domain Name Service (DNS)

Title Time and date synchronization using Simple Network Time Protocol (SNTP)

17.11/2 Lightweight Directory Access Protocol (LDAP) for directory lookup and download

آزا IEEE 802.1p/Q tagging (VLAN)/DSCP tagging

High-performance scanning

� Type 1D/2D Area Imagers

آز½ Light Source 617 nm Highly Visible LED (5)

تزاري Scan Angle 38.9° Horiz., 25.4° Vert.

ï¿1/2 Label print contrast Down to 25%

ï¿⅓ Resolution Optical Resolution 752 x 480 pixels

آز½ Reading distance Up to 34 in. (864 mm)

BARCODE SYMBOLOGIES

ī¿½ 1D: RSS, Stacked RSS, RSS-14, GS1-DataBar, Code 39, Code 93, Code 128, UPC (E&A)

ī¿½ 2D: Aztec, Codabar, Code 11, Code 39, Code 93/93I, Code 128, GS1-128, ISBT8, Databar (RSS), Datamatrix, EAN13, EAN8, Interleaved 2 of 5, Micro PDF 417, MSI, PDF 417, Plessey, QC code, Telepen, UPCA, UPCE, UPC/EAN

Please Enquire

Options available for Spectralink 8452 EU Blue Handset Lync & SIP:

Spectralink 8400 Series Standard Battery

Not Required,



Required (+£55.70).

Spectralink 8400 Series Dual Charger and PSU

Required (+£81.40), Not Required.