

## Yealink T52S Smart Media Phone (SIP-T52S)



Product Name: Yealink T52S Smart Media Phone (SIP-T52S)

Manufacturer: -

Model Number: SIP-T52S

Please Note: Please Note: This product is no longer available. Please see alternative products in our Yealink VoIP Phones section.

Please Note: Yealink T52S IP Phones are PoE (Powered-Over-Ethernet) and do not include a mains Power Supply. If mains power is required, this can be added via the drop down menu above.

Yealink T52S Smart Media Phone (SIP-T52S)

The Yealink T52S is a feature rich and easy to use smart media VoIP phone. The SIP-T52S comes with a 2.8-inch colour screen, Up to 12 VoIP accounts, Built-in Bluetooth 2.1 and a distinctive appearance and structure. Yealink T52S Key Features

- Up to 12 VoIP accounts
- New structure design
- 2.8" 320 x 240-pixel colour display with backlight
- Built-in Bluetooth 2.1
- USB 2.0 port for USB recording and wired/wireless USB headsets
- Opus Codec support
- T54S&T52S firmware and Auto-P template unified
- Dual-port Gigabit Ethernet
- PoE support
- Paperless label design
- Wi-Fi via WF40
- Color-screen Expansion Module support
- Stand with 2 adjustable angles

The Yealink SIP-T52S builds in Gigabit Ethernet technology, Bluetooth and a USB 2.0 port for enhanced collaboration and productivity. Yealink SIP-T52S is designed to satisfy users who need a higher cost-performance IP phone with improvement in hardware, audio quality, user experience and collaboration efficiency. The T52S also enhances its audio quality via adding Opus audio codec, so that it delivers superb audio quality and crystal clear voice communications.

Yealink T52S - Technical Specifications

Audio Features

- HD voice: HD handset, HD speaker
- Hearing aid compatible (HAC) handset
- Audio codec: Opus, G.722, G.711 (A/&micro;), G.723, G.723.1, G.726, G.729AB, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 12 VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call

## Yealink T52S Smart Media Phone (SIP-T52S)

- Redial, call return, auto answer
- 3-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan, XML Browser, Action URL/URI
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Built-in Bluetooth for: Bluetooth headset, Mobile contacts synchronization
- USB port (2.0 compliant) for: wired/wireless USB headset, Wi-Fi through WF40, USB call recording through USB flash drive
- Enhanced DSS key

### Directory

- Local phonebook up to 1000 entries
- Blacklist
- XML/LDAP remote phonebook
- Smart dialing
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded

### IP-PBX Features

- Busy Lamp Field (BLF)
- Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Hot-desking, voice mail
- Flexible seating
- Call park, call pickup
- Executive and Assistant
- Centralized call recording
- Call recording

### Display and Indicator

- 2.8" 320 x 240-pixel color display with backlight
- 16 bit depth color
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Screensaver
- Power saving

### Feature keys

- 8 line keys with LED
- 8 line keys can be programmed up to 21 various features (3-page view)
- 5 features keys: mute, headset, message, redial, hands-free speakerphone
- 4 context-sensitive "soft" keys
- 6 navigation keys
- Volume control keys
- Illuminated mute key

## Yealink T52S Smart Media Phone (SIP-T52S)

- 1/2 Illuminated headset key
- 1/2 Illuminated hands-free speakerphone key Interface
- 1/2 Dual-port Gigabit Ethernet
- 1/2 Power over Ethernet (IEEE 802.3af), class 3
- 1/2 1 x USB port (2.0 compliant)
- 1/2 1 x RJ9 (4P4C) handset port
- 1/2 1 x RJ9 (4P4C) headset port
- 1/2 Supports up to 3 color-screen expansion modules

### Management

- 1/2 Configuration: browser/phone/auto-provision
- 1/2 Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- 1/2 Auto-provision with PnP
- 1/2 Broadsoft device management
- 1/2 Zero-sp-touch, TR-069
- 1/2 Phone lock for personal privacy protection
- 1/2 Reset to factory, reboot
- 1/2 Package tracing export, system log
- 1/2 T54S&T52S unified firmware and Auto-P template

### Network and Security

- 1/2 SIP v1 (RFC2543), v2 (RFC3261)
- 1/2 Call server redundancy supported
- 1/2 NAT traversal: STUN mode
- 1/2 Proxy mode and peer-to-peer SIP link mode
- 1/2 IP assignment: static/DHCP/PPPoE
- 1/2 HTTP/HTTPS web server
- 1/2 Time and date synchronization using SNTP
- 1/2 UDP/TCP/DNS-SRV(RFC 3263)
- 1/2 QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- 1/2 SRTP for voice
- 1/2 Transport Layer Security (TLS)
- 1/2 HTTPS certificate manager
- 1/2 AES encryption for configuration file
- 1/2 Digest authentication using MD5/MD5-sess
- 1/2 OpenVPN, IEEE802.1XIPv6, LLDP/CDP/DHCP VLAN, ICE

### Other Physical Features

- 1/2 > Stand with 2 adjustable anglesWall mountable (optional)External Yealink AC adapter (optional): AC 100~240V input and DC 5V/2A output
- 1/2 Power consumption (PSU): 1.9W-3.4W
- 1/2 Power consumption (PoE): 2.1W-4.0W
- 1/2 Dimension (W\*D\*H\*T): 211.6mm\*212.0mm\*166.8mm\*42.6mm
- 1/2 Operating humidity: 10~95%
- 1/2 Operating temperature: -10~40deg;C (+14~104deg;F)

### Package Features

- 1/2 Package content:- Yealink SIP-T52S IP phone- Handset with handset cord- Ethernet Cable- Stand- Quick Start Guide- Power Adapter (Optional)
- 1/2 Qty/CTN: 5 PCS
- 1/2 N.W/CTN: 6.4 kg

## Yealink T52S Smart Media Phone (SIP-T52S)

1 1/2 G.W/CTN: 7.1 kg

1 1/2 Giftbox size: 249 mm\*255 mm\*128 mm

1 1/2 Carton Meas: 660 mm\*263 mm\*261 mm

**Please Enquire**

---

Options available for Yealink T52S Smart Media Phone (SIP-T52S) :

### **Power Supply Required?**

EU PSU required (+£10.00), UK PSU 10V Required (+£10.00), None - Using PoE.

### **Wi-Fi USB Dongle Required?**

Yealink WF40 Wi-Fi USB Dongle (+£33.54), Not Required.