Snom D712 IP Phone



Product Name: Snom D712 IP Phone
Manufacturer: -
Model Number: D712

Please Note: This product has been discontinued. Please see the Snom D713 IP Phone for an available alternative.

Snom D712 IP Phone
The Snom D712 is a state-of-the-art, full-featured IP desk phones for small or large scale deployments suitable for use in a multitude of business scenarios. With the benefits of 4 SIP identities and 5 programmable keys with backlit graphical display, 4 lines, the D712 is a sleek and modern IP phone that is a great option for range of proffessionals at a great price.
Snom D712 Key Features

ï¿½ Supports up to 4 SIP accounts
ï¿½ 4-line black and white backlit graphical display
ï¿½ 4 context-sensitive keys
ï¿½ 2 x 10/100 Mbps Ethernet Switch (RJ45)
ï¿½ PoE support (PSU available separately)
ï¿½ IPv6 capable5 configurable function keys with LEDs
ï¿½ Wideband hands-free talking (speakerphone)

The D712 delivers a rich set of business telephony features critical to today's real-time, information-driven business workforce. Built for HD audio, it provides superior, crystal-clear end-to-end call quality. Its sleek ergonomic design includes an advanced speaker and microphone system and supports a broad range of audio codecs. Like all Snom desktop phones, the D712 features Snom’s security, interoperability and SIP firmware.
Snom D712 - Technical Specifications
Benefits

ï¿½ Backlit graphical display, 4 lines
ï¿½ Dual-angle foot stand: 46° and 28°
ï¿½ Wall mountable
ï¿½ Hands-free talking (speakerphone)
ï¿½ Digital Signal Processor (DSP) enhanced audio quality
ï¿½ 2-port 10/100 Mbps Ethernet switch (RJ45)
ï¿½ Power over Ethernet IEEE 802.3af, Class 1
ï¿½ Electronic Hook Switch (EHS)(1) support for wireless headsets
ï¿½ IPv6

Features

ï¿½ 4 SIP identities / accounts
ï¿½ XML browser
ï¿½ Call lists for dialled, received, missed calls
ï¿½ Local directory with 1000 entries
ï¿½ Multiple language support
ï¿½ DTMF in-band / out-of-band / SIP-INFO
ï¿½ Interoperable with all major IP PBX platforms
ï¿½ Call Features

Call Features

Snom D712 IP Phone

ï¿½ Speed dialing
ï¿½ URL Dialling
ï¿½ Local dial plan
ï¿½ Automatic redial on busy
ï¿½ Call completion (busy/unreachable)(2)
ï¿½ Caller identification
ï¿½ Call waiting
ï¿½ Call blocking (deny list)
ï¿½ Auto answer
ï¿½ Hold
ï¿½ Music on hold(2)
ï¿½ Handling of up to 4 simultaneous calls
ï¿½ Blind and attended transfer
ï¿½ Call forwarding
ï¿½ 3-way conferencing on the phone
ï¿½ Extension monitoring, call pickup(2)
ï¿½ Call park, call unpark(2)
ï¿½ Multicast paging
ï¿½ DND mode (do not disturb)
ï¿½ Keyboard lock
ï¿½ Client matter code (CMC)(2)
ï¿½ Unified communications ready

Audio

ï¿½ Codecs:G.711 A-law, μ-lawG.722 (wideband)G.726, G.729AB, GSM 6.10 (FR)
ï¿½ Built-in assignable ringtones
ï¿½ Comfort Noise Generator (CNG)
ï¿½ Voice Activity Detection (VAD)

Setup

ï¿½ Configuration via web interface
ï¿½ Provisioning:Automatic loading of settings via HTTP/HTTPS/TFTPDHCP Options 66/67Snom Redirection ServiceRemote management via TR-069 / TR-111

Protocols

ï¿½ SIP (RFC3261)
ï¿½ DHCP, NTP
ï¿½ HTTP / HTTPS / TFTP
ï¿½ LDAP (Directory)
ï¿½ Dual Stack IPv4 / IPv6

User Interface

ï¿½ Localization (language, time, dial tone)
ï¿½ Red LED for call indication/message waiting
ï¿½ 4 context-sensitive keys
ï¿½ 5 programmable line/function keys with green LEDs
ï¿½ Paper inlay for labelling of function keys
ï¿½ Dedicated message key
ï¿½ Audio keys with LED indication: Mute, speakerphone, headset
ï¿½ Volume key
ï¿½ 4-way navigation key

Snom D712 IP Phone

ï¿½ OK and Cancel
ï¿½ Menu-driven user interface

Security

ï¿½ 802.1X Authentication and EAPOL
ï¿½ Transport layer security (TLS)
ï¿½ SRTP (RFC3711), SIPS, RTCP
ï¿½ HTTPS server/client
ï¿½ Password-protected web interface
ï¿½ VPN support
ï¿½ VLAN (IEEE 802.1Q)
ï¿½ LLDP-MED, RTCP-XR

Phone Features

ï¿½ Dimensions (approx.):205 x 185 x 40 mm (LxWxD) w/o footstand205 x 185 x 200/220 mm (LxWxD) with footstand
ï¿½ Weight (approx.): device 440 g, footstand 120 g
ï¿½ Input voltage: 5 Vdc (SELV)
ï¿½ Power supply: PoE or 5Vdc power adapter (1)
ï¿½ Handset: 4P4C connector
ï¿½ Headset: 4P4C
ï¿½ Hearing aid compatible (HAC) handset
ï¿½ Environmental conditions:
ï¿½ Ambient temperature: 0°C to 35°C (32°F to 95°F)
ï¿½ Storage temperature: -10°C to 45°C (14°F to 113°F)
ï¿½ Humidity: 5% to 95% (non-condensing)
ï¿½ Included in delivery:Phone unitFootstandHandset with cordEthernet cableQuick Installation Guide
ï¿½ Color: blackWarranty: 2 YearsPart Number: 00004353 (all markets

Accessories

ï¿½ (1) Optional accessory (see below for part numbers)(2) If supported by PBX
ï¿½ Part numbers for optional accessories
ï¿½ 00004325 Power Adapter A6 with EU clip
ï¿½ 00004326 Power Adapter A6 with US clip
ï¿½ 00001168 UK clip for Power Adapter A6
ï¿½ 00001167 AUS clip for Power Adapter A6
ï¿½ 00002362 Snom EHS Advanced
ï¿½ 00004341 Monaural Headset Snom A100M
ï¿½ 00004342 Binaural Headset Snom A100D

Please Enquire

Options available for Snom D712 IP Phone :

Need Product Setup / Training / Support?

Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00), Not Required.

Snom D712 IP Phone

Power Supply Required?

Not Required, 1 x UK Power Supply Required (+£10.00).

Snom A100D Wideband Binaural Headset

Not Required, Required (+£49.10).

Snom A100M Wideband Monaural Headset

- Not Required -, Required (+£43.90).

Snom A170 Wireless DECT Headset

- Not Required -, Required (+£183.10).