

## Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway



Product Name: Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway

Manufacturer: -

Model Number: UC2000-VG-32GM

Please Note: This product has been discontinued. Please see the Dinstar UC2000-VG-32G 32 Port GSM VoIP Gateway for an available alternative.

Dinstar UC2000-VG-32GM 32 Port GSM Channels Built in Antenna combiner Quad-band 850/900/1800/1900 MHz G.711.G.723.1.G.729A IMEI Changer Support SIMBank  
The Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway is a multi-functional product used to effectively implement the smooth transition between PLMN (Mobile) and VoIP network. The UC2000-VG gateway is designed for comfort, ease-of-use to satisfied necessary of customers. It is not only inherits tradition of quality voice communication over IP network but reduce the human resource of VoIP network deployment. It's a cost-effective gateway for call termination (VoIP to GSM) and origination (GSM to VoIP). It is fully compatible with leading Soft-switch and SIP server.  
Dinstar UC2000-VG-32GM Key Features

- 32 GSM Channels with 128 SIM Slots, Easy to Conduct SIM Rotation Locally
- GSM: 850/900/1800/1900MHz; CDMA: 800MHz; WCDMA: 850/900/1900/2100MHz
- Built-in Bandwidth Saving, Signaling&RTP Encryption
- HTTP API for Bulk SMS
- Auto Call/SMS Generation
- Auto Update SIM Number and Balance Check
- No Balance Alarm and Call Minutes Limitation

### Dinstar UC2000-VG-32GM - Technical Specifications

#### Voice Processing

- Protocol: SIP v2.0, RFC3261
- Codecs:G.711A/U law, G.723.1, G.729A/B
- Silence Suppression
- Comfort Noise Generator(CNG)
- Voice Activity Detection(VAD)
- Echo Cancellation: G.168 with up to 128ms
- Dynamic Jitter Buffer
- DTMF: RFC2833, SIP Info
- Call Progress Tone Generation
- Programmable Gain Control
- NAT: STUN, Dynamic NAT, Static NAT

#### Mobile

- SIM Interface: 1.8v, 3.0v SIM Interface
- Frequency Range:GSM: 850/900/1800/1900MHz; CDMA: 800MHzWCDMA:850/900/1900/2100MHz
- USSD Encoding: Unicode/ASCII
- HTTP API for SMS
- Polarity Reversal
- PIN Modify
- Carrier Auto/Manual Selection
- CID/CLIR
- BCCH
- SMS Send and Receive

## Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway

• SMS to Email  
• Call Waiting/Call Back  
• Call Forward  
• GSM Audio Coding: HR, FR, EFR, AMR\_FR, AMR\_HR

### Software Features

• Calling Type: Mobile to VoIP, VoIP to Mobile  
• SIP Trunk and Trunk Group  
• Caller/Called Number Manipulation Rules  
• SIP Codes Mapping  
• White/Black List  
• PSTN Hotline  
• VoIP Hotline  
• Password authentication for incoming and outgoing calls  
• Abnormal Call Monitor  
• Call Minutes Limitation for Ports/Single Call  
• Auto SMS/Call Generation  
• Balance Check  
• Low Balance Alarm  
• Auto Update SIM Number  
• Random Call Interval  
• Abnormal Call Monitor  
• SIM Rotating by SIM Run Time  
• SIM Balance Bandwidth Saving  
• Signaling & RTP Encryption

### Network

• Static IP, DHCP Client, PPPoE  
• Network Protocols: TCP/UDP, TFTP, FTP, RTP/RTCP, SSH, ARP, RARP, ICMP Ping, NTP, HTTP, DNS  
• Static/Dynamic ARP Request

### Maintenance

• Web/Telnet Configuration  
• Configure Backup/Restore  
• Firmware Upgrade by HTTP/TFTP  
• Factory Reset  
• CDR (10000 Lines CDRs Storage Locally)  
• Syslog/Filelog  
• Ping and Tracert  
• Traffic statistics: TCP, UDP, RTP  
• VoIP Call Statistics  
• PSTN Call statistics: ASR, ACD, PDD  
• Voice Dialogist with Loopback  
• GSM Network Dialogist  
• IVR Customization  
• Auto Provisioning  
• SIP/RTP/PCM Capture

### Physical Interface

• Mobile: 32 GSM Channels  
• SIM Card Slots: 128

## Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway

• Ethernet Interfaces: 2\*10/100 Base-T, RJ45  
• LED Indicators: Power, RUN, Signal Strength Indicators  
• Console: 1\* RS232 115200bps

### Environmental

• Power Supply: 100-240VAC, 50-60Hz  
• Power Consumption: 68w  
• Operating Temperature: 0 °C ~ 40 °C; Storage Temperature: -20 °C ~ 80 °C  
• Humidity: 10%-90% Non-Condensing  
• Dimensions (W/D/H): 440\*270\*75mm  
• Unit Weight: 4.7kg

**Please Enquire**

---