

Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway



Product Name: Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway

Manufacturer: -

Model Number: UC2000-VG-32GM

Please Note: This product has been discontinued. Please see the Dinstar UC2000-VG-32G 32 Port GSM VoIP Gateway for an available alternative.

Dinstar UC2000-VG-32GM 32 Port GSM Channels Built in Antenna combiner Quad-band 850/900/1800/1900 MHz G.711.G.723.1.G.729A IMEI Changer Support SIMBank
The Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway is a multi-functional product used to effectively implement the smooth transition between PLMN (Mobile) and VoIP network. The UC2000-VG gateway is designed for comfort, ease-of-use to satisfied necessary of customers. It is not only inherits tradition of quality voice communication over IP network but reduce the human resource of VoIP network deployment. It's a cost-effective gateway for call termination (VoIP to GSM) and origination (GSM to VoIP). It is fully compatible with leading Soft-switch and SIP server.
Dinstar UC2000-VG-32GM Key Features

- 32 GSM Channels with 128 SIM Slots, Easy to Conduct SIM Rotation Locally
- GSM: 850/900/1800/1900MHz; CDMA: 800MHz; WCDMA: 850/900/1900/2100MHz
- Built-in Bandwidth Saving, Signaling&RTP Encryption
- HTTP API for Bulk SMS
- Auto Call/SMS Generation
- Auto Update SIM Number and Balance Check
- No Balance Alarm and Call Minutes Limitation

Dinstar UC2000-VG-32GM - Technical Specifications

Voice Processing

- Protocol: SIP v2.0, RFC3261
- Codecs:G.711A/U law, G.723.1, G.729A/B
- Silence Suppression
- Comfort Noise Generator(CNG)
- Voice Activity Detection(VAD)
- Echo Cancellation: G.168 with up to 128ms
- Dynamic Jitter Buffer
- DTMF: RFC2833, SIP Info
- Call Progress Tone Generation
- Programmable Gain Control
- NAT: STUN, Dynamic NAT, Static NAT

Mobile

- SIM Interface: 1.8v, 3.0v SIM Interface
- Frequency Range:GSM: 850/900/1800/1900MHz; CDMA: 800MHzWCDMA:850/900/1900/2100MHz
- USSD Encoding: Unicode/ASCII
- HTTP API for SMS
- Polarity Reversal
- PIN Modify
- Carrier Auto/Manual Selection
- CID/CLIR
- BCCH
- SMS Send and Receive

Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway

• SMS to Email
• Call Waiting/Call Back
• Call Forward
• GSM Audio Coding: HR, FR, EFR, AMR_FR, AMR_HR

Software Features

• Calling Type: Mobile to VoIP, VoIP to Mobile
• SIP Trunk and Trunk Group
• Caller/Called Number Manipulation Rules
• SIP Codes Mapping
• White/Black List
• PSTN Hotline
• VoIP Hotline
• Password authentication for incoming and outgoing calls
• Abnormal Call Monitor
• Call Minutes Limitation for Ports/Single Call
• Auto SMS/Call Generation
• Balance Check
• Low Balance Alarm
• Auto Update SIM Number
• Random Call Interval
• Abnormal Call Monitor
• SIM Rotating by SIM Run Time
• SIM Balance Bandwidth Saving
• Signaling & RTP Encryption

Network

• Static IP, DHCP Client, PPPoE
• Network Protocols: TCP, UDP, TFTP, FTP, RTP/RTCP, SSH, ARP, RARP, ICMP Ping, NTP, HTTP, DNS
• Static/Dynamic ARP Request

Maintenance

• Web/Telnet Configuration
• Configure Backup/Restore
• Firmware Upgrade by HTTP/TFTP
• Factory Reset
• CDR (10000 Lines CDRs Storage Locally)
• Syslog/Filelog
• Ping and Tracert
• Traffic statistics: TCP, UDP, RTP
• VoIP Call Statistics
• PSTN Call statistics: ASR, ACD, PDD
• Voice Dialogist with Loopback
• GSM Network Dialogist
• IVR Customization
• Auto Provisioning
• SIP/RTP/PCM Capture

Physical Interface

• Mobile: 32 GSM Channels
• SIM Card Slots: 128

Dinstar UC2000-VG-32GM 32 Port GSM VoIP Gateway

• Ethernet Interfaces: 2*10/100 Base-T, RJ45
• LED Indicators: Power, RUN, Signal Strength Indicators
• Console: 1* RS232 115200bps

Environmental

• Power Supply: 100-240VAC, 50-60Hz
• Power Consumption: 68w
• Operating Temperature: 0 °C ~ 40 °C; Storage Temperature: -20 °C ~ 80 °C
• Humidity: 10%-90% Non-Condensing
• Dimensions (W/D/H): 440mm*270mm*75mm
• Unit Weight: 4.7kg

Please Enquire
