

RTX 4022 DECT Repeater



Product Name: RTX 4022 DECT Repeater

Manufacturer: -

Model Number: RTX4022

Please Note: This product has been discontinued. Please see the Snom Wireless VoIP Phones for an alternative.

RTX 4022 DECT Repeater

A RTX 4022 DECT Repeater can be deployed when a need to extend the range of a DECT telephone arises. The repeater can also be utilized wherever there is a need to increase limited coverage or improve reception in remote areas.

RTX 4022 Key Features

- าั¿½ RTX is the world leading supplier of repeaters and an obvious choice as your future supplier.
- آذِيً Technically superior at the best price on the market.
- าั¿½ Double the range of a DECT base station or achieve up to 2.4 km range with the Professional edition.
- � Possibility to register multiple repeaters.
- ī¿½ Superior audio quality both narrow band and wide band.

RTX 4022 - Technical Specifications

GENERAL FEATURES

- ï¿⅓ Worldwide DECT support
- � Extending the DECT coverage
- i¿1/2 Supports automatic handover of calls between cells
- ï¿1/2 Handling of 2 active calls simultaneously
- � Up to 6 repeaters per base station
- � Automatic registration method
- าั¿½ Environmental conditions: temp range, from -10°C to +50°C

DESIGN/SIZE

- ï¿⅓ Indoor cabinet
- � Manual mounting kit
- � Easily mounted on walls
- $\ddot{\imath}$ ۇ½ Size: 120(W) x 35(D) x 135(H)mm

POWER SUPPLY

� 230 VAC and 110 VAC versions available

FREQUENCY/COVERAGE

- آذِيً Frequency bands coverage: EU/AU/NZ, US/CA, LATAM, TW
- � Up to 50m indoor and 300m outdoor
- ï¿1/2 Receiver sensitivity: -92dBm
- า๊¿1/2 2 internal omni-directional antennas

STANDARDS/APPROVALS

រ៉េ្ស The DECT repeater is designed in accordance with the Digital Enhanced Cordless Telecommunications (DECT) standard



RTX 4022 DECT Repeater

 $\ddot{i}_{\dot{c}}$ The DECT repeater is compliant with: - TBR6, TBR22 (Generic Access Profile, GAP) - ETS 300 700 - ETSI Wireless Relay Station Specification

LED INDICATOR

ï¿⅓ Radio link quality indication

Price: £84.75