

2N IP Verso Base Unit - Black (9155101B)



Product Name: 2N IP Verso Base Unit - Black (9155101B)

Manufacturer: 2N Telecommunications

Model Number: 9155101B

Please Note: All 2N products come with a 3 year warranty as standard however, this can be extended up to 5 years. Customers have the option to extend their warranty by either one or two years. To find out more, please [click here](#) or call our sales team on 0330 088 0195.

Please Note: This product is just the base unit. You will need to purchase modules separately to make the intercom function. Find out more below. The 2N Helios intercoms may require additional licenses to activate all features.

2N IP Verso Base Unit - Black (9155101B)

The 2N IP Verso is a modular security intercom that can be used everywhere a specific function and purpose of use is needed. The 2N Verso 9155101B comes without a camera and can be easily integrated into an existing monitoring system, and thanks to programmable scripts, the whole system can be used as a security component to protect a building.

2N Verso 9155101B Key Features

• IP (Internet Protocol) connected Door Entry System

• 2N Verso Modular Intercom Device allows flexibility of specification

• SIP communication protocol

• Programmable scripts for actions and reactions

• Integrates within a LAN, WAN, Web Ethernet network system

• Integration with third-party CCTV systems with ONVIF support

• Power over Ethernet (PoE) (or 12v power supply)

• Next Generation html5 web server configuration

• iPad, iPhone, Smart Phone, Tablet audio & video support

• Web Interface Administration / Control of all 2N Helios IP devices from one location

• Stylish, discreet design; robust materials and construction

• IP54 protection rating

Once you have selected your 2N base unit, you can then start to build your customized 2N solution. There are a range of Surface Frames, Back Boxes, and Extending Modules available for Verso.

This Verso 9155101 Unit must be ordered with either a Two Frame Position or Three Frame Position mounting frame; the second (and third) mounting position is available for installation of additional function modules).

The modularity of the 2N Verso enables for a great number of combinations that can be tailored exactly to the requirements of the deployment.

See the full list of modules available below.

Main Basic Units - (*required) 9155101 Basic Unit 9155101C Basic Unit with camera

Mounting Frames - (*required) 9155011 1 Module Flush-mounting Frame 9155012 2 Module

Flush-mounting Frame 9155013 3 Module Flush-mounting Frame 9155021 1 Module

Surface-mounting Frame 9155022 2 Module Surface-mounting Frame 9155023 3 Module

Surface-mounting Frame

2N IP Verso Base Unit - Black (9155101B)

Extending Function Modules - (*option) 9155030 InfoPanel Module 9155031 Keypad Module
9155032 RFID Card Reader 125 KHz Module 9155033 RFID Card Reader 13 MHz Module
9155034 Input / Output Module 9155035 5 Quick-Call Button Module 9155039 Blank Module
Flush Mounting Back Boxes - (*option) 9155014 1 Module Flush Mount Back Box 9155015 2
Module Flush Mount Back Box 9155016 3 Module Flush Mount Back Box
Accessories - (*option) 9159010 Security Relay
2N Helios IP Verso Base Unit - Black (9155101B) - Technical Specifications
Signalling Protocol

• SIP 2.0 (RFC - 3261)

Buttons

• Quick dial buttons Transparent, white backlit buttons with easily replaceable name tags
• Number of buttons 1 to 146
• Numeric keypad optional

Audio

• Microphone 1 integrated microphones
• Loudspeaker 2W

Audio Stream

• Codecs G.711, G.729

RFID card reader

• Supported cards Mifare Classic 1k & 4k, DESFire EV1, Mini, Plus S&X, SmartMX, Ultralight, Ultralight C, SLE44R35, my-d move (SLE66Rxx), PayPass, Legic Advant Calypso, CEPAS, Moneo, PicoPass, HID iCLASS

Interface

• Power supply 12V±15%/2A DC or PoE PoE 802.3af (Class 0 - 12.95W) LAN 10/100BASE-TX with Auto-MDIX, RJ-45 Relay outputs NC/NO contacts, max 30V/1A AC/DC Active relay output 10V/400mA DC

Mechanical

• Operating temperature range -40°C – 60°C
• Storage temperature range -40°C – 70°C
• Relative humidity 10% - 95% (not condensing)
• Protection level IP 54

Dimensions

• Wall-mounted 1 modul 107x130x28 mm
• Wall-mounted 2 modul 107x234x28 mm
• Wall-mounted 3 modul 107x361x28 mm
• In-wall 1 modul 130x153x5 mm
• In-wall 1 modul 130x257x5 mm
• In-wall 1 modul 130x361x5 mm

2N IP Verso Base Unit - Black (9155101B)

Price: £483.90
