

AVer CAM340 4K Camera with 3x lossless digital Zoom; 4K@25fps; 1080@60fps



Product Name: AVer CAM340 4K Camera with 3x lossless digital Zoom; 4K@25fps; 1080@60fps

Manufacturer: -

Model Number: 61U8C00000AB

Please Note: This product is no longer available. To find an alternative, please see our IP Video Conferencing solutions.

AVer CAM340 4K Camera with 3x lossless digital Zoom; 4K@25fps; 1080@60fps Meet the AVer CAM340 - the next generation of intelligent camera that gives you the freedom to express yourself and collaborate anywhere. Unbox, unfold, and connect to your computer and instantly start a next generation video communication experience for huddle and small conference rooms. The CAM340 is compatible with all of your favorite applications; connecting to virtually any desktop or laptop, via a single USB cable.

AVer CAM340 Key Features

า๊¿½ Sensor: 1/2.5" Sony Exmor R™ 4K CMOS sensor

� Frame rate: 4K 25fps; 1080p, 720p, 960x540, 848x480, 640x480, 640x360, 424x240,

320x240, 320x180 at 60, 30, 15 fps � Lens iris, focus, zoom: fixed

� AE, white balance: auto, manual override by PTZApp

ï¿1/2 Lens focal length: 3.37 mm +/- 5%

ï¿⅓ Lens F#: 2.8

آذِيًّ Field of view: diagonal 94°, horizontal 85°, vertical 55°

ï¿⅓ S/N ratio: > 50dB

آذِيً Minimal illumination: 1.4 lx (50 IRE, F2.8, shutter 1/30)

� 2D noise reduction ï¿⅓ Back light compensation

� Minimum working distance: 80cm

AVer CAM340 - Technical Specifications Package contents

� USB3.0 4K camera

� Power adapter (for USB 2.0 usage)

 $\ddot{\imath}$ USB3.0 type-C to type-A (6ft) cable

� USB3.0 type-A to type-C adapter

ï¿⅓ Quick guide

Microphone

� 1 uni-directional microphones

� Frequency response: 100~12K Hz

ï¿1/2 Sensitivity: -37dB

USB

� 2.0, 3.0, type-C

� UVC (USB Video Class) 1.1

� UAC (USB Audio Class) 1.0

Other features



AVer CAM340 4K Camera with 3x lossless digital Zoom; 4K@25fps; 1080@60fps

- � Privacy shutter door
- آزا Infra-red receiver supports optional CAM520/VC520 remote control

PTZApp

- � Free download for Windows®
- ï¿⅓ Firmware field upgrade
- � Advance device setting and diagnostic

Dimension & amp; package

- � Package dimensions: 138 x 138 x 149mm
- � Package weight: 0.622kg
- � Camera (folded): 60 x 60 x 75mm
- � Camera weight: 0.251kg

Warranty*

� Camera: 3+2 year � Accessories: 1-year

Camera

- آذِل Sensor: 1/2.5" Sony Exmor R™ 4K CMOS sensor
- � Frame rate: 4K 25fps; 1080p, 720p, 960x540, 848x480, 640x480, 640x360, 424x240,
- 320x240, 320x180 at 60, 30, 15 fps � Lens iris, focus, zoom: fixed
- آذِ AE, white balance: auto, manual override by PTZApp
- � Lens focal length: 3.37 mm +/- 5%
- � Lens F#: 2.8
- � Field of view: diagonal 94°, horizontal 85°, vertical 55°
- ï¿⅓ S/N ratio: > 50dB
- آزا Minimal illumination: 1.4 lx (50 IRE, F2.8, shutter 1/30)
- � 2D noise reduction
- � Back light compensation
- ï¿⅓ Minimum working distance: 80cm

Connectors

- ï¿1/2 USB type-C connector
- � DC jack for power adapter (for USB2.0 connection)
- ï¿1/2 3.5mm audio jack for line output
- ï¿1/2 Reset button

Control

- ï¿⅓ UVC
- آزٰ½ PTZApp
- าั¿½ Optional IR remote control (compatible with CAM520/VC520 remote control)

System requirement



AVer CAM340 4K Camera with 3x lossless digital Zoom; 4K@25fps; 1080@60fps

� Windows 7/8/8.1/10 � Google Chromebook version 29.0.1547.70 Platform 4319.79.0

Power adaptor

� AC 100V ~240V, 50/60Hz � Consumption: EIAJ 5V, 2A

Optional accessories

� Wall mount � Remote control

Zoom, pan and tilt movement

īస్ట్ Zoom: up to 4X leveraging 4K sensor (not available in 4K or 60 fps)

าั¿1/2 Pan and tilt: when zoom in leveraging 4K sensor

Video format

� YUV and MJPEG

Security and mount

ï¿1/2 Built-in TV mount (above TV, up to 46mm deep)

ï¿⅓ Kensington slot

ï¿1/2 1/4" tripod mounting screw

Hardware spec

ï¿1/2 2.4GHz Intel Core 2 Duo processor

� 2GB RAM or more

ï¿⅓ Hard drive space for recorded videos

� 4K or 1080p 60fps require higher system configuration

រ៉េះ/ 1 USB 2.0 port and above (USB 3.0 required for 4K or 60fps)

Environmental data

� Operation temperature: 0 ~40°C

� Operation humidity: 20% ~80%

� Storage temperature: -20 ~60°C

ï¿⅓ Storage humidity: 20% ~80%

Compatible applications

T¿½ Skype™, Skype for Business, Zoom, BlueJeans, FaceTime®, Cisco Webex®, Google Hangouts™, GoToMeeting®, V-CUBE, Adobe® Connect™, Vidyo®, Fuze, WebRTC, Cisco Jabber®, Youtube™

Please Enquire