

Digium Wildcard TE121B PCI Express ISDN PRI Card with Echo Cancellation (1TE121BF)



Product Name: Digium Wildcard TE121B PCI Express ISDN PRI Card with Echo Cancellation (1TE121BF)

Manufacturer: -

Model Number: 1TE121BF

Please Note: The Digium TE121B has been discontinued. For an alternative, we highly recommend the Digium TE133.

Please Note: This is a PCI Express Card. Please make sure your motherboard/server is compatible with this product.

View PCI vs PCI-Express example

Digium Wildcard TE121B PCI Express ISDN PRI Card with Echo Cancellation
The Digium TE121B is a high-performance, cost effective digital telephony interface card with the power to create a seamless network, interconnecting traditional telephony systems with emerging Voice over IP technologies.

Used in conjunction with Asterisk, the Digium TE121B can be used to deliver a wide range of PBX and IVR services to the network or handset including Voicemail, Call Conferencing, Three-way Calling, and VoIP Gateways. The Digium TE121B is a single span, selectable T1 (24-channel), E1 (32-channel), or J1 (24-channel) card utilizing Digium's VoiceBus technology. VoiceBus technology allows the Digium TE121B to use an industry standard bus-mastering PCIe 1.0+ interface, as found in millions of PCs worldwide, to maximize system compatibility and eliminate system conflicts.

The Digium TE121B supports both voice and data modes on its single—span, for example, the card can support 12 channels dedicated to voice, routed directly to the Asterisk Open Source PBX, and 12 to data, handled by the underlying Linux operating system, thus eliminating the need for an external router. The Digium TE121B works in a X1 PCle 1.0+—slot with the bus-mastering Digium TE121B improving I/O speed over—slave-only architectures, resulting in reduced CPU usage and increased card density per server. The cards provide the power to interconnect traditional telephony systems with emerging Voice-over IP (VoIP) technologies. Target Applications

- ï¿1/2 Legacy PBX/IVR Services
- ï¿⅓ Voice-over Internet Protocol (VoIP) services
- � Complex IVR Trees
- � "Meet-Me" Bridge Conferencing
- � VoIP Gateways (supports SIP, H.323 and IAX)
- � Calling Card Platforms
- � Voice/Data Router (replace expensive routers)
- า๊ะ่ 1/2 PRI Switch Compatibility Network or CPE

By utilizing Digium's TDMoE (TDM over Ethernet) technology, an exclusive Digium process, you can easily connect multiple PCs equipped with the Digium TE121B and achieve voice quality on par with single PBX implementations. Scalability for this product is derived from adding multiple Digium TE121B cards to each individual PC adding additional cards as you need them for your expanding applications. The Digium TE121B supports industry standard telephony and data protocols, including both RBS and Primary Rate ISDN (PRI) protocol families for voice and PPP, Cisco HDLC, and Frame Relay data modes. The board drives both line-side and trunk-side interfaces, including call features. The Digium TE121B supports industry standard telephony and data protocols, including Primary Rate ISDN (both N. American and Euro Standard) protocol



Digium Wildcard TE121B PCI Express ISDN PRI Card with Echo Cancellation (1TE121BF)

families for voice, PPP, Cisco HDLC, and Frame Relay data modes. Both line-side and trunk-side interfaces are supported, as well as advanced call features.

Improving upon the prior TE120P which does not offer expansion capabilities, the Digium TE121B is combined with Digium's VPMADT032 echo cancellation module to deliver 128ms of echo cancellation across 30 channels in E1 mode or 24 channels in T1 mode.

The Digium TE121B has been designed to be fully compatible with existing software applications. They are fully integrated with Digium's Asterisk software. The open source drivers for these cards support an API for custom application development. With the combination of Digium hardware and Asterisk software, numerous telephony configurations are possible. From

the traditional PBX to VoIP Gateways, Digium solutions are paving the way for a new generation

Digium TE121B Technical Specifications Hardware

� Ports: 1 x E1/T1/J1 PRI � Bus Type: PCIe 1.0+

of worldwide communications.

آزار Connector: X1

� Processor: 32-bit 33MHz

าั¿½ Echo Cancellation: VPMADT032 module included

Minimum Hardware Requirement

� 800-Mhz Pentium III

ï¿⅓ 64MB RAM

� Available PCle 1.0+ Slot

Framing Types

ï¿⅓ Superframe (D4)

i¿½ Channel Associated Signaling (CAS)

� Common Channel Signaling (CCS)

Coding Types

� Alternative Mark Inversion (AMI)

تزير Bipolar with 8 Zeros Substitution (B8ZS)

i¿½ High Density Bipolar of Order 3 Code (HDB3)

12/2 Optional Cyclic Redundancy Check 4 (CRC4)

Primary Rate Interface (PRI) Switch Types

ï¿1/2 National ISDN 1 (NI1)

ï¿1/2 National ISDN 2 (NI2)

� Nortel DMS100

AT&T 4ESS

� Lucent 5ESS

� EuroISDN Q.931

ï¿1/2 Q.SIG (Limited Support)

Signaling Types

� E&M, E&M E1, E&M Wink

� Feature Group D (DTMF)



Digium Wildcard TE121B PCI Express ISDN PRI Card with Echo Cancellation (1TE121BF)

- � Feature Group D (MF)
- � Feature Group D (Tandem Access)
- ï¿⅓ Feature Group B
- ï¿1/2 Feature Group C-CAMA
- � Feature Group C-CAMA (MF)
- ī 1 2/2 Foreign Exchange Station (FXS) Loop Start, Ground Start, Kewl Start
- īస్ట్ Foreign Exchange Office (FXO) Loop Start, Ground Start, Kewl Start
- � PRI Network and CPE

Physical

� Dimensions: 12.2x5.5x1.6 cm

� Full-Height: No � Half-length: Yes

ï¿1/2 Temperature: 0 to 50° C

Regulatory

- � RoHS compliant
- ī¿1/2 Manufactured in an ISO 9001:2001 certified facility in the United States
- � Maintain an MTBF greater than 1 million hours

Please Enquire