

## Yeastar S20 VoIP PBX



Product Name: Yeastar S20 VoIP PBX

Manufacturer: -

Model Number: S20

Please Note: This product has been discontinued. Please see the Yeastar S50 VoIP PBX.

Please Note: This product only comes with EU power supplies.

### Yeastar S20 VoIP PBX - 20 Users

The Yeastar S20 VoIP PBX is designed with the small and medium sized enterprises in mind, supporting up to 20 users and built using the very latest technology, the Yeastar S-Series delivers exceptional cost savings, productivity and efficiency improvements, delivering power, performance, quality and peace of mind.

### Yeastar S-Series Key Features

ï¿½ Users 20

ï¿½ Max Concurrent Calls 10

ï¿½ Max Analog Ports 4

ï¿½ Max BRI Ports 4

ï¿½ Max Cellular Ports 1

ï¿½ Linkus Unified Communications App for Desktop and Mobile

ï¿½ Works with SIP/IAX2, PSTN lines, ISDN BRI, E1/T1/PRI, and GSM/3G/4G

ï¿½ Built-in call recording capability

ï¿½ Control and manage customer premises PBX easily and quickly with Remote Management

ï¿½ Convenient integration with call center, PMS, and CRM

**Appreciate the Easy-to-use Solution** The S-Series features fast installation with comprehensive auto provisioning, advanced plug and play capability, together with an intuitive Metro UI driven by point-and-click configuration, from any location.

**Your Choice of Technologies and Features** With a unique modular design, the S-Series will install into the most demanding of environments. You can also take advantage of advanced enterprise grade features with the fullest and most complete software versions.

**Telephone System without Risk** S-Series is built with the future in mind, utilizing the latest technology advances, from Freescale industrial grade Quad Core processors, TI DSP voice processors, and long-life power units and lightning protection.

**Play Safe and Expect Reliability** With advanced failover, security, monitoring and reporting capabilities as standard, combined with an internal firewall and with support for TLS and SRTP encryption, there has never been such a robust system.

### Yeastar S-Series - Technical Specifications

#### General

ï¿½ Users 20

ï¿½ Max Concurrent Calls 10

ï¿½ Max Analog Ports 4

ï¿½ Max BRI Ports 4

ï¿½ Max Cellular Ports 1

ï¿½ VoIP Trunks 20

ï¿½ Protocol SIP (RFC3261), IAX2

ï¿½ Transport Protocol UDP, TCP, TLS, SRTP

ï¿½ Codec G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC, H263, H263P, H264, MPEG4

ï¿½ DTMF In-band, RFC4733, RFC2833, SIP INFO

## Yeastar S20 VoIP PBX

• LAN 1 × 10/100 Mbps  
• WAN 1 × 10/100 Mbps  
• IP Services Static IP, DHCP, VPN, Firewall, VLAN, DDNS, PPPoE, QoS, Static NAT, STUN  
• Voicemail 5000 min (expandable)  
• Firewall Yes  
• T.38 Fax Yes  
• App Center Yes  
• External Storage TF Card  
• Power DC 12V 1A  
• Size (L x W x H) (cm) 16 x 16 x 3  
• Weight 0.3 kg  
• Power Consumption 1.8-10.6 W  
• Environment, Operation Range: 0°C to 40°C, 32°F to 104°F; Storage Range: -20°C to 65°C, -4°F to 149°F; Humidity: 10-90% non-condensing  
• Mounting Desktop & Wall-mount 1U Rack-mount

**Please Enquire**

---