

Grandstream GDS RFID Card Reader for GDS3710 (GDS-RD)



Product Name: Grandstream GDS RFID Card Reader for GDS3710 (GDS-RD)

Manufacturer: Grandstream

Model Number: RFID-CR

Grandstream GDS RFID Card Reader for GDS3710 (GDS-RD)

The Grandstream GDS-RD is available for use with the GDS3710 IP Video Door Station. The GDS-RD can be installed anywhere and connect via USB to any computer running Grandstream's free GDS Manager software. This allows all RFID Card Reader activity to be tracked, monitored, and managed centrally by GDS Manager. The device is fully powered through USB and offers a built-in antenna with card-seeking mode.

Grandstream GDS-RD - Technical Specifications

General

Card Supported: Generic RFID card

Working Frequency: 125 KHz

Power Supply: DC 5V (±4%)

Electric Current: Standby Current 20mA; Operation Current Less Than 35 mA

Operating Distance: 0-40 mm effective distance, the use of ID card and the Reader

Working Temperature: -10°C ~ 70°C

Storage Temperature: -20°C ~ 80°C

Dimensions: 108.5mm x 108.5mm x 24mm ± 3mm

USB Cable Length: 1.5 Meters

Price: £31.90

Options available for Grandstream GDS RFID Card Reader for GDS3710 (GDS-RD) :

Require RFID Fobs?

Not Required, 10 x RFID Fobs (+£77.40).

Require RFID Cards?

Not Required, 10 x RFID Cards (+£77.45).