Yealink W60 DECT IP Phone Package



Product Name: Yealink W60 DECT IP Phone Package
Manufacturer: -
Model Number: W60P

Please Note: This product is end of life. For an alternative, see the Yealink W76P.

Yealink W60 DECT IP Phone Package
The Yealink W60, being a high-performance SIP cordless phone system, is the ideal solution for small and medium-sized businesses. Paring with up to a total of 8 Yealink W52H/W56H DECT handsets, it allows you enjoy superb mobility and flexibility.
Yealink W60 Key Features

ï¿½ High-performance SIP cordless phone system
ï¿½ Up to 8 concurrent calls
ï¿½ Up to 8 DECT cordless handsets
ï¿½ Up to 8 VoIP accounts
ï¿½ Up to 30-hour talk time and 400-hour standby time
ï¿½ Noise Reduction System

By supporting Opus codec, W60 Package consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions. Offering the convenience of cordless with a simple add-on device without losing the SIP features, it brings a seamless call management for users while “on-the-go”.
The Yealink DECT IP phone W60 Package supports efficient provisioning and effortless mass deployment with Yealink’s Redirection and Provisioning Service (RPS) and Boot mechanism, saving time and additional costs.
Yealink W60 - Technical Specifications
Phone Features

ï¿½ Up to 8 simultaneous calls
ï¿½ Up to 8 handsets
ï¿½ Up to 8 VoIP accounts
ï¿½ Up to 2 simultaneous calls per handset
ï¿½ Up to 5 repeaters per base station
ï¿½ Handset selection for receiving call
ï¿½ Handset and number selection for placing call
ï¿½ Paging, intercom, auto answer, dial plan
ï¿½ Call hold, call transfer, 3-way conference
ï¿½ Switching between calls
ï¿½ Call waiting, mute, silence, DND
ï¿½ Caller ID with name and number
ï¿½ Anonymous call, Anonymous call rejection
ï¿½ Call forward (always/busy/no answer)
ï¿½ Speed dial, voicemail, redial
ï¿½ Message Waiting Indication (MWI)
ï¿½ Local phonebook for up to 500 entries (store in the base)
ï¿½ Remote phonebook/LDAP
ï¿½ Phonebook search/import/export
ï¿½ Call history (all/missed/placed/received)
ï¿½ Direct IP call without SIP proxy
ï¿½ Reset to factory, reboot
ï¿½ Keypad lock, emergency call, music on hold
ï¿½ Broadsoft directory, BroadSoft call log

Yealink W60 DECT IP Phone Package

ï¿½ Broadworks feature key synchronisation
ï¿½ Shared Call Appearance (SCA)

Personalisation

ï¿½ 9 ringer melodies
ï¿½ Screen saver
ï¿½ Multilingual user interface

Management

ï¿½ Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
ï¿½ Auto-provision with PnP
ï¿½ Handset upgrade: OTA (Over-The-Air)/USB port
ï¿½ Configuration: browser/phone/auto-provision
ï¿½ Trace package and system log export

Audio Features

ï¿½ Full-duplex speakerphone
ï¿½ Hearing Aid Compatibility (HAC) compliant
ï¿½ Receiver volume control: 5 steps
ï¿½ Ringer volume control: 5 steps+off
ï¿½ Multiple advisory tones
ï¿½ Acoustic warning for low battery status
ï¿½ DTMF
ï¿½ Wideband codec: Opus, AMR-WB (optional), G.722
ï¿½ Narrowband codec: PCMU, PCMA, G.726, G.729, iLBC
ï¿½ VAD, CNG, AEC, AGC, PLC, AJB
ï¿½ Support VQ-RTCPXR (RFC6035)

Network Features

ï¿½ SIP v1 (RFC2543), v2 (RFC3261)
ï¿½ SNTP/NTP
ï¿½ VLAN (802.1Q and 802.1P)
ï¿½ 802.1x, LLDP, PPPoE
ï¿½ STUN Client (NAT Traversal)
ï¿½ UDP/TCP/TLS
ï¿½ IP assignment: static/DHCP
ï¿½ Support outbound proxy server backup

Security

ï¿½ Open VPN
ï¿½ Transport Layer Security (TLS)
ï¿½ HTTPS (server/client), SRTP (RFC3711)
ï¿½ Digest authentication using MD5
ï¿½ Secure configuration file via AES encryption
ï¿½ Support SHA256/SHA512/SHA384
ï¿½ Three-level configuration mode: Admin/Var/User

DECT

ï¿½ Frequency bands: 1880 – 1900 MHz (Europe), 1920 – 1930 MHz (US)

Yealink W60 DECT IP Phone Package

ï¿½ DECT Standards: CAT-iq2.0

Interface

ï¿½ 1 x RJ45 10/100M Ethernet port
ï¿½ Power over Ethernet (IEEE 802.3af), Class 1
ï¿½ Headset jack (3.5 mm)

Physical Features

ï¿½ Indoor Range: 20m~50m (The ideal distance is 50m)
ï¿½ Outdoor Range: 300m (in ideal conditions)
ï¿½ Standby Time: 400 hours (in ideal conditions)
ï¿½ Talk Time: 30 hours
ï¿½ 2.4’’ 240x320 pixels color display
ï¿½ Desktop or wall mountable
ï¿½ LCD backlit, key backlit
ï¿½ Energy-saving ECO mode/ECO Mode+
ï¿½ 12 key numerical keypad, 5 navigation keys, 2 softkeys, 6 function keys, 6 shortcut keys
ï¿½ Three LED indicators on W60B:1 x Registration LED1 x Network Status LED1 x Power Indicator LED
ï¿½ External Yealink AC adapter AC 100-240V Input and DC 5V/600mA Output
ï¿½ Phone size: 175mm x 53mm x 20.3mm
ï¿½ Base station size: 130mm x 100mm x 25.1mm
ï¿½ Operating humidity: 10~95%
ï¿½ Operating temperature: 10~+50°C (+14~122°F)

Package Features

ï¿½ Package content:-W56H Handset-W60B Base Station-Base Stand-USB Charger Cradle-Two Power Adapters-Ethernet Cable-Belt Clip-Rechargeable Battery-Quick Start Guide
ï¿½ Qty/CNT: 10 PCS
ï¿½ Giftbox size: 205mm*196mm*95mm
ï¿½ Carton meas: 495mm*406mm*223mm
ï¿½ N.W: 7.5 kg
ï¿½ G.W: 8.3 kg

Price: £83.10

Options available for Yealink W60 DECT IP Phone Package :

Need Product Setup / Training / Support?

Required - 30 minutes (+£40.00), Required - 1 Hour (+£65.00), Not Required.

Additional Handset

Yealink W56H Additional DECT Handset (+£56.00), Not Required.