

# Yealink W60B DECT IP Base Station



Product Name: Yealink W60B DECT IP Base Station

Manufacturer: -

Model Number: W60B

Please Note: This product has been discontinued. Please see the other Yealink Dect IP Phones for an available alternative.

## Yealink W60B DECT IP Base Station

The Yealink W60B is the DECT IP base station for small and medium-sized businesses. Paring with up to a total of 8 Yealink W56H DECT handsets, the W60B allows you enjoy mobility and flexibility. A powerful chip ensures a better and higher performance, allowing this DECT IP base station to support up to 8 VoIP accounts and 8 concurrent calls.

Yealink W60B Key Features

� Up to 8 concurrent calls

� Up to 8 DECT cordless handsets

� Up to 8 VoIP accounts

� Support Opus audio codec

� TLS and SRTP security encryption

� Noise Reduction System

Designed with a modern and elegant style, this compact DECT IP base station possesses a wire-hidden design, with the option to be wall-mounted. By supporting Opus codec, Yealink W60B consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions.

Yealink W60B - Technical Specifications

Phone Features

� Up to 8 concurrent calls

آزٰ Up to 8 handsets

� Up to 8 VoIP accounts

� Up to 5 repeaters per base station

ï¿⅓ Paging, intercom, auto answer

ï¿1/2 Call hold, call transfer, call waiting

ï¿1/2 Three-way conference

ï¿1/2 Switching between calls

ï¿1/2 Mute, silence, DND

� Caller ID with name and number

� Redial

� Anonymous call

� Anonymous call rejection

ï¿1/2 Call forward (always/busy/no answer)

ï¿⅓ Speed dial

تز½ Voicemail

� Message Waiting Indication (MWI)

آذًا Local phonebook for up to 500 entries (store in the base)

� Remote phonebook/LDAP

� Phonebook search/import/export

تز1/2 Call history (all/missed/placed/received)

� Direct IP call without SIP proxy

� Reset to factory, reboot

� Emergency call

ï¿⅓ Dial plan



# Yealink W60B DECT IP Base Station

- ï¿1/2 Music on hold
- ï¿1/2 Broadsoft directory
- ï¿1/2 BroadSoft call log
- ï¿1/2 Broadworks feature key synchronisation
- ï¿1/2 Shared Call Appearance (SCA)

#### Management

- า๊¿½ Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
- � Auto-provision with PnP
- า๊¿½ Handset upgrade: OTA (Over-The-Air)/USB port
- آزا Configuration: browser/phone/auto-provision
- � Trace package and system log export

#### **Audio Features**

- آذِ1/2 Wideband codec: Opus, AMR-WB (optional), G.722
- آذِ1/2 Narrowband codec: PCMU, PCMA, G.726, G.729, iLBC
- � VAD, CNG, AEC, AGC, PLC, AJB
- � Support VQ-RTCPXR (RFC6035)

#### **Network Features**

- ï¿1/2 SIP v1 (RFC2543), v2 (RFC3261)
- ï¿⅓ SNTP/NTP
- ï¿1/2 VLAN (802.1Q and 802.1P)
- � 802.1x, LLDP, PPPoE
- تزارط STUN Client (NAT Traversal)
- ï¿⅓ UDP/TCP/TLS
- ï¿⅓ IP assignment: static/DHCP
- � Support outbound proxy server backup

### Security

- ï¿⅓ Open VPN
- � Transport Layer Security (TLS)
- ï¿1/2 HTTPS (server/client)
- ï¿⅓ SRTP (RFC3711)
- � Digest authentication using MD5
- � Secure configuration file via AES encryption
- ï¿1/2 Support SHA256/SHA512/SHA384
- تزارد Three-level configuration mode: Admin/Var/User

#### DECT

- � Frequency bands: 1880 1900 MHz (Europe), 1920 1930 MHz (US)
- � DECT Standards: CAT-iq2.0

### Interface

- ï¿1/2 1 x RJ45 10/100M Ethernet port
- � Power over Ethernet (IEEE 802.3af), Class 1

#### **Physical Features**



## Yealink W60B DECT IP Base Station

- า๊ะ่ 1/2 Indoor Range: 20m~50m (The ideal distance is 50m)
- آذِرُ Outdoor Range: 300m (in ideal conditions)
- � Desktop or wall mountable
- � Energy-saving ECO mode/ECO Mode+
- าั¿½ Three LED indicators on W60B:1 x Registration LED1 x Network Status LED1 x Power Indicator LED
- าั¿½ External Yealink AC adapter:AC 100-240V Input and DC 5V/600mA Output
- � Dimension (W\*D\*H): 130mm x 100mm x 25.1mm
- � Operating humidity: 10~95%
- تزاره Operating temperature: -10~+50°C (+14~122°F)

#### Package Features

าั¿½ Package content:-W60B Base Station-Base Stand-Power Adapter-Ethernet Cable-Quick Start Guide

� Qty/CNT: 10 PCS

ï¿1/2 Giftbox size: 205mm\*196mm\*95mm

� Carton measures: 512mm\*414mm\*213mm

� N.W: 3.6 kg � G.W: 4.3 kg

## **Please Enquire**

Options available for Yealink W60B DECT IP Base Station:

## **DECT Repeater Required**

Not Required, Yealink DECT Repeater RT30 (RT30-repeater) (+£80.45).

## **Need Product Setup / Training / Support?**

Required - 30 minutes (+£40.00), Not Required, Required - 1 Hour (+£65.00).

## **Handset Required?**

Yealink W56H (+£67.00), Not Required, Yealink W59R (+£88.00), Yealink W53H (+£47.30), Yealink CP930W (+£284.80).