

## Grandstream HA100 High Availability Controller for UCM6510

Product Name: Grandstream HA100 High Availability Controller for UCM6510

cococommuna 2007 —

Manufacturer: Grandstream Model Number: HA100

Grandstream HA100 High Availability Controller for UCM6510

The Grandstream HA100 offers an automated failover solution for the UCM6510 IP PBX. When connecting between two UCM6510, the HA100 constantly monitors the operation status of both UCM6510 and automatically switches the system control to the hot-standby secondary UCM6510 in the event that the primary UCM6510 fails.

Grandstream HA100 Key Features

ī¿½ Connects and constantly monitors two UCM6510's together for high availability

 $\ddot{\imath}_{\dot{\imath}}$  Smart failover solution that automatically switches to a hot-standby secondary UCM6510 if the primary one fails

าั¿½ Up to 14 LED indicators showing real-time status of all of the telecom lines, network links, and more

រី¿½ Gratuitous ARP forces SIP endpoints to refresh the MAC address of the new UCM6510 without interruptions

า๊¿½ Fast 10 to 50 second system switching time depending on the number of registered endpoints

Thanks to its smart monitoring and automated failover capability, the HA100 is an ideal high-availability solution for the UCM6510 to ensure maximum total system reliability and uptime. Grandstream HA100 - Technical Specifications

**INTERFACES: BACK PANEL** 

ï¿1/2 Analog Telephone FXS Ports: 2 ports

� PSTN Line FXO Ports: 2 ports

� T1/E1 Interface: 1 port

� Network Interfaces: 1 LAN/ 1WAN

រី¿½ RS-485 2; 1 for Primary UCM6510; 1 for Secondary UCM6510

ï¿⅓ Reset Switch: Yes

า๊¿½ Universal Power Supply: DC Power Port

INTERFACES: FRONT PANEL

آذِارِ Analog Telephone FXS Ports: 2; 1 FXS A, 1 FXS B

าั¿½ PSTN Line FXO Ports: 2; 1 FXO A, 1 FXO B าั¿½ T1/E1 Interface: 2 ports; T1/E1 A, T1/E1 B

� LED Indicators Power, T1/E1, FXS, FXO, LAN, WAN

## **Please Enquire**