

Ubiquiti UniFi Video Camera G3 Dome 5 Pack -UVC-G3-DOME-5



Product Name: Ubiquiti UniFi Video Camera G3 Dome 5 Pack - UVC-G3-DOME-5 Manufacturer: -

Model Number: UVC-G3-DOME-5

Please Note: This product is no longer available. Please see the Ubiquiti UniFi Video section for alternative products.

Ubiquiti UniFi Video Camera G3 Dome 5 Pack - UVC-G3-DOME-5 The Ubiquiti UniFi Video Camera G3 Dome 5 Pack - UVC-G3-DOME-5 features a wide-angle lens and 1080p video performance for expanded surveillance coverage. The new surface-mount design provides options for wall or ceiling installations. The infrared LEDs and anautomatic IR cut filter provide day and night monitoring. Ubiquiti UniFi Video Camera G3 Dome -UUVC-G3-DOME-5 Features

� 1080p Full HD, 30 FPS � EFL 2.8 mm, ƒ/2.0 � Wide-Angle Lens � 802.3af PoE or 24V Passive PoE � Built-in Microphone � Wall or Ceiling Mount

The UniFi Video mobile app is now available in the App Store for iOS and Google Play Store for Android.

Ubiquiti UniFi UVC-G3-DOME-5 - Technical Specifications

UVC-G3-DOME-5 Specifications

� 5 x UVC-G3-DOME

- ï¿1/2 Dimensions Ø 132 x 60 mm (Ø 5.20 x 2.36")
- ï¿1/2 Weight 260 g (9.17 oz) x 5
- ï¿¹/₂ Networking Interface (1) 10/100 Ethernet Port
- ï¿1/2 Sensor 1/3" 4-Megapixel HDR Sensor
- ï¿1/2 Lens EFL 2.8 mm, ƒ/2.0
- تزك¹/₂ Night Mode IR LEDs with Mechanical IR Cut Filter
- ï¿1/2 Microphone Yes
- i¿1/2 Button Factory Reset Button
- ï¿1/2 Power Method 802.3af PoE or 24V Passive PoE
- ïزئ Power Supply 802.3af PoE Switch or24V, 0.5A PoE Adapter (Included with Single-Pack)
- ï¿1/2 Maximum Power Consumption 4W
- ï¿1∕2 Mounting Wall/Ceiling

ï¿¹/₂ Operating Temperature -30 to 70° C (-22 to 158° F)Operating Humidity 20 - 90% Noncondensing

Video

ï¿1/2 Video Compression H.264



Ubiquiti UniFi Video Camera G3 Dome 5 Pack -UVC-G3-DOME-5

ï¿1/2 Resolution 1080p Full HD (1920x1080)

ï¿1/2 Maximum Frame Rate 30 FPS

ï¿1/2 Image Settings Brightness, Contrast, Sharpness, Saturation, Noise Reduction, 50/60 Hz

General

ï¿1/2 Processor Ambarella S2L66 (816 MHz ARM Cortex-A9)

ï¿1/2 Memory 512 MB DDR3L

ï¿1/2 Viewing Angle Before Lens Correction After Lens Correction 100.4° (H), 59.1° (V),

117.3° (D)87.8° (H), 55.4° (V), 96.4° (D)

ïزئ Supported UniFi Video Version UniFi Video 3.2 (or Newer)

� UniFi Video System Requirements 64-bit Microsoft Windows 10/8/7, Ubuntu 12.04 or 14.04, or Debian 7.0 System withan Intel or Compatible 1.86 GHz (or Above) Processor and a Minimum of 2 GB RAM.

Please Enquire