

Ubiquiti UniFi Video Camera G3 5 Pack - UVC-G3-AF-5



Product Name: Ubiquiti UniFi Video Camera G3 5 Pack - UVC-G3-AF-5

Manufacturer: -

Model Number: UVC-G3-AF-5

Please Note: This product has been discontinued. Please see the Ubiquiti UniFi Video Camera G3 BULLET - 3 PACK (UVC-G3-BULLET-3).

Please Note: This product is the latest UVC-G3-AF variant. If you also require a system to record, monitor, and manage the UniFi IP CCTV system, please follow a link to the UVC-NVR-2TB.

Please Note: PoE Injectors are not included with 5 packs.

Ubiquiti UniFi Video Camera G3 5 Pack - UVC-G3-AF-5

The Ubiquiti UniFi Video Camera G3 5 Pack - UVC-G3-AF-5 features clear 1080p video resolution. The new balljoint mount design offers flexible 3-axis adjustment and can be mounted indoors or outdoors. The camera has infrared LED with an automatic IR cut filter for day and night surveillance. Ubiquiti UniFi UVC-G3-AF-5 Key Features

- 1080p Full HD, 30 FPS
- EFL 3.6 mm, f/1.8
- Outdoor Weather Resistant
- 24V Passive PoE
- Built-in Microphone
- Wall, Ceiling, or Pole Mount

Powerful Software Management Use the UniFi Video mobile app for easy camera management and live streaming from an iOS or Android-based smartphone or tablet. The UniFi Video mobile app is now available in the App Store for iOS and Google Play Store for Android. **HD Image Quality** Featuring an EFL 3.6 mm f/1.8 lens for superior vision, the UniFi Video Camera G3 (UVC-G3-AF) provides 1080p HD resolution at 30 FPS. **Hybrid Cloud Technology** Hybrid Cloud Technology combines the best of local and cloud management: secure, local storage and convenient remote access with streaming privacy & no licensing or maintenance fees.

Ubiquiti UniFi Video Camera G3 (UVC-G3-AF-5) - Technical Specifications
General

- Dimensions 75 x 140 mm (2.95 x 5.51")
- Weight 300 g (10.58 oz)
- Enclosure Injection-Molded Polycarbonate and Die-Cast Aluminum
- Networking Interface (1) 10/100 Ethernet Port
- Sensor 1/3" 4-Megapixel HDR Sensor
- Lens EFL 3.6 mm, f/1.8
- Night Mode IR LEDs with Mechanical IR Cut Filter
- Microphone Yes
- Button Factory Reset Button
- Power Method 24V Passive PoE
- Power Supply 24V, 0.5A PoE Adapter (Included with Single-Pack)
- Maximum Power Consumption 4W
- Mounting Wall/Ceiling/Pole
- Operating Temperature -30 to 70°C (-22 to 158°F)
- Operating Humidity 20 - 90% Noncondensing

Ubiquiti UniFi Video Camera G3 5 Pack - UVC-G3-AF-5

Video

• Video Compression H.264

• Resolution 1080p Full HD (1920x1080)

• Maximum Frame Rate 30 FPS

• Image Settings Brightness, Contrast, Sharpness, Saturation, Noise Reduction, 50/60 Hz

General

• Processor Ambarella S2L66 (816 MHz ARM Cortex-A9)

• Memory 512 MB DDR3L

• Viewing Angle Before Lens Correction After Lens Correction 85°; (H), 44.8°; (V), 98.1°; (D) 72°; (H), 42.9°; (V), 80.4°; (D)

• Supported UniFi Video Version UniFi Video 3.2 (or Newer)

• UniFi Video System Requirements 64-bit Microsoft Windows 10/8/7, Ubuntu 12.04 or 14.04, or Debian 7.0 System with an Intel or Compatible 1.86 GHz (or Above) Processor and a Minimum of 2 GB RAM.

Please Enquire
