



Product Name: Polycom VVX 400 Skype For Business Edition Gigabit Media Phone (VVX400) Manufacturer: -

Model Number: 2200-46157-019

Please Note: This item has been discontinued. We recommend the VVX401 as an alternative.

Polycom VVX 400 Skype For Business Edition Gigabit Media Phone The Polycom VVX 400 Skype For Business Edition is a 12 line HD Voice business media phone with a 3.5" colour LCD display and dual 10/100 RJ45 ports. This version of the VVX 400 is compatible with the Skype for Business service. This entry level 'always on' phone enhances your communications options over just using a Skype for a Business client with a headset.

Polycom VVX 400 Skype For Business Edition Key Features

- ï¿1/2 Compatible with Skype for Business / Lync
- � Up to 12 SIP accounts
- ï¿1/2 2 Ethernet Ports 10/100
- ï¿1/2 Backlit 3.5" colour screen
- ï¿1/2 Intuitive colour user Interface
- ï¿1/2 RJ9 earpiece socket
- ï¿1/2 Power over Ethernet with optional external PSU
- ï¿1/2 Voicemail compatible
- ï¿1/2 Polycom HD sound
- ï¿1/2 Expandable using up to three expansion modules

The Polycom VVX 400 is an expandable multimedia IP business phone that offers crystal clear communications, and an intuitive colour user interface for minimal training, improved collaborative functionality with other business media and greater user productivity. Polycom VVX 400 Business Media Phone - 2200-46157-019 - Technical Specifications User interface features

� Backlit 3.5" colour LCD (320 x 240) resolution• Voicemail support2• WebKit-based Browser• Adjustable base height• Unicode UTF-8 character support. Multilingual user interface including Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, and Swedish

Audio Features

ï¿1/2 Polycom HD Voice technology delivers life-like voice quality for each audio path-handset, the hands-free speakerphone, and the optional headset1

 i_{ℓ} ^{1/2} Polycom Acoustic Clarity technology providing full-duplex conversations, acoustic echo cancellation and background noise suppression - Type 1 compliant (IEEE 1329 full duplex) i_{ℓ} ^{1/2} Frequency response – 150 Hz – 7 kHz for handset, optional headset and hands-free speakerphone modes

ï¿1/2 Codecs: G.711 (A-law and μ-law), G.729AB, G.722, G.722, G.722.1C, iLBC

i¿1/2 Individual volume settings with visual feedback for each audio path

- ï¿1/2 Voice activity detection
- ï¿1/2 Comfort noise generation
- � DTMF tone generation (RFC 2833 and in-band)
- ï¿1/2 Low-delay audio packet transmission



i¿1/2 Adaptive jitter buffers i¿1/2 Packet loss concealment

Headset and handset compatibility

ï¿1/2 Dedicated RJ-9 headset port

- ï¿1/2 Hearing aid compatibility ITU-T P.370 and TIA 504A standards
- ï¿¹/₂ Compliant with ADA Section 508 Subpart B 1194.23 (all)
- ï¿1/2 Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
- ïزئ Compatible with commercially-available TTY Adapter equipment

Call handling features

- ï¿1/2 12 lines (programmable line keys)
- ï¿1/2 Shared call/bridged line appearance
- � Flexible line appearance (one or more line keys can be assigned for each line extension)
- ï¿1/2 Distinctive incoming call treatment/call waiting
- ï¿1/2 Call timer and call waiting
- ï¿1/2 Call transfer, hold, divert (forward), pickup
- ï¿¹/₂ Called, calling, connected party information
- ï¿1/2 Local three-way audio conferencing
- ï¿1/2 One-touch speed dial, redial
- ï¿1/2 Remote missed call notification
- ï¿1/2 Do not disturb function
- ï¿1/2 Electronic hook switch capable
- ï¿1/2 Local configurable digit map/dial plan

Open Application Form

ïزئ WebKit enabled full browser that supports HTML5, CSS, SSL security, and JavaScript

- i¿1/2 Supports Polycom Apps SDK and API for third-party business and personal applications
- ï¿1/2 Bundled with Polycom UC Software:
- ï¿1/2 Corporate Directory Access using LDAP
- ï¿1⁄2 Local Voice Call Recording on USB flash drive

ï¿1/2 Visual Conference Management

Network and Provisioning

ï¿1/2 SIP Protocol Support

� SDP

ï¿1/2 IETF SIP (RFC 3261 and companion RFCs)

ï¿1/2 Two-port Ethernet switch

ï¿1/2 10/100Base-TX across LAN and PC ports

ïزئ Conforms to IEEE802.3-2005 (Clause 40) for Physical Media Attachment

ïزئ Conforms to IEEE802.3-2002 (Clause 28) for link Partner Auto-Negotiation

 $i_{\ell}i_{2}^{1/2}$ Manual or dynamic host configuration protocol (DHCP) network setup $i_{\ell}i_{2}^{1/2}$ Time and date synchronization using SNTP



ï¿1/2 FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments

ï¿¹/₂ Provisioning and call server redundancy supported2

ïزئ QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP

iز 1/2 VLAN-CDP, DHCP VLAN discovery, LLDP-MED for VLAN discovery

� Network Address Translation (NAT) – support for static configuration and "Keep-Alive" SIP signaling

- ï¿1/₂ RTCP and RTP support
- ï¿1∕2 Event logging
- � Syslog
- ï¿1/2 Hardware diagnostics
- ï¿1/2 Status and statistics reporting
- ï;½ IPv4
- � TCP
- � UDP � DNS-SRV

Security

- ï¿1/2 802.1X Authentication and EAPOL
- ï¿1/2 Media encryption via SRTP
- ï¿1/2 Transport Layer Security (TLS)
- ï¿1/2 Encrypted configuration files
- ï¿1/2 Digest authentication
- ï¿1∕2 Password login
- ï¿1/2 Support for URL syntax with password for boot server address
- ï¿1/2 HTTPS secure provisioning
- ï¿1/2 Support for signed software executables

Power

ïزئ Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 2)

- ï¿1/2 Energy-saving after hours mode
- ï¿1/2 External Universal AC Adaptor (optional) 48VDC; 12W

Approvals

Safety



i¿¹⁄₂ UL 60950-1 i¿¹⁄₂ CE Mark i¿¹⁄₂ CAN/CSA C22.2 No. 60950-1 i¿¹⁄₂ EN 60950-1 i¿¹⁄₂ IEC 60950-1 i¿¹⁄₂ AS/NZS 60950-1 i¿¹⁄₂ ICASA (add) i¿¹⁄₂ CITC (add)

Operating Conditions

i¿½ Temperature: 0 to 40°C (+32 to 104°F) i¿½ Relative Humidity: 5% to 95%, noncondensing

Storage Temperature

ï¿1/2 40 to +70°C (-40 to +160°F)

Price: £155.60

Options available for Polycom VVX 400 Skype For Business Edition Gigabit Media Phone (VVX400) :

Require Power Supply

Not Required, Universal 12V, 0.5A Power supply (+£15.10).