



Product Name: Polycom VVX 501 Skype For Business Edition Gigabit Media Phone (VVX501) Manufacturer: -

Model Number: 2200-48500-019

Please Note: This item has been discontinued. See the Poly VVX 301 for an alternative.

Please Note: Polycom VVX IP Phones are PoE (Powered-Over-Ethernet) and do not include a mains Power Supply. If mains power is required, this can be added via the drop down menu above.

Polycom VVX 501 Skype For Business Edition Gigabit Media Phone - Enhanced processor and memory

The Polycom VVX 501 Skype For Business Edition is a high-end VoIP desktop phone, perfect for any power-user or executive. With Polycom's HD Voice and Acoustic Clarity technology, you can be sure of crisp and loud sound quality on any phone call. This version of the VVX 501 is compatible with the Skype for Business service. This entry level 'always on' phone enhances your communications options over just using a Skype for a Business client with a headset.

Polycom VVX 501 Skype For Business Edition Key Features

- ï¿¹/₂ Compatible with Skype for Business / Lync
- ï¿1/2 Professional VoIP Desktop Phone

ï¿1/2 12 lines

- ï¿1/2 2 Gigabit Ethernet ports
- ï¿1/2 Enhanced processor and memory over the VVX 500
- ï¿1/2 3.5" touchscreen display
- ï¿1/2 HD Voice & amp; full duplex speakerphone
- ï¿1/2 USB & amp; RJ9 headset jack

Polycom VVX 501 Skype For Business Edition - Technical Specifications User interface features

ï¿1/2 Gesture-based, multitouch-capable, capacitive touch-screen

- ï¿1/2 3.5-in TFT LCD display at QVGA (320 x 240 pixel) resolution, 4:3 aspect ratio
- ï¿1/2 Screensaver and digital picture frame mode
- ï¿1/2 On-screen virtual keyboard
- ï¿1/2 Voicemail and videomail support1
- ï¿1/2 Dual USB ports (2.0 compliant) for media and storage applications
- ï¿1/2 WebKit-based browser

ï¿1/2 Adjustable base height

� Unicode UTF-8 character support.Multilingual user interface includingChinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian,Japanese, Korean, Norwegian, Polish,Portuguese, Russian, Slovenian, Spanishand Swedish

Audio features

 i_{ℓ} Polycom® HD Voice™ technology delivers life-like voice quality for each audio patch handset, the hands-free speakerphone and the optional headset

� Polycom® Acoustic Clarity™ technology, providing full-duplex conversations, acoustic echo cancellation and background noise suppression-- Type 1 compliant (IEEE 1329 full



duplex)

ï¿1/2 Frequency response: 100 Hz–20 kHz for handset, optional headset and hands-free speakerphone modes

- ï¿1/2 Codecs: G.711 (A-law and μ-law), G.729AB, G.722, G.722.1, G.722.1C
- ï¿1/2 Individual volume settings with visual feedback for each audio path
- ï¿1/2 Voice activity detection
- ï¿1/2 Comfort noise generation
- ï¿1/2 DTMF tone generation (RFC 2833 and in-band)
- ï¿1/2 Low-delay audio packet transmission
- ï¿1/2 Adaptive jitter buffers
- ï¿1/2 Packet loss concealment

Headset and handset compatibility

ï¿1/2 Dedicated RJ-9 headset port

ï¿1/2 Hearing aid compatibility to ITU-T P.370 and TIA

� 504A standards

ï¿1/2 Compliant with ADA Section 508 Subpart B 1194.23 (all)

- i¿1/2 Hearing aid compatible handset for magnetic coupling to hearing aids
- ïزئ Compatible with commercially available TTY adapter equipment
- ï¿¹/₂ Supports compatible USB headsets

Call handling features1

- ï¿1/2 12 lines (registrations)
- ï¿1/2 Up to 24 simultaneous calls
- ï¿1/2 Shared call/bridged line appearance
- ïزئ Flexible line appearance (1 or more line keys can be assigned for each line extension)
- ï¿1/2 Distinctive incoming call treatment/ call waiting
- ï¿¹/₂ Call timer and call waiting
- ï¿¹/₂ Call transfer, hold, divert (forward), pickup
- ï¿1/2 Called, calling, connected party information
- ï¿1/2 Local 3-way audio conferencing
- ï¿1/2 1-touch speed dial, redial
- ï¿1/2 Remote missed call notification
- ï¿1/2 Do not disturb function
- ï¿1/2 Electronic hook switch capable
- ï¿1/2 Local configurable digit map/dial plan

Open application platform

i¿½ WebKit-enabled full browser that supports HTML5, CSS, SSL security and JavaScript
 i¿½ Supports Polycom Apps SDK and API for third-party business and personal applications
 i¿½ Bundled with Polycom Productivity Suite:-- Corporate directory access using LDAP-- Local voice call recording on USB flash drive-- Visual conference management

Network and Provisioning

i¿½ Network (LAN) cable - CAT-5E
i¿½ SIP protocol support
i¿½ SDP
i¿½ IETF SIP (RFC 3261 and companion RFCs)
i¿½ Two-port Gigabit Ethernet switch-- 10/100/1000Base-TX across LAN and PC ports--



Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment-- Conforms to IEEE802.3-2002 (Clause 28) for link

ï¿1/2 Partner auto-negotiation

i¿1/2 Manual or dynamic host configuration protocol (DHCP)

ï¿1/2 DHCP network setup

ï¿¹/₂ Time and date synchronization using SNTP

ïز1/2 FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments

i¿1/2 Provisioning and call server redundancy supported1

ï¿1/2 QoS support—IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DSCP

ïزئ VLAN—CDP, DHCP VLAN discovery, LLDP- MED for VLAN discovery-- Network

address translation support for static configuration and "Keep-Alive"

ï¿¹∕₂ RTCP and RTP support

� Event logging

� Syslog

ï¿1/2 Local configurable digit map/dial plan

ï¿1/2 Hardware diagnostics

ï¿1/2 Status and statistics reporting

� IPv4

TCP ₂⁄′غï

� UDP

� DNS-SRV

Security

ï¿1/2 802.1X authentication and EAPOL

ï¿1/2 Media encryption via SRTP

ï¿¹/₂ Transport layer security

ï¿1/2 Encrypted configuration files

ï¿1/2 Digest authentication

ï¿1∕2 Password login

 $\ddot{\imath}\dot{\imath}^{\prime\prime}_2$ Support for URL syntax with password for boot server address

ï¿1/2 HTTPS secure provisioning

ï¿1/2 Support for signed software executables

Approvals

ï¿1/2 FCC Part 15 (CFR 47) Class B ï¿1/2 ICES-003 Class B ï¿1/2 EN55022 Class B ï¿1/2 CISPR22 Class B i¿1/2 VCCI Class B � EN55024 ï¿1/2 EN61000-3-2; EN61000-3-3 i¿1/2 NZ Telepermit � Korea KC � UAE TRA � Russia CU � Brazil ANATEL � Australia RCM ï¿1/2 South Africa ICASA ï¿1/2 China CCC ï¿1/2 Saudi Arabia CITC



Safety

i¿½ UL 60950-1 i¿½ CE Mark i¿½ CAN/CSA-C22.2 No. 60950-1-03 i¿½ EN 60950-1 i¿½ IEC 60950-1 i¿½ AS/NZS 60950-1

Operating conditions

i¿½ Temperature: +32 to 104°F (0 to 40°C) i¿½ Relative humidity: 5% to 95%, noncondensing

Storage temperature

ï¿1/2 -40 to +160°F (-40 to +70°C)

Polycom® VVX® 500 Series comes with

i¿½ Polycom VVX 500 Series console i¿½ Handset with handset cord i¿½ Network (LAN) cable - CAT-5E i¿½ Quick start guide

Size

� 7.5 x 6 x 7 in (19 x 15 x 18 cm) (W x H x D)

Weight

ï¿1/2 Unit weight: 2.0 lbs (0.9 kg)

Unit box dimensions/weight

ī ¿½ 11.46 x 7.9 x 3.82 in (29.1 x 20 x 9.7 cm) ī ¿½ 3.1 lbs (1.4 kg)

Price: £213.40

Options available for Polycom VVX 501 Skype For Business Edition Gigabit Media Phone (VVX501) :

Require Power Supply

Universal 12V, 0.5A Power supply (+£15.10), Not Required.