

## Cisco 8845 SIP Video Phone



Product Name: Cisco 8845 SIP Video Phone

Manufacturer: Cisco Systems

Model Number: CP-8845

Please Note: The Cisco 8845 SIP Video Phone is PoE (Powered-Over-Ethernet) and does include a mains Power Supply. If mains power is required, this can be added via the drop down menu above.

### Cisco 8845 SIP Video Phone

The Cisco 8845 IP Video Phone forms part of the 8800 Series. It features a large 5" high-resolution colour display for increased productivity, as well as wideband audio for crystal clear voice communications and a 720p HD video camera for two-way video calling. This IP phone supports many advanced features including an in-built Gigabit Ethernet switch and Bluetooth capabilities. Cisco 8845 SIP Video Phone Features

- 5" high resolution colour display (800x480 pixel)

- 720p HD video

- 2x Gigabit Ethernet Switch

- PoE IEEE 802.3af/at Class 2 compliant (PSU available separately)

- Wideband audio (G.722)

- 5 SIP accounts (5 programmable line keys)

- Hands-free talking (speaker phone)

The Cisco 8845 supports five programmable line keys, which you can configure to support either multiple directory numbers or calling features such as speed dial / BLF.

Cisco 8845 - Table 1 lists features and benefits of the IP Phone 8845.

### Hardware Features

- Ergonomic design

- The phone offers an easy-to-use interface and provides a traditional telephony-like user experience

- Graphical display

- The 800 x 480, 24-bit color, 5-in. WVGA display provides scrollable access to calling features and textbased XML applications

- Video

- 720p HD video (encode and decode)

- H.264/AVC

- Handset

- The handset is a standard wideband-capable audio handset (connects through an RJ-9 port)

- The standard coiled cord has a custom end for concealed cable routing beneath the phone (cord length is approximately 21 in. [55 cm] coiled and up to 72 in. (183 cm) extended)

- The handset is hearing aid-compatible (HAC) and meets Federal Communications

## Cisco 8845 SIP Video Phone

Commission (FCC) loudness requirements for the Americans with Disabilities Act (ADA). You can achieve Section 508 loudness requirements with industry-standard inline handset amplifiers such as Walker Equipment W-10 or CE-100 amplifiers. The dial pad is also ADA-compliant

### 🔗 Speaker phone

🔗 A full-duplex speakerphone gives you flexibility in placing and receiving calls with hands free. For added security, the audible dual tone multifrequency (DTMF) tones are masked when the speakerphone mode is used.

### 🔗 Analog headset

🔗 The analog headset jack is a standard wideband-capable RJ-9 audio port

### 🔗 AUX port

🔗 You can use an auxiliary port to support electronic hookswitch control with a third-party headset connected to it

### 🔗 Ethernet switch

🔗 An internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000BASE-T Ethernet network (IEEE 802.3i/802.3u/802.3ab) through an RJ-45 interface with single LAN connectivity for both the phone and a co-located PC

🔗 The system administrator can designate separate VLANs (IEEE 802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic

### 🔗 Bluetooth

🔗 Bluetooth 4.1 LE, Enhanced Data Rate (EDR) Class 1 technology (up to 66-ft [20m] range) is supported

🔗 Hands-Free Profile (HFP) is supported for untethered headset connections and voice communications

🔗 Phone Book Access Profile (PBAP) is supported for phone book object exchange between devices

### 🔗 Keys

🔗 The phone has the following keys:

🔗 Line keys

🔗 Soft keys

🔗 Back and release keys

🔗 Four-way navigation and select keys

## Cisco 8845 SIP Video Phone

½ Hold/Resume, Transfer, and Conference keys

½ Messaging, Application, and Directory keys

½ Standard keypad

½ Volume-control toggle key

½ Speakerphone, headset, and mute key

½ Backlit indicator

½ The phone supports backlit indicators for the audio path keys (Handset, Headset, and Speakerphone), select key, line keys, and message waiting

½ Replaceable bezel

½ The phone includes a black bezel; an optional silver bezel is also orderable separately

½ Dual-position foot stand

½ The display is easy-to-view and the buttons and keys are easy-to-use. The two-position foot stand supports viewing angles of 35 and 50 degrees; you can remove the foot stand for wall mounting, with mounting holes located on the base of the phone

½ Wall-mountable

½ You can install the phone on a wall using an optional wall-mount kit (orderable separately)

½ Physical security

½ The phone is compatible with the Kensington Security Slot (K-Slot) antitheft system

### Power Features

½ IEEE Power over Ethernet (PoE)

½ PoE on the phone is IEEE Power over Ethernet class 2. The phone is compatible with both IEEE 802.3af and 802.3at switch blades and supports both Cisco Discovery Protocol and Link Layer Discovery Protocol -Power over Ethernet (LLDP-PoE)

## Cisco 8845 SIP Video Phone

### • Cisco IP Phone Power Cube 4

• This optional power cube is used as an AC-to-DC (48V) power supply for non-PoE deployments. Use of the power cube 4 also requires the use of one of the corresponding AC country cords

### Call-Control Support

#### • Cisco Unified Communications Manager

• 8.5.1 (non-secured mode only)

• 8.6.2

• 9.1.2

• 10.5.2

• 11.0 and later

#### • Cisco Unified Communications Manager Express (Unified CME)

• Planned to be supported 11.5

#### • Cisco Business Edition 6000 (BE 6000)

• 8.6.2

• 9.1.2

• 10.5.2

• 11.0 and later

#### • Cisco Hosted Collaboration Solution (HCS)

• 8.6.2 and later (using supported UCM versions listed previously)

Cisco 8845 - Table 2 lists the features and specifications of the 8845.  
Features

#### • Audio codec support

• G.711a-law and mu-law, G.722, G.729a, Internet Low Bitrate Codec (iLBC), and Internet Speech Audio Codec (iSAC)

#### • Call features

• + Dialing

• Abbreviated dialing

• Adjustable ring tones and volume levels

## Cisco 8845 SIP Video Phone

- ½ Adjustable display brightness
- ½ Agent greeting
- ½ Application launch pad
- ½ Auto-answer
- ½ Auto-detection of headset
- ½ cBarge
- ½ Busy Lamp Field (BLF)
- ½ BLF Pickup
- ½ BLF speed dial
- ½ Callback
- ½ Call forward
- ½ Call forward notification
- ½ Call filter
- ½ Call history lists
- ½ Call park
- ½ Call pickup
- ½ Call timer
- ½ Call waiting
- ½ Call chaperone
- ½ Caller ID
- ½ Corporate directory
- ½ Conference, including traditional Join feature
- ½ Cross-Cluster Extension Mobility (EMCC)
- ½ Direct transfer
- ½ Extension mobility
- ½ Fast-dial service
- ½ Forced access codes and client matter codes
- ½ Group call pickup
- ½ Hold
- ½ Intercom
- ½ Immediate divert
- ½ Malicious-caller ID
- ½ Message-waiting indicator (MWI)
- ½ Meet-me conference
- ½ Mobility
- ½ Music on hold (MoH)
- ½ Mute
- ½ Network profiles (automatic)
- ½ On- and off-network distinctive ringing
- ½ Personal directory
- ½ PickUp
- ½ Predialing before sending
- ½ Privacy
- ½ Private Line Automated Ringdown (PLAR)
- ½ Redial
- ½ Ring tone per line appearance
- ½ Service Uniform Resource Locator (URL)
- ½ Shared line
- ½ Silent monitoring and recording
- ½ Speed dial
- ½ Time and date display
- ½ Transfer
- ½ Uniform Resource Identifier (URI) dialing
- ½ Visual Voicemail
- ½ Voicemail

## Cisco 8845 SIP Video Phone

### ½ Whisper coaching

½ Mobility and remote access You can deploy the phones remotely with the following two options:

½ You can have your phone remotely registered to the on-premises network through a built-in VPN client if the administrator has provisioned this VPN feature

½ You also can directly connect to the on-premises network without VPN through Cisco Expressway if you are provided with log-in credentials. Contact your system administrator

### ½ Electronic hookswitch

½ You can control the hookswitch electronically with a third-party headset connected to the auxiliary port.

### ½ Cisco Intelligent Proximity

½ Audio path moving sends audio through the IP Phone 8861 for a mobile device-connected call

½ Call-history synchronization allows you to view placed and missed calls of your mobile device from the IP Phone 8845

½ Contact synchronization allows you to synchronize the contact objects from your mobile device to your 8845

### ½ Quality-of-service (QoS) options

½ The phone supports Cisco Discovery Protocol and 802.1Q/p standards, and you can configure it with an 801.1Q VLAN header containing the VLAN ID overrides configured by the Admin VLAN ID

### ½ Network features

½ Session Initiation Protocol (SIP) for signaling

½ Session Description Protocol (SDP)

½ IPv4 and IPv6

½ User Datagram Protocol (UDP) (used only for Real-Time Transport Protocol [RTP] streams)

½ Dynamic Host Configuration Protocol (DHCP) client or static configuration

½ Gratuitous Address Resolution Protocol (GARP)

½ Domain Name System (DNS)

½ Trivial File Transfer Protocol (TFTP)

½ Secure HTTP (HTTPS)

½ VLAN

½ Real-Time Transport Protocol (RTP)

½ Real-Time Control Protocol (RTCP)

½ Cisco Peer-to-Peer Distribution Protocol (PPDP)

½ Cisco Discovery Protocol

½ LLDP (including LLDP Media Endpoint Discovery [LLDP-MED])

½ Switch speed auto-negotiation

## Cisco 8845 SIP Video Phone

### Security features

- Secure boot
- Secure credential storage
- Device authentication

- Configuration file authentication and encryption
- Image authentication
- Random bit generation
- Hardware cryptographic acceleration
- Certificate Authority Proxy Function (CAPF)
- Manufacturer-Installed Certificates (MIC)
- Locally Significant Certificates (LSC)
- Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) and Extensible Authentication Protocol-Transport Layer Security (EAP-TLS)
- Signaling authentication and encryption using TLS
- Media authentication and encryption using SRTP
- HTTPS for client and server
- Secure Shell (SSH) Protocol server
- SSL-based VPN client

### Physical dimensions (H <math>\times</math> W <math>\times</math> D)

- 9.01 x 10.13 x 3.87 in. (228.78 x 257.34 x 98.39 mm) (excluding foot stand)

### Weight (with handset)

- 2.97 lb (1.35 kg)

### Phone-casing composition

- Polycarbonate acrylonitrile butadiene styrene (ABS) textured plastic; Cosmetic class A

### Operating temperature

- 32 to 104<math>^{\circ}</math>F (0 to 40<math>^{\circ}</math>C)

### Nonoperating temperature shock

- 14 to 140<math>^{\circ}</math>F (-10 to 60<math>^{\circ}</math>C)

### Humidity

- Operating 10 to 90%, noncondensing
- Nonoperating 10 to 95%, noncondensing

## Cisco 8845 SIP Video Phone

### ½ Language support

- ½ Arabic (Arabic Area)
- ½ Bulgarian (Bulgaria)
- ½ Catalan (Spain)
- ½ Chinese (China)
- ½ Chinese (Hong Kong)
- ½ Chinese (Taiwan)
- ½ Croatian (Croatia)
- ½ Czech (Czech Republic)
- ½ Danish (Denmark)
- ½ Dutch (Netherlands)
- ½ English (United Kingdom)
- ½ Estonian (Estonia)
- ½ French (France)
- ½ French (Canada)
- ½ Finnish (Finland)
- ½ German (Germany)
- ½ Greek (Greece)
- ½ Hebrew (Israel)
- ½ Hungarian (Hungary)
- ½ Italian (Italy)
- ½ Japanese (Japan)
- ½ Latvian (Latvia)
- ½ Lithuanian (Lithuania)
- ½ Korean (Korea Republic)
- ½ Norwegian (Norway)
- ½ Polish (Poland)
- ½ Portuguese (Portugal)
- ½ Portuguese (Brazil)
- ½ Romanian (Romania)
- ½ Russian (Russian Federation)
- ½ Spanish (Columbia)
- ½ Spanish (Spain)
- ½ Slovak (Slovakia)
- ½ Swedish (Sweden)
- ½ Serbian (Republic of Serbia)
- ½ Serbian (Republic of Montenegro)
- ½ Slovenian (Slovenia)
- ½ Thai (Thailand)
- ½ Turkish (Turkey)

### ½ Certification and compliance

#### ½ Regulatory compliance

- ½ CE Markings per directives 2004/108/EC and 2006/95/EC
- ½ Safety

- ½ UL 60950 Second Edition
- ½ CAN/CSA-C22.2 No. 60950 Second Edition
- ½ EN 60950 Second Edition (including A11 and A12)
- ½ IEC 60950 Second Edition (including A11 and A12)
- ½ AS/NZS 60950

## Cisco 8845 SIP Video Phone

ȧ½ GB4943

ȧ½ EMC - Emissions

ȧ½

ȧ½ 47CFR Part 15 (CFR 47) Class B

ȧ½ AS/NZS CISPR22 Class B

ȧ½ CISPR22: 2005 w/Amendment 1: 2005 Class B

ȧ½ EN55022: 2006 w/Amendment 1: 2007 Class B

ȧ½ ICES003 Class B

ȧ½ VCCI Class B

ȧ½ EN61000-3-2

ȧ½ EN61000-3-3

ȧ½ KN22 Class B

ȧ½ EMC - Immunity

ȧ½ EN55024

ȧ½ CISPR24

ȧ½ EN60601-1-2

ȧ½ KN24

ȧ½ Armadillo Light

ȧ½ Telecom

ȧ½ FCC Part 68 HAC

ȧ½ CS-03-HAC&#9702;

ȧ½ AS/ACIF S004

ȧ½ AS/ACIF S040

ȧ½ NZ PTC 220

ȧ½ Industry standards: TIA 810 and TIA 920

ȧ½ Industry standards: IEEE 802.3 Ethernet and IEEE 802.3af and 802.3at

ȧ½ Korea (RRA Public Notification 2010-36, Nov. 1, 2010)

ȧ½ Korea (RRA Announce 2011-2, Feb. 28, 2011)

ȧ½ Radio

ȧ½ FCC Part 2.1093 (BT RF Exposure TR)

ȧ½ RSS-102 (BT RF Exposure TR)

ȧ½ RSS-210

ȧ½ EN 300.328

ȧ½ EN50385 (BT RF Exposure TR)

ȧ½ EN 301-489-1

ȧ½ EN 301-489-17

ȧ½ NCC LP0002

ȧ½ Korea (RRL No. 2006-128, RRL No. 2006-129)

ȧ½ Japan Bluetooth GFSK/EDR

## Cisco 8845 SIP Video Phone

**Please Enquire**

---

Options available for Cisco 8845 SIP Video Phone :

**Power Supply Required**

[Cisco Power Cube 4 with UK Cord \(+£19.00\)](#), [Not Required](#).