

# **Polycom RealPresence Trio 8800 Collaboration Kit**



Product Name: Polycom RealPresence Trio 8800 Collaboration Kit Manufacturer: -Model Number: 7200-23450-001

Please Note: This product has been discontinued. Please see the Polycom Trio 8800 Collaboration Kit, EagleEye Mini, with 1 year premier support (7200-853-001) as an alternative.

Polycom RealPresence Trio 8800 Collaboration Kit The Polycom RealPresence Trio 8800 Collaboration Kit is the perfect smart hub for group collaboration that transforms the iconic three-point conference phone into a voice, video, and content sharing system, that can fit into any team environment, large or small. Polycom RealPresence Trio 8800 Collaboration Kit Key Features

i¿½ Includes: Trio 8800, TrioVisual+, Logitech Webcam C930e, and 1 yr Partner Premier i¿½ Built-in Power over Ethernet (PoE) i¿½ Digital Signaling Protocol: SIP

Polycom RealPresence Trio 8800 Collaboration Kit - Technical Specifications General

� Device Type: Video Conferencing Kit
� VoIP Protocols: SDP
� Digital Signaling Protocol: SIP
� Data Compression Protocol: G.711, G.722, G.729.A, G.729.B, G.722.1, G.722.1C
� Features: Auto gain control, echo cancellation
� Audio Input: Three microphones
� Networking: Network adapter - Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b,
IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, Bluetooth 4.0, NFC
� Bundled with: Trio Visual+, Logitech C930e
� Built-in Devices: 5" touch screen display
� Device Type: Video Conferencing Kit
� Dimensions & amp; Weight (Main system)
� Width 7.5 cm

i¿½ Width 7.5 cm i¿½ Depth 38.3 cm i¿½ Height 33.2 cm i¿½ Weight 950 g

i¿½ Security: WPA, WEP, WPA2 i¿½ VoIP Protocols: SDP i¿½ Frequency Response: 100 - 22000 Hz

**Environmental Conditions** 

� Humidity Range Operating: 5 - 95% (non-condensing)
 � Max Operating Temperature: 40 °C
 � Min Operating Temperature: 0 °C

Expansion/Connectivity

ïزن Interfaces: 1 x USB host - 4 pin USB Type A ¦ 1 x USB 2.0 - 5 pin Micro-USB Type B



¦ 2 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 ¦ 1 x camera -60 pin HDCI & brvbar; 2 x audio / video - HDMI output - 19 pin HDMI Type A & brvbar; 1 x serial -RS-232 - 8 PIN DIN & brvbar; 1 x audio - line-out - mini-phone stereo 3.5 mm

Additional Features

i¿1/2 Manufacturer Warranty Service & amp; Support: Limited warranty - 1 year i¿1/2 Compliant Standards: C-Tick, CISPR 22 Class B, EN55024, EN55022 Class B, ICES-003 Class B, FCC Part 15.247, AS/NZS 60950-1, MIC, FCC Part 15.225, RoHS, UL 60950-1, IEC 60950-1, EN 60950-1, AS/NZS 4268, A-Tick, FCC Part 15.407, CAN/CSA C22.2 No. 60950-1-03, VCCI Class B, EN61000-3-2, EN61000-3-3, ETSI EN 300 328 V1.9.1, ETSI EN 301 893 V1.7.1, ETSI EN 300 330, ETSI EN 301 489-3, ETSI EN 301 489-17 ï¿1/2 Mounting Kit: Included ï¿1/2 Data Compression Protocol: G.711, G.722, G.729.A, G.729.B, G.722.1, G.722.1C i¿1/2 Digital Signaling Protocol: SIP ï¿1/2 Features: Auto gain control, echo cancellation � Type: Wired Networking

i¿½ Compliant Standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3af, IEEE 802.1x, IEEE 802.3at ï¿1/2 Connectivity Technology: Wireless, wired i¿1/2 Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, Bluetooth 4.0, NFC i¿1/2 Features: Power over Ethernet (PoE), LDAP support, VLAN support, Wi-Fi Multimedia (WMM) support, Quality of Service (QoS), LLDP support, tagged VLAN, Power Sourcing Equipment (PSE), DiffServ Code Point (DSCP) support i¿1/2 Network / Transport Protocol: FTP, DHCP ï¿1/2 Type: Network adapter

## **Please Enquire**

Options available for Polycom RealPresence Trio 8800 Collaboration Kit :

### **Power Supply Required?**

Not Required, Required (+£113.60).